

# LifeBook S7021

- 14.1" Express Multimedia. Lighter than 1.8kg\*
- Uncompromised Security with Fingerprint Recognition Technology
- Health and Environment friendliness with RoHS<sup>9</sup> compliance
- Multimedia on-the-go with SD/MS PRO/xD, Dual Layer DVD Super Multi Writer<sup>6</sup> option, color enhanced SuperFine display and quick multimedia playback buttons

\* with weight saver option



S7021 Recommended Configuration	
Platform	Intel® Centrino® Mobile Technology - Intel® Pentium® M Processor 750/740 <sup>10</sup> - Intel® PRO/Wireless 2915ABG/2200BG Network Connection - Intel® 915GM Express Chipset
OS Supported	Windows® XP Home Edition Windows® XP Professional
Display	14.1" SuperFine XGA TFT, 1024 x 768 pixels
Modular Bay Device	DVD/CD-RW Combo Drive
Memory	512MB DDR2 533MHz
Hard Disk	80GB
Battery	Up to 4.3hrs (6-cell Li-Ion 5200mAh)
Weight	Approx. 1.75kg (w/ Weight Saver Option)
Specifications	
Max. Memory Supported	2GB DDR2 533MHz, Dual Channel
Hard Disk Drive	Ultra ATA-100, S.M.A.R.T. support, Two Partitions - 50/50 <sup>8</sup>
Graphics	Integrated Intel® Graphics Media Accelerator 900 with DVMT <sup>3</sup> 3.0 delivers low-power, high-performance 2D/3D graphics, video and display capabilities at a maximum shared memory of 128MB
High Definition (HD) Audio	RealTek ALC260 HD audio codec with built-in dual stereo speakers and dual jacks HD Audio-in: Mic-in, Line-in HD Audio-out: Headphone-out, Line-out
Communication	56K V.92 <sup>2</sup> Global Modem MDC1.5, 1000/100/10Mbps <sup>4</sup> PCI Express® x1 Gigabit Ethernet and Intel® PRO/Wireless 2915ABG/2200BG network connection with Dual Antenna. Separate ON/OFF switch for wireless network connection
User Interface	Keyboard: 84-key, 19mm key pitch, 3mm key stroke Intelligent Touch Pad with configurable vertical and horizontal scroll functions Fingerprint Sensor with vertical scroll functions
Card Slot	PC Card Type II ExpressCard™/ 34/ 54 support Secured Digital/ Memory Stick® PRO/xD
Connector Interface	USB 2.0 x 3, VGA (external display), RJ45 (LAN), RJ11 (modem), IEEE1394, Mini S-Video out, HD Audio-in, HD Audio-out, Power Adapter DC-in
Quick Launch Panel	Four Programmable Application Launch Buttons (Internet, Email and two other software)
Media Playback Panel	Four Functions: Stop/ Eject, Play/Pause, Next, Previous
Security <sup>5</sup>	BIOS Lock, Hard Disk Lock, Anti-theft Lock Slot, Fingerprint Sensor
Dimensions	306mm (W) x 248mm (D) x 25.4mm (H)
Bundled Accessories	
AC Adapter	Input AC 100~240V, Output DC 19V 60W
Bundled Software	Softex OmniPass, CyberLink PowerDVD™, CyberLink PowerProducer™ 3, Roxio Digital Media SE, Roxio DLA, Adobe Acrobat Reader 6.0, Fujitsu Update Navi <sup>7</sup> , Fujitsu Hardware Diagnostic Tool, Fujitsu Display Manager
Software on CD	1 year Full Licensed Norman Virus Control with Sandbox Technology, Norman Personal Firewall, Acronis True Image 8.0 Personal Edition
Optional Accessories	
Modular Bay Options	Replaceable with - Bay Battery, 6-cell Li-Ion 3800mAh, up to 7.2hrs <sup>1</sup> battery life (Standard + Bay Batteries) - Dual Layer DVD Super Multi Writer <sup>6</sup> - DVD/CD-RW Combo Drive - Weight Saver
Mini S-Video Cable	Converts Mini S-Video out port to standard S-Video out port. Use a S-Video Cable for connection to a TV
Floppy Disk Drive	External USB 1.44MB FDD
Mouse	USB Optical Scroll Mouse

The above information shows the general technical specifications of the product and does not represent actual configuration. For specific configurations and their availability, please check with your local distributors.

- Results obtained from Mobile Mark 2002 performed on systems with maximum battery life settings. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences. Modular Bay devices or hard drive usage may also have a significant impact on battery life.
- Maximum 56Kbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.
- Dynamic Video Memory Technology (DVMT) dynamically responds to application requirement and efficiently allocates the proper amount of memory (max. 128MB) for optimal graphics and system performance. The memory size available to the Operating System will be less than the size of installed memory module.
- This term does not represent actual data rate of 1000/100/10Mbps and simply indicates compliance with IEEE 802.3, IEEE 802.3u and IEEE 802.3ab standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.
- BIOS Lock needs a supervisor/user password to access BIOS setup. BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setup is needed to configure Hard Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. Anti-theft Lock Slot allows the use of a lock to physically secure the LifeBook. Fingerprint Sensor uses AuthenTec TruePrint™ Technology and Softex OmniPass to remember customer list of user IDs and passwords.
- Supports DVD multi formats such as DVD-RAM, DVD+RW, DVD+R DL, DVD-R DL, DVD+R, DVD-RW, DVD-R, CD-RW, CD-R, CD-ROM and DVD-ROM.
- Update Navi is a Fujitsu Proprietary application that updates LifeBook drivers by connecting automatically to Fujitsu's server. This will help update your LifeBook with the latest software drivers and utilities to ensure compatibility between hardware and software, maintaining smooth operation anytime, anywhere.
- This refers to Window® XP hard disk drivers C:\ and D:\. 50/50 refer to approximate 50% allocation of user accessible hard disk storage to C:\ and D:\ drives.
- RoHS (Restriction on Hazardous Substances) compliance means the system and its internal components comply with the EU RoHS directive (2002/95/EC) on the restricted use of six hazardous substances in the manufacture of the system and its internal components.
- Configurations vary among countries. Please check with your local distributors for country's configurations. Intel® Pentium® M Processor 750 refers to (1.86GHz, 2MB L2 cache, 533MHz FSB), Intel® Pentium® M Processor 740 refers to (1.73GHz, 2MB L2 cache, 533MHz FSB).

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5~to 35°C / 41 to 95°F (operating), -10~to 60°C / 14 to 140°F (non-operating). Relative humidity: 20% to 80% RH (operating and non-operating).

"PCI Express" and the PCI Express design marks are registered trademarks and/or service marks of PCI-SIG.

Dolby and the double-D symbols are registered trademarks of Dolby Laboratories.



www.pc-ap.fujitsu.com

All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

Dealer:

## SINGAPORE:

**Fujitsu PC Asia Pacific Pte Ltd**  
Tel : (65) 6776 0688  
Fax : (65) 6776 0788

## MALAYSIA:

**Fujitsu PC Asia Pacific Pte Ltd**  
Tel : (60-3) 2093 3997  
Fax : (60-3) 2093 4245

## HONG KONG:

**Fujitsu PC Asia Pacific Ltd**  
Tel : (852) 3101 8133  
Fax : (852) 3101 0633

## THAILAND:

**Fujitsu Systems Business (Thailand) Ltd PC Division**  
Tel : (66-2) 263 7888  
Fax : (66-2) 263 7880

## AUSTRALIA & NEW ZEALAND:

**Fujitsu PC Australia**  
Toll Free: 1800 288 283  
Tel : (61-2) 8877 9500  
Fax : (61-2) 9889 3360  
[www.lifebook.com.au](http://www.lifebook.com.au)

## CHINA:

**Fujitsu PC China Division**  
Tel : (86-21) 3310 0808  
Fax : (86-21) 3310 0606  
[www.pc-cn.fujitsu.com](http://www.pc-cn.fujitsu.com)

## PHILIPPINES:

**Fujitsu Philippines Inc.**  
Tel : (63-2) 812 4001  
Fax : (63-2) 817 7576

## TAIWAN:

**Fujitsu Taiwan Ltd**  
Tel : (886-2) 2311 2255  
Fax : (886-2) 2311 2277

## VIETNAM:

**Fujitsu Vietnam Ltd**  
Tel : (84-4) 831 3895~7  
Fax : (84-4) 831 3898

## INDONESIA:

**PT Fujitsu Systems Indonesia**  
Tel : (62-21) 570 9330  
Fax : (62-21) 573 5150  
[www.fujitsu.com/id](http://www.fujitsu.com/id)

**Note:** For countries not listed above, please contact our Singapore office.