

## ESPRIMO™ Mobile V5535

- Designed for the value conscious mobile professional, ESPRIMO™ Mobile is the perfect synthesis of form, function and style.
- Enjoy the viewing quality of 15.4-inch wide format SuperFine WXGA TFT display
- High-speed connectivity everywhere with embedded LAN and WLAN



Specifications	
Platform	Intel® Pentium® dual core Processor T2330 (1.6GHz, 1MB L2 cache, 533 MHz FSB) - SiS M672 chipset
Operating System	Include Knoppix <sup>4</sup> Linux CD
Display	15.4-inch SuperFine WXGA TFT, 1280 x 800 pixels
Modular Bay Device	Dual Layer DVD Super Multi Writer
Memory	1GB DDR2 677MHz
Hard Disk	160GB
Battery	2hrs <sup>1</sup> (6-cell Li-Ion 2000mAh)
Weight	2.7kg
Detailed Specifications	
Hard Disk Drive	SATA (5400 rpm)
Graphics	SiS Mirage 3+ Graphics, up to a max. shared memory of 256MB
High Definition (HD) Audio	RealTek ALC268 HD Audio-in: Line-in, Microphone HD Audio-out: Line-out, Headphone
Communication	Built-in 10/100/1000 <sup>2</sup> Mbps SiS 196 LAN and Atheros BG WLAN network connection
User Interface	Keyboard: 86-key, 19mm keys pitch, 2.5mm key stroke Touch Pad with two mouse buttons
Card Slots	1 x ExpressCard™ 54/34mm slot
Connector Interface	USB 2.0 x 3, VGA (external display), RJ45 (LAN), Audio-in, Audio-out, Power Adapter DC-in
Security <sup>3</sup>	User and supervisor BIOS password, Anti-theft Lock Slot
Dimensions	360mm(W) x 260mm (D) x 39mm (H)
Bundled Accessories <sup>3</sup>	
AC Adapter	Input AC 100-240V, Output DC 20V/90W Adapter

#### HONG KONG (Head Office):

**Fujitsu PC**  
**Asia Pacific Ltd**  
 Tel : (852) 3101 8133  
 Fax : (852) 3101 0633  
[hk.fujitsu.com/pc](http://hk.fujitsu.com/pc)

#### AUSTRALIA & NEW ZEALAND:

**Fujitsu PC Australia**  
 Toll Free: (AU) 1800 288 283  
 (NZ) 0800 288 283  
 Fax : (61-2) 9889 3360

#### CHINA:

**Fujitsu PC China Division**  
 Tel : (86-21) 3310 9888  
 Fax : (86-21) 3310 0606  
[cn.fujitsu.com/pc](http://cn.fujitsu.com/pc)

#### INDIA:

**Fujitsu India Limited**  
 Tel : (91-11) 2370 6070  
 Fax : (91-11) 2370 6079

#### INDONESIA:

**Fujitsu Indonesia**  
 Tel : (62-21) 570 9330  
 Fax : (62-21) 573 5150

#### MALAYSIA:

**Fujitsu PC Asia Pacific Pte Ltd**  
 Tel : (60-3) 7728 4868  
 Fax : (60-3) 7728 4830  
[my.fujitsu.com/pc](http://my.fujitsu.com/pc)

#### PHILIPPINES:

**Fujitsu Philippines Inc.**  
 Tel : (63-2) 812 4001  
 Fax : (63-2) 817 7576  
[ph.fujitsu.com/pc](http://ph.fujitsu.com/pc)

#### SINGAPORE:

**Fujitsu PC Asia Pacific Pte Ltd**  
 Tel : (65) 6776 0688  
 Fax : (65) 6776 0788  
[sg.fujitsu.com/pc](http://sg.fujitsu.com/pc)

#### TAIWAN:

**Fujitsu Taiwan Ltd**  
 Tel : (886-2) 2311 2255  
 Fax : (886-2) 2311 2277

#### THAILAND:

**Fujitsu Systems Business (Thailand) Ltd PC Division**  
 Tel : (66-2) 263 7888  
 Fax : (66-2) 263 7880

#### VIETNAM:

**Fujitsu Vietnam Ltd**  
 Tel : (84-4) 831 3895  
 Fax : (84-4) 831 3898

Note: For countries not listed above, please contact our Hong Kong office.

The above information shows the general technical specifications of the product and does not represent actual configuration that would be sold in your region. For specific configurations and their availability, please check with your local distributors.

1. Results obtained from BAPCo® MobileMark® 2005 (Reader Workload) performed on systems with maximum battery life settings under laboratory testing environment. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences in real life situation.
2. This term does not represent actual data rate of 1000/100/10Mbps and simply indicates compliance with IEEE 802.3, IEEE 802.3u and IEEE 802.3ab standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices
3. Please check actual bundling / Specification with country local distributor.
4. Both the Knoppix Linux Operation System and its respective Drivers are not supported.

BAPCo® MobileMark® 2005 is the premier notebook battery life and performance under battery life metric based on real world applications for Windows® XP platforms.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C / 41 to 95°F (operating), -15° to 60°C / 5 to 140°F (non-operating). Relative humidity: 20% to 85% RH (operating), 8% to 85% RH (non-operating). Please note that GB = billion bytes. 1GB is equivalent to 1,073,741,824 bytes.



All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

Dealer: