

Datasheet FUJITSU Desktop ESPRIMO D7010

New small form factor PC in a more compact and space-saving design

The FUJITSU ESPRIMO D7010 Desktop is a high performance, secure small form factor PC with ultimate expandability, along with best-in-class connectivity. Faster operations and a new housing help in space saving to create the perfect working desk. The USB Type C, flexible graphics options offer great connectivity. The 80Plus GOLD and 80Plus PLATINUM power supply helps to reduce environmental impact and energy bills.

Latest Intel® Chipset technology and higher memory speed High performance ensures faster operations and lower system response time

- Intel® 8460 chipset with higher memory frequency of 2,933 MT/s
- Latest Intel® Chipset technology and higher memory speed

New housing and ultimate expandability

Easily customizable and expandable small form factor PC that enables more space saving

- 2x low profile (LP) or 1x LP/ 1x Full height (Riser) via BTO
- Space saving in width and depth with new 8.3 litres volume

Best-in-Class connectivity

Be flexible and stay productive in a hyper-connected world

- A Support of new USB Type C in front
- Flexible graphics options (VGA, DVI-D, HDMI, Type C)
- USB Type C support of 60W (optional to power a display)
- Legacy PS2, serial port, parallel port connectors as option

High security with integrated options

Designed to protect data and hardware components against manipulation and theft

- Cable cover in addition to existing Smartcard reader, Erasedisk software
- Integrated Cabinet lock with Master key option

Low Power Consumption; Easy serviceability and usability Reduced environmental impact and reduced energy bills; Features designed for easy access, control and use of the system

- 80Plus GOLD and 80Plus PLATINUM power supply efficiency with monitor outlet
- Tool-less access to components, easy change and Screw-less add on cards













Specification

Operating System pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business.
Operating system notes	Windows 10 support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details, please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at http://supports ts.fujitsu.com.
Processor	Intel® Core™ i9-10900 processor (10 Cores/ 20 Threads, 2.80 GHz, 20MB, Intel® UHD Graphics 630) ** Intel® Core™ i7-10700 processor (8 Cores/ 16 Threads, 2.90 GHz, 16 MB, Intel® UHD Graphics 630) ** Intel® Core™ i5-10600 processor (6 Cores/ 12 Threads, 3.30 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i5-10500 processor (6 Cores/ 12 Threads, 3.10 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i5-10400 processor (6 Cores/ 12 Threads, 2.90 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i3-10100 processor (4 Cores/ 8 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630) * *with Intel® Turbo Boost Technology 2.9 (clock speed and performance will vary depending on workload and other variables) **with Intel® Turbo Boost Max Technology 3.0 (clock speed and performance will vary depending on workload and other variables)
Ethernet (RJ-45)	
Memory modules	4GB (1 module(s) 4GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM 8GB (1 module(s) 8GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM 16GB (1 module(s) 16GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM 32GB (1 module(s) 32GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM
Mass storage 2.5 inch size	SSD SATA III, 512 GB, 2.5-inch SSD SATA III, 256GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch HDD SATA III, 500 GB, 5.4k rpm
Mass storage M.2 technology	SSD PCIe, 1024 GB M.2 NVMe module, SED SSD PCIe, 1024 GB M.2 NVMe module SSD PCIe, 512 GB M.2 NVMe module, SED SSD PCIe, 512 GB M.2 NVMe module SSD PCIe, 512 GB M.2 NVMe module SSD PCIe, 256 GB M.2 NVMe module, SED SSD PCIe, 256 GB M.2 NVMe module SSD PCIe, 128 GB M.2 NVMe module SSD PCIe, 128 GB M.2 NVMe module
Mass storage 3.5 inch size	HDD SATA III, 7,200 rpm, 2000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 1000 GB, 3.5-inch
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. SSD (Solid State Disk) SED (Self-Encrypting Drive)
Graphics	NVIDIA® Quadro® P400 LP, 2GB MiniDP to DP Adapter Cable
Drives	BD Triple Writer SATA ultra slim (tray) DVD Super Multi ultra slim (tray) SD Card reader
Interface add on cards/components	Gigabit Ethernet PCle x 1 WLAN 802.11ax (2x2) PCle x1 LP and Bluetooth 5.0, SRD 5.8GHz (dedicated regions only) Dual serial card PCle x1 LP



Base unit


Base unit	ESPRIMO D7010
Mainboard	ESI MINO D7010
Mainboard type	D3823-A2
Formfactor	
Chipset	Proprietary Intel® B460
Processor socket	LGA 1200
Processor quantity maximum	1
Supported capacity RAM (max.)	128 GB
Memory slots	4 DIMM (DDR4)
Memory frequency	2,933 MT/s
Memory notes	Dual channel support For dual channel performance, 2 memory modules must be ordered. Capacity per channel must be the same. 2933 MHz may be clocked down to 2400MHz depending on processor and memory configuration
LAN	10/100/1,000 Mbit/s Realtek RTL8111H
BIOS version	AMI Aptio V UEFI Specification 2.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extraosible Firmware Interface (UEFI)
Audio typo	Unified Extensible Firmware Interface (UEFI) On board
Audio type	Realtek ALC623
Audio codec Audio features	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound
	internal speaker supports audio piayback (optional), High Definition audio, 5.1 Suffound Sound
I/O controller on board	
Serial ATA total	4
Thereof SATA III	4
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI
late force	And
Interfaces	
Audio: line-in	1
Audio: line-out	1
Front audio: headset	
USB 2.0 total	4 Conditions
USB 3.2 Gen1 (5 Gbps) total	6 and 1 optional
USB 3.2 Gen2 (10 Gbps) total	2
USB front USB rear	2x USB 2.0; 1x USB 3.2 Gen1; 1x USB 3.2 Gen2; 1x USB 3.2 (Gen 2) Type-C (supports up to 15W) 2x USB 2.0; 4x USB 3.2 Gen 1; optional: additional 1x USB 3.2 Gen 1 Type-C (supports DisplayPort 1.4 and power
LICD :abases!	delivery (PD) up to 15W or 60W (occupies PCle x16 slot)
USB internal	1x USB 2.0 or 1x USB 3.2 Gen 1 Type A
VGA	optional
DisplayPort	2
DVI	Optional (DVI-D)
Serial (RS-232)	1 (optional serial port (9pin, 16 byte FIFO, 16550 compatible))
Mouse / Keyboard (PS/2)	2 (optional)
Ethernet (RJ-45)	1/ 1//25 :
Parallel	1 (optional) (25pin with EPP and ECP)
Interface Module notes	Anytime USB charge functionality
Kensington Lock support	I
Input device / components	
Input devices (optional)	Keyboard Mouse
Drive bays	
Drive bays total	3
2.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	1x internal 3.5" or 1x internal 2.5"
M.2-2280	1x on mainboard for SSD NVMe (PCle 3.0 x4; up to 32Gbit/s)
	· · · · · · · · · · · · · · · · · · ·



Slots	4 (450 4504 1)
PCI-Express 3.0 x4 (mech. x16)	1 x (150mm/ 5.91 inch)
PCI-Express 3.0 x16	1 x (210 mm/ 8.27 inch) Low profile or full height (via Riser card), optional
Graphics on board	
Graphics brand name	Intel® UHD Graphics 610, Intel® UHD Graphics 630
Shared video memory	Up to half size of total system memory
TFT resolution (VGA)	Up to 1,920 x 1,080 pixel
TFT resolution (DVI)	Up to 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel
TFT resolution (HDMI)	Up to 4,096 x 2,160 pixel (30Hz)
Graphics features	Support for up to three independent displays
	DirectX® 12
	HDCP support
	OpenCL™ 2.1
	OpenGL® 4.5
	For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.4 incl. Multi-Stream
	1 / 11
	Digital audio formats are supported, including Dolby Digital Plus (7.1 channels) DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cables (not
	included)
	Additional I/O connectors configurable, choice of
	DVI-D
	HDMI(RM)
	VGA
	USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 15W)
	USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 60W. Occupies PCle x16 slot)
Graphics notes	Up to 1GB dedicated video memory (main memory owned and locked for graphics use)
·	Tested resolutions, depending on display type additional resolutions and frequencies possible
	Shared memory depending on main memory size and operating system
	Resolution (colour depth up to 32 Bit/pixel)
	For TFT we recommend using 60Hz
Electrical values	
Power efficiency note	Power supply efficiency in % at 10% /20% /50% /100% load
	80Plus GOLD:
	For 230V; 87/90/92/91
	For 115V; 86/89/91/88
	CODE - DIATINUM
	80Plus PLATINUM:
	For 230V; 88/92/94/93
Rated voltage range	For 115V; 87/91/92/91 100V – 240V
Rated frequency range	50 Hz – 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz – 63 Hz
Max. output of single power	T/ IIL VJ IIL
supply	GOLD: 280W; PLATINUM: 300W
Power factor correction/active	
power	Active
Monitor outlet	Switched for PLATINUM power supply
Power consumption	
Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	https://docs.ts.fujitsu.com/dl.aspx?id=5d83ba46-8367-4613-9cee-40166b474f79
	mepsineous.comegnuecommencupatre outro outra out
Heat dissipation	Coa white caper Forces Consumption
Heat dissipation notes	Sea white paper Energy Consumption



Noise emission	
Related Processors for noise	Intel® Core™ i9-10900 processor and
	128GB, ODD; Windows 10 (tower position)
Standard noise emission	According to ISO 7779:2010, ECMA-74
Standard noise notes/ description	A-weighted sound power level Lwad (in B)/ Workplace related A-weighted sound pressure level LpAm (in db(A))
Chandred asias appearing made.	For GOLD PSU:
Standard noise operation mode:	3.1 B/ 18 db(A) Bystander; 18 db(A) Operator position (SSD M.2)
CPU 50% load	3.3 B/ 20 db(A) Bystander; 22 db(A) Operator position (SSD M.2 and 3.5" HDD)
Standard noise operation mode:	For GOLD PSU:
HDD mode	3.1 B/ 17 db(A) Bystander; 18 db(A) Operator position (SSD M.2)
	3.3 B/ 20 db(A) Bystander; 22 db(A) Operator position (SSD M.2 and 3.5" HDD)
Standard noise operation mode:	For GOLD PSU:
Idle mode	3.1 B/ 18 db(A) Bystander; 18 db(A) Operator position (SSD M.2)
	3.3 B/ 20 db(A) Bystander; 21 db(A) Operator position (SSD M.2 and 3.5" HDD)
Standard noise operation mode:	For GOLD PSU:
ODD load	4.5 B/ 31 db(A) Bystander; 37 db(A) Operator position (SSD M.2)
	4.5 B/ 32 db(A) Bystander; 36 db(A) Operator position (SSD M.2 and 3.5" HDD)
Standard noise operation mode:	For GOLD PSU:
Office Applications 2.0	3.1 B/ 18 db(A) Bystander; 18 db(A) Operator position (SSD M.2)
	3.3 B/ 20 db(A) Bystander; 21 db(A) Operator position (SSD M.2 and 3.5" HDD)
Dimensions / Weight / Environment	al
Dimensions (W x D x H)	314 x 296 x 89 mm
,	12.36 x 11.65 x 3.51 inch
Operating position	Horizontal / vertical (optional, feet needed)
Weight	Approx. 8 kg
Weight (lbs)	Approx. 17.64 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 − 35 °C (50 − 95 °F)
Operating relative humidity	5 – 85 % (relative humidity)
Compliance	3 03 % (Teledite Halliday)
Global	RoHS (Restriction of hazardous substances)
diobai	WEEE (Waste electrical and electronic equipment)
	Microsoft Operating Systems (HCT / HCL entry / WHQL)
	ENERGY STAR® 8.0, depending on configuration
	TCO Certified 8.0 (depending on configuration)
	EPEAT® Silver (dedicated regions), depending on configuration
	ENERGY STAR® compliance is an order option. Non-ENERGY STAR/ TCO/ EPEAT compliant products are marked at
	brand name with additional suffix "n".
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
<u>'</u>	nttps://sp.cs.tujicsu.com/sites/certificates
Additional Software	
Additional software (preinstalled)	Adobe® Reader® (pdf reader)
	McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial preinstalled)
A L l':: 1 (6 / .: 1)	Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows®
	Drivers & Utilities DVD (DUDVD)
	CyberLink PowerDVD BD (playback software for Blu-ray Disc™)
	CyberLink PowerDVD DVD (playback software for DVD)
	Nero Essentials XL
	Microsoft® Office Professional 2019
	Microsoft® Office Home and Business 2019
	(A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the
	region in which it was acquired.)





Manageability	
,	DeskUpdate Driver management
	PXE 2.1 Boot code
Manageability technology	Wake up from S5 (off mode)
	Intrusion switch (optional)
	WoL (Wake on LAN)
Manageability software	DeskView Client
	DeskView Instant BIOS Management
DeskView components	BIOS Management incl. Security
	Inventory Management
	Driver Management
	Alarm Management
Supported standards	DMI (Desktop Management Interface)
	SMBIOS (System Management BIOS)
	PXE (Preboot Execution Environment)
	WMI (Windows Management Instrumentation)
	WBEM (Web Based Enterprise Management)
AA Late to t	CIM (Common Information Model)
Manageability link	https://www.fujitsu.com/fts/manageability
Security Device I Consider	Vascinates Ladi sussest
Physical Security	Kensington Lock support
	Eye for padlock
	Integrated cabinet lock (optional)
Custom and DIOC Conveits	Cable Cover (optional; covers and secures the ports and cables on rear side)
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk
	Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME) Modern Standby ready (for configurations with NVMe SSD and w/o PCIe cards)
	Write protect option for the Flash EPROM
	Control of all USB interfaces
	External USB ports can be disabled separately
	Control of external interfaces
User Security	User and supervisor BIOS password
oser security	Hard disk password
	Access protection via external SmartCard reader (optional)
	Access protection via internal SmartCard reader (optional)
	AuthConductor Client Basic (secure authentication solution)
Packaging information	
Packaging dimension (mm)	499 x 296 x 439 mm
Packaging dimension (inch)	19.65 x 11.65 x 17.28 inch
Max. quantity/ pallet	24
Material – Weight (g) Carton	1117 g
Material – Weight (lbs) Carton	2.46 lbs
Material – Weight (g) EPS / PS	225 g
Material – Weight (lbs) EPS / PS	0.5 lbs
Material – Weight (lbs) PE	25g
Material – Weight (lbs) PE	0.06 lbs
Packaging notes	Printed user documentation is bleached in chlorine free process;
	Bulk packaging for projects (optional)
Warranty	
Warranty period	1 year
Warranty type	Bring-In / Onsite Service (depending on country)
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years

FUJITSU

More information

Fujitsu OPTIMIZATION solutions

In addition to Fujitsu Desktop ESPRIMO D7010, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products https://www.fujitsu.com/hk/products/computing/pc/

Software www.fujitsu.com/software/

Contact Us

HONG KONG Fujitsu Business Technologies Asia Pacific Ltd. Tel: (852) 3910-8228 Email: fpca.hksales@hk.fujitsu.com hk.fujitsu.com/pc

INDONESIA PT Fujitsu Indonesia Tel: (62) 21-570-9330 Email: marketing@id.fujitsu.com id.fujitsu.com/pc

TAIWAN
Fujitsu Taiwan Ltd.
Tel: (886) 2-2311-2255
Email: ftl.lifebook@fujitsu.com
tw.fujitsu.com/pc

More information

To learn more about Fujitsu Desktop ESPRIMO D7010, please contact your Fujitsu sales representative, Fujitsu Business partner, or visit our website.

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at http://www.fujitsu.com/global/about/environment/



SINGAPORE Fujitsu Asia Pte Ltd. Tel: (65) 6512-7555 Email: fapl.info@fujitsu.com sg.fujitsu.com/pc

PHILIPPINES Fujitsu Philippines, Inc. Tel: (63) 2-8841-8488 Email: info.fpi@fujitsu.com ph.fujitsu.com/pc

THAILAND
Fujitsu (Thailand) Co., Ltd.
Tel: (66) 0-2302-1500
Email: info.th@fujitsu.com
th.fujitsu.com/pc

Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms © 2020 Fujitsu Business Technologies Asia Pacific Limited

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CHINA
Fujitsu (China) Holdings Co., Ltd. –
PC China Division
Tel: 86 (21) 58871000-8721
Email: fpcacn.support@cn.fujitsu.com
cn.fujitsu.com/pc

MALAYSIA Fujitsu (Malaysia) Sdn. Bhd Tel: (60) 3-8230-4188 Email: askfujitsu.my@fujitsu.com my.fujitsu.com/pc

VIETNAM Fujitsu Vietnam Limited Tel: (84-24) 2220-3113 Email: sales-vn@fujitsu.com vn.fujitsu.com/pc

Note: For countries not listed above, please contact our Hong Kong office.

Specification disclaimers

Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. ⁷ (B = 1 billion bytes. TB = 1 trillion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on main memory sizes. ⁸ the possible of possible in a possible capacity may vary, also depending on main memory sizes. ⁸ the possible in a possible in specific countries only. It requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. Please contact our Fujitsu sales specialist for more information. ⁸ Interfaces depend on the configuration selected by customers. ⁸ Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2018 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. ²-cell battery will only be available in specific countries/ regions. For more detail, please contact Fujitsu sales specialist. ⁷The stated thickness does not include rubber feet.

FUJITSU shall not be liable for technical or editorial errors or omissions contained herein. Ultrabook, Celeron, Celeron Inside, Intel, Intel Logo, Intel Atom, Intel Atom, Intel Atom, Intel Core, Intel Inside, Intel Inside, Logo, Intel Norm, Itanium, Itan

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms.

© 2021 Fujitsu Business Technologies Asia Pacific Limited

Last Update: 13th May 2021