Datasheet FUJITSU Desktop ESPRIMO D7010/8

New small form factor PC in a more compact and space-saving design

The FUJITSU ESPRIMO D7010/8 Desktop is a high performance, secure small form factor PC with ultimate expandability, along with best-in-class connectivity. Faster operations and a new housing help in space saving to create the perfect working desk. The USB Type C, flexible graphics options offer great connectivity. The 80Plus GOLD and 80Plus PLATINUM power supply helps to reduce environmental impact and energy bills.

Latest Intel® Chipset technology and higher memory speed

- High performance ensures faster operations and lower system response time
- Intel[®] B460 chipset with higher memory frequency of 2,933 MT/s

New housing and ultimate expandability

Cost-effective small form factor PC that enables more space saving

- 1 x low profile (LP)
- Space saving in width and depth with new 8.3 litres volume

Good connectivity

Be flexible and stay productive in a hyper-connected world

- 4 x USB Type A ports
- USB and audio port in front for easy access
- Legacy PS2 connectors as option

High security with integrated options

Designed to protect data and hardware components against manipulation and theft

- Cable cover in addition to existing Smartcard reader, EraseDisk software
- Hole for pad lock and Kensington as standard for security
- Embedded security with TPM 2.0

Low Power Consumption

Reduced environmental impact and reduced energy bills

80Plus GOLD and 80Plus PLATINUM power supply efficiency with monitor outlet









Components



Operating System pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business.
Operating system notes	Windows 10 support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details, please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at http://supports ts.fujitsu.com.
Processor	Intel® Core™ i9-10900 processor (10 Cores/ 20 Threads, 2.80 GHz, 20MB, Intel® UHD Graphics 630) **
	Intel® Core™ i7-10700 processor (8 Cores/ 16 Threads, 2.90 GHz, 16 MB, Intel® UHD Graphics 630) **
	Intel® Core™ i5-10600 processor (6 Cores/ 12 Threads, 3.30 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i5-10500 processor (6 Cores/ 12 Threads, 3.10 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i5-10400 processor (6 Cores/ 12 Threads, 2.90 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i3-10100 processor (4 Cores/ 8 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630) *
	*with Intel® Turbo Boost Technology 2.9 (clock speed and performance will vary depending on workload and other variables)
	**with Intel® Turbo Boost Max Technology 3.0 (clock speed and performance will vary depending on workload and
	other variables)
Ethernet (RJ-45)	
Memory modules	4GB (1 module(s) 4GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM
	8GB (1 module(s) 8GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM
	16GB (1 module(s) 16GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM
	32GB (1 module(s) 32GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM
Mass storage 2.5 inch size	SSD SATA III, 512 GB, 2.5-inch
	SSD SATA III, 256GB, 2.5-inch
	SSD SATA III, 128 GB, 2.5-inch
	HDD SATA III, 500 GB, 5.4k rpm
Mass storage M.2 technology	SSD PCIe, 1024 GB M.2 NVMe module, SED
	SSD PCIe, 1024 GB M.2 NVMe module
	SSD PCIe, 512 GB M.2 NVMe module, SED
	SSD PCIe, 512 GB M.2 NVMe module
	SSD PCIe, 256 GB M.2 NVMe module, SED
	SSD PCIe, 256 GB M.2 NVMe module
	SSD PCIe, 128 GB M.2 NVMe module
Mass storage 3.5 inch size	HDD SATA III, 7,200 rpm, 2000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 1000 GB, 3.5-inch
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
	SSD (Solid State Disk)
	SED (Self-Encrypting Drive)
Drives (optional)	BD Triple Writer SATA ultra slim (tray)
	DVD Super Multi ultra slim (tray)
Interface add on	Gigabit Ethernet PCIe x 1
cards/components	WLAN 802.11ax (2x2) PCIe x1 LP and Bluetooth 5.0, SRD 5.8GHz (dedicated regions only)
(optional)	Dual serial card PCIe x1 LP

FUJITSU

Base unit

Base unit	ESPRIMO D7010/8
Mainboard	D2022 A1
Mainboard type	D3823-A1
Formfactor	Proprietary
Chipset	Intel® B460
Processor socket	LGA 1200
Processor quantity maximum	1
Supported capacity RAM (max.)	128 GB
Memory slots	4 DIMM (DDR4)
Memory frequency	2,933 MT/s
Memory notes	Dual channel support
	For dual channel performance, 2 memory modules must be ordered. Capacity per channel must be the same.
	2933 MHz may be clocked down to 2400MHz depending on processor and memory configuration
LAN	10/100/1,000 Mbit/s Realtek RTL8111H
BIOS version	AMI Aptio V
	UEFI Specification 2.6
BIOS features	BIOS Flash EPROM update by software
	Recovery BIOS
	Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC623
Audio features	High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	3
Thereof SATA III	3
Controller functions	Serial ATA III (6 Gbit)
	NCQ
	AHCI
Interfaces	
Audio: line-in	1
Audio: line-out	1
Front audio: headset	1
USB 2.0 total	5
USB 3.2 Gen1 (5 Gbps) total	4
USB front	2x USB 2.0; 2x USB 3.2 Gen1
USB rear	2x USB 2.0; 2x USB 3.2 Gen 1
USB internal	1x USB 2.0
VGA	Optional: via external active adapter cable
DisplayPort	2
Mouse / Keyboard (PS/2)	2 (optional)
Ethernet (RJ-45)	1
Interface Module notes	Anytime USB charge functionality
Input device / components	
Input devices (optional)	Keyboard
• • • •	Mouse
Drive bays	
Drive bays total	3
2.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	1x internal 3.5" or 1x internal 2.5"
M.2-2280	1x on mainboard for SSD NVMe (PCle 3.0 x4; up to 32Gbit/s)
Slots	יא או וומווסטמום וטי שש איזויב נו כוב ש.ט איז, מף נט שבמטומשן
Slots PCI-Express 3.0 x4 (mech_x16)	1 x (150mm/ 5 91 inch)

PCI-Express 3.0 x4 (mech. x16)

1 x (150mm/ 5.91 inch)



Graphics on board	
Graphics brand name	Intel® UHD Graphics 610, Intel® UHD Graphics 630
Shared video memory	Up to half size of total system memory
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel
Graphics features Graphics notes	Support for up to three independent displays
	DirectX [®] 12
	HDCP support
	OpenCL™ 2.1
	OpenGL® 4.5
	For multi monitoring mode, graphics card and integrated graphics run in parallel
	DisplayPort interface supports Ver. 1.4 incl. Multi-Stream
	Digital audio formats are supported, including Dolby Digital Plus (7.1 channels) Up to 1GB dedicated video memory (main memory owned and locked for graphics use)
	Tested resolutions, depending on display type additional resolutions and frequencies possible
	Shared memory depending on main memory size and operating system
	Resolution (colour depth up to 32 Bit/pixel)
	For TFT we recommend using 60Hz
Electrical values	
	Power supply efficiency in % at 10% /20% /50% /100% load
Power efficiency note	80Plus GOLD:
	For 230V; 87/90/92/91
	For 115V; 86/89/91/88
	80Plus PLATINUM:
	For 230V; 88/92/94/93
	For 115V; 87/91/92/91
Rated voltage range	100V - 240V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz – 63 Hz
Max. output of single power supply	GOLD: 280W; PLATINUM: 300W
Power factor correction/active	Active
power Monitor outlet	Switched for PLATINUM power supply
Power consumption	
Power consumption note Link to Energy White Paper	See white paper Energy Consumption https://docs.ts.fujitsu.com/dl.aspx?id=f4739e6a-7596-4ab6-b38e-6b1b5d58e28b
37 1	nttps://docs.ts.tujitsu.com/di.aspx?id=14739e6a-7596-4ab6-D38e-60105058e28b
Heat dissipation	
Heat dissipation notes	Sea white paper Energy Consumption
Noise emission	
Related Processors for noise	Intel® Core™ i9-10900 processor and
Chandrad and the state of the s	128GB, ODD; Windows 10 (tower position)
Standard noise emission	According to ISO 7779:2010, ECMA-74
Standard noise notes/ description	A-weighted sound power level Lwad (in B)/ Workplace related A-weighted sound pressure level LpAm (in db(A))
Standard noise operation mode: CPU	For PLATINUM PSU:
50% load	3.0 B / 17 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2)
50% load	For GOLD PSU:
	3.1 B / 17 dB(A) Bystander; 18 dB(A) Operator position (3.5" HDD)
Standard noise operation mode:	
HDD	For PLATINUM PSU:
mode	3.0 B / 17 dB(A) Bystander; 17 dB(A) Operator position (SSD M.2)
	For GOLD PSU:
	3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position (3.5" HDD)
Standard noise operation mode:	For PLATINUM PSU:
Idle	3.0 B / 16 dB(A) Bystander; 17 dB(A) Operator position (SSD M.2)
mode	For GOLD PSU: 3.1 B / 17 dB(A) Bystander; 18 dB(A) Operator position (3.5" HDD)



Noise emission	
Standard noise operation mode:	For PLATINUM PSU:
ODD .	4.3 B / 30 dB(A) Bystander; 35 dB(A) Operator position (SSD M.2)
load	For GOLD PSU:
	4.3 B / 30 dB(A) Bystander; 35 dB(A) Operator position (3.5" HDD)
Standard noise operation mode:	For PLATINUM PSU:
Office	3.0 B / 17 dB(A) Bystander; 17 dB(A) Operator position (SSD M.2)
Applications 2.0	For GOLD PSU:
որիումսնու 2.0	3.2 B / 19 dB(A) Bystander; 22 dB(A) Operator position (3.5" HDD)
Dimensions / Weight / Environment	
Dimensions (W x D x H)	314 x 296 x 89 mm
	12.36 x 11.65 x 3.51 inch
Operating position	Horizontal / vertical (optional, feet needed)
Weight	Approx. 8 kg
Weight (lbs)	Approx. 17.64 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 – 35 °C (50 – 95 °F)
Operating relative humidity	5 – 85 % (relative humidity)
1 2 1	
Compliance	
Global	RoHS (Restriction of hazardous substances)
	WEEE (Waste electrical and electronic equipment)
	Microsoft Operating Systems (HCT / HCL entry / WHQL)
	ENERGY STAR [®] 8.0, depending on configuration
	TCO Certified 8.0 (depending on configuration)
	EPEAT® Silver (dedicated regions), depending on configuration
	ENERGY STAR® compliance is an order option. Non-ENERGY STAR/ TCO/ EPEAT compliant products are marked at
	brand name with additional suffix "n".
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Additional Software	
Additional software (preinstalled)	Adobe® Reader® (pdf reader)
	McAfee [®] LiveSafe [™] (provides award-winning antivirus protection for your PC and much more. 30 days trial preinstalled
	Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows®
	Drivers & Utilities DVD (DUDVD)
	CyberLink PowerDVD BD (playback software for Blu-ray Disc™)
	CyberLink PowerDVD DVD (playback software for DVD)
	Nero Essentials XL
	Microsoft® Office Professional 2019
	Microsoft® Office Home and Business 2019
	(A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the
	region in which it was acquired.)
the fields	
Manageability	
	DeskUpdate Driver management
	PXE 2.1 Boot code
	PXE 2.1 Boot code Wake up from S5 (off mode)
	PXE 2.1 Boot code
	PXE 2.1 Boot code Wake up from S5 (off mode)
Manageability technology	PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional)
Manageability technology	PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN)
Manageability technology Manageability software	PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) DeskView Client DeskView Instant BIOS Management
Manageability technology Manageability software	PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) DeskView Client DeskView Instant BIOS Management BIOS Management incl. Security
Manageability technology Manageability software	PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) DeskView Client DeskView Instant BIOS Management BIOS Management incl. Security Inventory Management
Manageability technology Manageability software	PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) DeskView Client DeskView Instant BIOS Management BIOS Management incl. Security Inventory Management Driver Management
Manageability technology Manageability software DeskView components	PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) DeskView Client DeskView Instant BIOS Management BIOS Management incl. Security Inventory Management Driver Management Alarm Management
Manageability technology Manageability software DeskView components	PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) DeskView Client DeskView Instant BIOS Management BIOS Management incl. Security Inventory Management Driver Management Alarm Management DMI (Desktop Management Interface)
Manageability technology Manageability software DeskView components	PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) DeskView Client DeskView Instant BIOS Management BIOS Management incl. Security Inventory Management Driver Management Alarm Management DMI (Desktop Management BIOS)
Manageability technology Manageability software DeskView components	PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) DeskView Client DeskView Instant BIOS Management BIOS Management incl. Security Inventory Management Driver Management Alarm Management DMI (Desktop Management BIOS) PXE (Preboot Execution Environment)
Manageability technology Manageability software DeskView components	PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) DeskView Client DeskView Instant BIOS Management BIOS Management incl. Security Inventory Management Driver Management DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation)
Manageability technology Manageability software DeskView components	PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) DeskView Client DeskView Instant BIOS Management BIOS Management incl. Security Inventory Management Driver Management Alarm Management DMI (Desktop Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management)
Manageability Manageability technology Manageability software DeskView components Supported standards Manageability link	PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) DeskView Client DeskView Instant BIOS Management BIOS Management incl. Security Inventory Management Driver Management DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation)



Security	
Physical Security	Kensington Lock support
	Eye for padlock
	Integrated cabinet lock (optional)
	Cable Cover (optional; covers and secures the ports and cables on rear side)
System and BIOS Security	Embedded security (TPM 2.0)
	EraseDisk
	Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME)
	Modern Standby ready (for configurations with NVMe SSD and w/o PCIe cards)
	Write protect option for the Flash EPROM
	Control of all USB interfaces
	External USB ports can be disabled separately
	Control of external interfaces
User Security	User and supervisor BIOS password
	Hard disk password
	Access protection via external SmartCard reader (optional)
	Access protection via internal SmartCard reader (optional)
	AuthConductor Client Basic (secure authentication solution)
Miscellaneous	
	Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards
	Keyboard on with any key (USB)
Packaging information	
Packaging dimension (mm)	499 x 296 x 439 mm
Packaging dimension (inch)	19.65 x 11.65 x 17.28 inch
Max. quantity/ pallet	24
Material – Weight (g) Carton	1117 g
Material – Weight (lbs) Carton	2.46 lbs
Material – Weight (g) EPS / PS	225 g
Material – Weight (lbs) EPS / PS	0.5 lbs
Material – Weight (lbs) PE	25g
Material – Weight (lbs) PE	0.06 lbs
Packaging notes	Printed user documentation is bleached in chlorine free process;
	Bulk packaging for projects (optional)
Warranty	
Warranty period	1 year
Warranty type	Bring-In / Onsite Service (depending on country)
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years

More information

Fujitsu OPTIMIZATION solutions

In addition to Fujitsu Desktop ESPRIMO D7010/8, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products https://www.fujitsu.com/hk/products/computing/pc/ Software www.fujitsu.com/software/

Contact Us

HONG KONG Fujitsu Business Technologies Asia Pacific Ltd. Tel: (852) 3910-8228 Email: fpca.hksales@hk.fujitsu.com hk.fujitsu.com/pc

INDONESIA PT Fujitsu Indonesia Tel: (62) 21-570-9330 Email: marketing@id.fujitsu.com id.fujitsu.com/pc

TAIWAN

Fujitsu Taiwan Ltd. Tel: (886) 2-2311-2255 Email: ftl.lifebook@fujitsu.com tw.fujitsu.com/pc

More information

To learn more about Fujitsu Desktop ESPRIMO D7010/8, please contact your Fujitsu sales representative, Fujitsu Business partner, or visit our website.

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at http://www.fujitsu.com/global/about/environment/



SINGAPORE Fujitsu Asia Pte Ltd. Tel: (65) 6512-7555 Email: fapl.info@fujitsu.com sq.fujitsu.com/pc

PHILIPPINES Fujitsu Philippines, Inc. Tel: (63) 2-8841-8488 Email: info.fpi@fujitsu.com ph.fujitsu.com/pc

THAILAND Fujitsu (Thailand) Co., Ltd. Tel: (66) 0-2302-1500 Email: info.th@fujitsu.com th.fujitsu.com/pc

Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms © 2020 Fujitsu Business Technologies Asia Pacific Limited

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CHINA

Fujitsu (China) Holdings Co., Ltd. – PC China Division Tel: 86 (21) 58871000-8721 Email: fpcacn.support@cn.fujitsu.com cn.fujitsu.com/pc

MALAYSIA Fujitsu (Malaysia) Sdn. Bhd Tel: (60) 3-8230-4188 Email: askfujitsu.my@fujitsu.com my.fujitsu.com/pc

VIETNAM Fujitsu Vietnam Limited Tel: (84-24) 2220-3113 Email: sales-vn@fujitsu.com vn.fujitsu.com/pc

Note: For countries not listed above, please contact our Hong Kong office.

Specification disclaimers

¹ Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. ² CB = 1 billion bytes. TB = 1 trillion bytes is exerved for system recovert, ³ Shared memory depending on used software. Up to 20 GB of HDD space is reserved for system countries only. It requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. Please contact our Fujitsu sales specialist for more information. ³ Interfaces depend on the configuration selected by customers. ⁶ Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2018 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark how thich actually can be lower and may vary depending on power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. 2-cell battery will only be available in specific countries/regions. For more detail, please contact Fujitsu sales specialist. ⁷ The stated thickness does not include rubber feet.

FUJITSU shall not be liable for technical or editorial errors or omissions contained herein. Ultrabook, Celeron, Celeron Inside, Intel, Intel Logo, Intel Atom, Intel Atom, Intel Atom Inside, Intel Inside, Intel Inside Logo, Intel VPro, Intel Evo, Itanium, Itanium, Itanium, Itanium, Rentium Inside, Pentium, Pentium Inside, VPro Inside, Xeon, Xeon Phi, Xeon Inside, Intel Agliex, Arria, Cyclone, Movidius, eASIC, Enpirion, Iris, MAX, Intel RealSense, Stratix, and Intel Optane are trademarks of Intel Corporation or its subsidiaries. USB Type-C[™] and USB (Type Intentes Forum, All Other trademarks are the property of their respective owners.

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms.

© 2021 Fujitsu Business Technologies Asia Pacific Limited

Last Update: 13th May 2021

