# Datasheet FUJITSU Desktop ESPRIMO P9910

## The sailor for most demanding applications!

The FUJITSU ESPRIMO P9910 Desktop is a very high performance PC powered by the 10<sup>th</sup> Gen Intel<sup>®</sup> Core<sup>™</sup> Processor family, a 680Watt Power Supply which ensures smooth running of all special purpose cards with improved efficiency. With increased encode/decode capabilities, excellent serviceability, ease of use and expandability, broad interface options, this is the PC needed for smooth sailing of most demanding applications.

Powerful performance for demanding business applications Increased performance due to more CPU and graphics power

- 10<sup>th</sup> generation Intel<sup>®</sup> Core<sup>™</sup> processor family
- **680**-watt power supply for most demanding applications

### Superior system management

Simple system administration for complex IT infrastructures

■ Based on the stable Intel<sup>®</sup> vPro<sup>™</sup> technology platform (depending on processor) and DeskView manageability suite

### Ultimate Expandability

Custom-size your computing performance according to your business needs

- Two 3.5" hard disk bays for huge mass storage capacity
- DVD bays in horizontal position for convenient access
- Support of full length PCIe cards (e.g., high level graphics cards) up to 4 cards

### Best-in-Class connectivity

Be flexible and stay productive in a hyper-connected world

- Flexible graphics connector options: VGA, DVI-D, HDMI, Type-C
- Type C option supporting 60-watt output power to run a display w/o extra power supply
- Legacy connectors as option: PS/2, serial port, parallel port

### High security with integrated options

Designed to protect data and hardware components against manipulation and theft

- Cable cover in addition to existing Smartcard reader
- Integrated Cabinet lock with Master key option
- Hole for pad lock and Kensington as standard for security









## Components



Operating systems	
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business.
Operating system notes	Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming
operating system notes	Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware
	services through FUJITSU Warranty top ups. For details, please see "FUJITSU Service Statement for Windows 10
	Semi-Annual-Ćhannel Support" at http://support.ts.fujitsu.com.
Processor	Intel® Core™ i9-10900 processor (10 Cores / 20 Threads, 2.80 GHz, 20 MB, Intel® UHD Graphics 630) **
	Intel® Core™ i9-10900K processor (10 Cores / 20 Threads, 3.70 GHz, 20 MB, Intel® UHD Graphics 630) **
	Intel® Core™ i7-10700 processor (8 Cores / 16 Threads, 2.90 GHz, 16 MB, Intel® UHD Graphics 630) **
	Intel® Core™ i7-10700K processor (8 Cores / 16 Threads, 3.80 GHz, 16 MB, Intel® UHD Graphics 630) **
	Intel® Core™ i5-10600 processor (6 Cores / 12 Threads, 3.30 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel <sup>®</sup> Core™ i5-10500 processor (6 Cores / 12 Threads, 3.10 GHz, 12 MB, Intel <sup>®</sup> UHD Graphics 630) *
	Intel® vPro® Platform Logo with Intel® Core™ i5-10500, Intel Core i5-10600, Intel® Core™ i7 and Intel® Core™
	i9 processors
	*with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and
	other variables)
	**with Intel® Turbo Boost Max Technology 3.0 (clock speed and performance will vary depending on workload
Ethernet (RJ-45)	and other variables)
	4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM
Memory modules	8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM
	16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM
	32 GB (1 module(s) 32 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, UDIMM
Graphics	NVIDIA® RTX 2060 Mini, 6GB
	NVIDIA® Quadro® P400, 2GB
	MiniDP to DP Adapter Cable
Mass storage 2.5 inch size	SSD SATA III, 512 GB, 2.5-inch
Mass storage 2.5 men size	SSD SATA III, 256 GB, 2.5-inch
	SSD SATA III 128GB, 2.5-inch
	HDD SATA III, 5,400 rpm, 500 GB, 2.5-inch
Mass storage M.2 technology	SSD PCIe, 1024 GB M.2 NVMe module, SED
	SSD PCIe, 1024 GB M.2 NVMe module
	SSD PCIe, 512 GB M.2 NVMe module, SED
	SSD PCIe, 512 GB M.2 NVMe module
	SSD PCIe, 256 GB M.2 NVMe module, SED
	SSD PCIe, 256 GB M.2 NVMe module
	SSD PCIe, 128 GB M.2 NVMe module
Mass storage 3.5 inch size Hard disk notes	HDD SATA III, 7,200 rpm, 2000 GB, 3.5-inch
	HDD SATA III, 7,200 rpm, 1000 GB, 3.5-inch, business critical
	HDD SATA III, 7,200 rpm, 1000 GB, 3.5-inch
	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
	SSD (Solid State Disk) SED (Self-Encrypting Drive)
	SED (Sell-Encrypting Drive)
Drives (optional)	BD Triple Writer SATA ultra slim (tray)
	DVD Super Multi
	DVD Super Multi ultra slim (tray)
	MultiCard Reader 15in1 USB 3.0 3.5"
Interface add on cards/components	Gigabit Ethernet PCIe x1
(optional)	Intel® WI-FI 6 AX200 and Bluetooth 5.1 vPro, SRD 5.8GHz (dedicated regions only)
	Dual serial card PCIe x1
	Dual serial card PCIe x1

## Base unit



Mainboard	
Mainboard type	D3812
Formfactor	Proprietary
Chipset	Intel® Q470
Processor socket	LGA1200
Processor quantity maximum	1
Support capacity RAM (max.)	128 GB
Memory slots	4 DIMM (DDR4)
Memory frequency	2,933 MT/s
Memory notes	Dual channel support
	For dual channel performance, 2 memory modules have to be ordered. Capacity per channel must be the same. 2933 MHz may be clocked down to 2400MHz depending on processor and memory configuration
LAN	10/100/1,000 Mbit/s Intel® I219LM
Integrated WLAN	Optional; Intel <sup>®</sup> Wi-Fi 6 AX200 (2x2/160) Gig+ and Bluetooth 5.1
BIOS version	AMI Aptio V
	UEFI Specification 2.6
BIOS features	BIOS Flash EPROM update by software
	Recovery BIOS
	Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC623
Audio codec Audio features	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound
	וותבווום אפמגבו שעירט מטטט אומצטמגג נטאנוטוום), ווועוו טפווווונטוו מטטוט, אוז אטווטטווט אטטוט
I/O controller on board	с
Serial ATA total Thereof SATA III	5
Controller functions	Serial ATA III (6 Gbit)
	NCQ
	AHCI
	RAID 0/1/5/10
Interfaces	
Audio: line-in	1
Audio: line-out	1
Front audio: headset	1
USB 2.0 total	4
USB 3.2 Gen1 (5 Gbps) total	3
USB 3.2 Gen2 (10 Gbps) total	5 and 1 optional
USB front	2x USB 2.0; 2x USB 3.2 Gen2; 1x USB 3.2 Gen 2 Type-C (supports up to 15W)
USB rear	2x USB 2.0; 2x USB 3.2 Gen 1; 2x USB 3.2 Gen 2; optional: additional 1x USB 3.2 Gen 2 Type-C (supports
	DisplayPort 1.4 and power delivery (PD) up to 15W or 60W (occupies PCIe x16 slot)
USB internal	1x USB 3.2 Gen 1 Type A
VGA	Optional
DisplayPort	2
DVI	Optional (DVI-D)
Serial (RS-232)	1 (optional serial port (9pin, 16-byte FIFO, 16550 compatible))
Mouse/ Keyboard (PS/2)	2 (optional)
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
Interface Module notes	Anytime USB charge functionality
Kensington Lock support	I
Input device/ components	
Input devices (optional)	Keyboard Mouse
Drive bays	
Drive bays total	6
2.5-inch internal bays	1
3.5-inch internal bays	2
3.5-inch external bays	1
5.25-inch external bays	2

(	SO
FU	ITSU

Drive bay notes	5.25" bays: one bay in HH format, one bay for slim optical disc drive only;
	Internal 3.5" bays: 3.5" drive (screwless) or 2.5" drive (screws; optional screwless)
M.2-2280	2 x on mainboard for SSD NVMe (PCIe 3.0 x4; up to 32Gbit/s)
Slots	
PCI-Express 3.0 x1	2 x (110 mm and 270 mm / 4.33 inch and 10.63 inch) Full height
PCI-Express 3.0 x4 (mech. x16)	1 x (270 mm / 10.63 inch)
PCI-Express 3.0 x16	1 x (270 mm / 10.63 inch) Full height
M.2-2230	On mainboard for WLAN/Bluetooth module
Graphics on board	
Graphics brand name	Intel® UHD Graphics 610, Intel® UHD Graphics 630
Shared video memory	Up to half size of total system memory
TFT resolution (VGA)	Up to 1,920 x 1,080 pixel
TFT resolution (DVI)	up to 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel
TFT resolution (HDMI)	Up to 4,096 x 2,160 pixel (30 Hz)
Graphics features	Support for up to three independent displays
	DirectX <sup>®</sup> 12
	HDCP support
	OpenCL™ 2.1
	OpenGL® 4.5
	For multi monitoring mode, graphics card and integrated graphics run in parallel
	DisplayPort interface supports Ver. 1.4 incl. Multi-Stream
	Digital audio formats are supported, including Dolby Digital Plus (7.1 channels)
	DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cable
	(not included)
	Additional I/O connectors configurable, choice of
	DVI-D
	HDMI™
	VGA
	USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 15W)
	USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 60W. Occupies PCIe x16 slot)
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use)
	Tested resolutions, depending on display type additional resolutions and frequencies possible
	Shared memory depending on main memory size and operating system
	Resolution (color depth up to 32 Bit/pixel)
	For TFT we recommend using 60Hz
Electrical values	
Power efficiency note	Power supply efficiency at 10% / 20% / 50% / 100% load
	80Plus PLATINUM:
	for 230V; tbd
	for 115V; tbd
Rated voltage range	100 V – 240 V
Rated frequency range	50 Hz – 60 Hz
Operating voltage range	90 V – 264 V
Operating line frequency range	47 Hz – 63 Hz
Max. output of single power supply	680 W
Power factor correction/active power	Active
Power supply output	2 graphics power rails (6 pin and 8 pin connectors)
Power consumption	
Power consumption note	See White paper Energy Consumption
Link to Energy White Paper	https://docs.ts.fujitsu.com/dl.aspx?id=698eec72-22cd-4343-87b2-1613c9f2b0bf
,,, _,, _	F



Heat dissipation	
Heat dissipation notes	See white paper Energy Consumption
Noise emission	
Related Processor for noise	Intel® Core™ i5-10500 processor
Standard noise emission	8 GB, ODD, Windows 10
	According to ISO 7779:2010, ECMA-74
Standard noise notes/ description	A-weighted sound power level Lwad (in B)/ Workplace related A-weighted sound pressure level LpAm (in db(A))
Standard noise operation mode: CPU 50% load	2.5 B / 18 dB(A) Bystander; 23 dB(A) Operator position (SSD M.2)
Standard noise operation mode: HDD load	2.5 B / 16 dB(A) Bystander; 19 dB(A) Operator position (SSD M.2)
Standard noise operation mode: Idle mode	2.5 B / 16 dB(A) Bystander; 19 dB(A) Operator position (SSD M.2)
Standard noise operation mode: ODD load	4.4 B / 33 dB(A) Bystander; 42 dB(A) Operator position (SSD M.2)
Standard noise operation mode: Office applications 2.0	2.5 B / 16 dB(A) Bystander; 19 dB(A) Operator position (SSD M.2)
Dimensions/ Weight/ Environmental	
Dimensions (W x D x H)	180 x 304 x 375 mm
	7.09 x 11.97 x 14.76 inch
Operating position	Vertical
Weight	Approx. 10 kg
Weight (lbs)	Approx. 22.05 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 – 35 °C (50 – 95 °F)
Operating relative humidity	5 – 85 % (relative humidity)
1 3 1	
Compliance	
Product	ESPRIMO P9910
Model	MI7W
Global	RoHS (Restriction of hazardous substances)
	WEEE (Waste electrical and electronic equipment)
	Microsoft Operating Systems (HCT / HCL entry / WHQL)
	Microsoft Secured-core PC certification (for selected configurations)
	ENERGY STAR <sup>®</sup> 8.0, depending on configuration
	TCO Certified 8.0 (depending on configuration)
	EPEAT® Silver (dedicated regions), depending on configuration
	ENERGY STAR® compliance is an order option. Non-ENERGY STAR/ TCO/ EPEAT compliant products are marked at
	brand name with additional suffix "n".
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Additional software	
Additional software (pre-installed)	Adobe® Reader® (pdf reader)
	McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial
	preinstalled)
	Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows <sup>®</sup>
	Drivers & Utilities DVD (DUDVD)
	CyberLink PowerDVD BD (playback software for Blu-ray Disc™)
	CyberLink PowerDVD DVD (playback software for DVD)
	Nero Essentials XL
	Microsoft® Office Professional 2019
	Microsoft® Office Home and Business 2019
	(A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the
	region in which it was acquired.)



A Labo	
Manageability	
Manageability technology	DeskUpdate Driver management
	PXE 2.1 Boot code
	Wake up from S5 (off mode)
	Intrusion switch (optional)
	WoL (Wake on LAN)
AA 1.11. 6	iAMT 14.0 (depending on processor)
Manageability software	DeskView Client
	DeskView Instant BIOS Management
DeskView components	BIOS Management incl. Security
	Inventory Management
	Driver Management
	Alarm Management
Supported standards	DMI (Desktop Management Interface)
	SMBIOS (System Management BIOS)
	PXE (Preboot Execution Environment)
	WMI (Windows Management Instrumentation)
	WBEM (Web Based Enterprise Management)
A. 1.11. 1. 1	CIM (Common Information Model)
Manageability link	https://www.fujitsu.com/fts/manageability
Security	
Physical Security	Kensington Lock support
	Eye for padlock
	Integrated cabinet lock (optional)
	Cable Cover (optional; covers and secures the ports and cables on rear side)
System and BIOS Security	Embedded security (TPM 2.0)
	EraseDisk
	Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME)
	Modern Standby ready (for configurations with NVMe SSD and w/o PCIe cards)
	Write protect option for the Flash EPROM
	Control of all USB interfaces
	External USB ports can be disabled separately
	Control of external interfaces
User Security	User and supervisor BIOS password
	Hard disk password
	Access protection via external SmartCard reader (optional)
	Access protection via internal SmartCard reader (optional)
	AuthConductor Client Basic (secure authentication solution)
Miscellaneous	
	Keyboard on with any key (USB)
	Thermal management
	Extended lifetime
Serviceability	
	EasyFix
	EasyChange for HDD
	EasyChange for optical drives
Packaging information	
Packaging dimension (mm)	439 x 296 x 499 mm
Packaging dimension (inch)	17.28 x 11.65 x 19.65 inch
Max. quantity / pallet	24
Material – Weight (g) Carton	1113 g
Material – Weight (lbs) Carton	2.45 lbs
Material – Weight (g) EPS / PS	164 g
Material – Weight (lbs) EPS / PS	0.36 lbs
Material – Weight (g) PE	25 g
Material Weight (lbs) PE	0.06 lbs
Packaging notes	Printed user documentation is bleached in chlorine free process;
i ackaying notes	Bulk packaging for projects (optional)
Mission a los	
Warranty	
Warranty Warranty period Warranty type	3 years Bring-In / Onsite Service (depending on country)

## More information

### Fujitsu OPTIMIZATION solutions

In addition to Fujitsu Desktop ESPRIMO P9910, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### **Computing Products**

https://www.fujitsu.com/hk/products/computing/pc/ Software www.fujitsu.com/software/

#### Contact Us

HONG KONG Fujitsu Business Technologies Asia Pacific Ltd. Tel: (852) 3910-8228 Email: fpca.hksales@hk.fujitsu.com hk.fujitsu.com/pc

#### INDONESIA PT Fujitsu Indonesia Tel: (62) 21-570-9330

Tel: (62) 21-570-9330 Email: marketing@id.fujitsu.com id.fujitsu.com/pc

### TAIWAN

Fujitsu Taiwan Ltd. Tel: (886) 2-2311-2255 Email: ftl.lifebook@fujitsu.com tw.fujitsu.com/pc

Note: For countries not listed above, please contact our Hong Kong office.

More information

To learn more about Fujitsu Desktop ESPRIMO P9910, please contact your Fujitsu sales representative, Fujitsu Business partner, or visit our website.

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at http://www.fujitsu.com/global/about/environment/



SINGAPORE Fujitsu Asia Pte Ltd. Tel: (65) 6512-7555 Email: fapl.info@fujitsu.com sq.fujitsu.com/pc

PHILIPPINES Fujitsu Philippines, Inc. Tel: (63) 2-8841-8488 Email: info.fpi@fujitsu.com ph.fujitsu.com/pc

THAILAND Fujitsu (Thailand) Co., Ltd. Tel: (66) 0-2302-1500 Email: info.th@fujitsu.com th.fujitsu.com/pc

### Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms © 2020 Fujitsu Business Technologies Asia Pacific Limited

### Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CHINA

Fujitsu (China) Holdings Co., Ltd. – PC China Division Tel: 86 (21) 58871000-8721 Email: fpcacn.support@cn.fujitsu.com cn.fujitsu.com/pc

MALAYSIA Fujitsu (Malaysia) Sdn. Bhd Tel: (60) 3-8230-4188 Email: askfujitsu.my@fujitsu.com

my.fujitsu.com/pc

VIETNAM Fujitsu Vietnam Limited Tel: (84-24) 2220-3113 Email: sales-vn@fujitsu.com vn.fujitsu.com/pc

Specification disclaimers

<sup>1</sup> Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. JSP fees may apply and additional requirements may apply over time for updates. <sup>7</sup>GB = 1 billion bytes. TB = 1 trillion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery. <sup>3</sup>Shared memory depending on main memory size and operating system. <sup>4</sup>WWAN module is optional and available in specific countries separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. Please contact our Fujitsu sales specialist for more information. <sup>3</sup>Interfaces depend on the configuration selected by customers. <sup>6</sup> Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2018 (office productivity). Refer to www.bapco.com for additional detains. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific countries which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. 2-cell battery will only be available in specific countries? regions. For more detail, please contact Fujitsu sales specialist. <sup>7</sup>The stated thickness does not include rubber feet.

FUJITSU shall not be liable for technical or editorial errors or omissions contained herein. Ultrabook, Celeron, Inside, Core Inside, Intel, Intel Logo, Intel Atom, Inside, Intel Atom, I

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <u>www.fujitsu.com/terms</u>.

© 2021 Fujitsu Business Technologies Asia Pacific Limited

Last Update: 13th May 2021

