

The Fujitsu F56

Multi Cassette Media Dispenser



Compact and Multi Cassette Media Dispenser

Designed for the OEM market, the Fujitsu F56 dispenser features six cassettes that can hold up to a total of 3,000 notes or other media.

- Width 6.3 in (160mm)
- Depth 15.7 in (397mm)
- Height 14 .8 in (375mm) 2-Denominations
- Up to 500 notes / cassette

High-end features at low cost

The Fujitsu F56 offers many features usually found only in more expensive units.

- RS232C
- Bunch presenter
- Bill low sensor
- Denomination sensor
- Shutter (option)
- Predictive failure analysis
- Lockable cassette option
- Firmware download
- Single note reject

Flexible, Easy integration

The Fujitsu F56 provides you with maximum flexibility in product design. It can be installed as a front-service or rear-service configuration.









FUJITSU FRONTECH LIMITED

All measurements are in millimeters. All measurements are in millimeters. Cash Cassette 1 Cash Cassette 2

SPECIFICATIONS			
Dimensions (W x D x H)	160mm x 397mm x 375mm	Capacities / denominations	Accommodation 60mm
2-denominations	Cassette: 116mm x 216mm x 98mm		New notes 500 each cassette (approx.)
Weight (w/o media)	11kg	Standard	UL, TUV certified
	Cassette: 0.7kg		
Service access	Front or Rear access or Dual	Reject bill area capacity	20 bills
Number of cassettes	Up to 6 Cassettes	Bill low sensor	Fixed sensor
	Standard 2 cassettes		40 bills
			Each cassette (approx.)
Bill count speed	2 notes / second	Interface	RS232C
Acceptable media range	Max. 82mm x 160mm	Electrical Power Requirements	DC +24V (+10%, -10%)
	Min. 60mm x 120mm		Max 7A
	Thickness 0.09 ~ 0.3mm		Ave. 5A
Bill transaction	20 bills / transaction	Temperature	Operation 0 ~ 40℃
			Stop State -5 ~ 50℃
Bill retrieval	One time standard Max 60 bills (option)	Relative Humidity	Operation 10 ~ 95%
Shutter	Optional		Stop state 8 ~ 95%



FUJITSU FRONTECH LIMITED

1776 Yanokuchi, Inagi-shi, Tokyo 206-8555, Japan

URL: http://www.frontech.fujitsu.com/en/

Inquiry: http://www.frontech.fujitsu.com/en/contact/
All rights reserved Copyright© FUJITSU FRONTECH LIMITED 2010