

FUJITSU Supercomputer PRIMEHPC FX700

A high-performance Arm server featuring the A64FX CPU, the same CPU used in the supercomputer Fugaku. Air-cooled and based on standard technology, making it easy to set up.

The FUJITSU Supercomputer PRIMEHPC FX700 is a PRIMEHPC series air-cooled model based on standard technology that features the A64FX CPU for use in the supercomputer Fugaku developed together with RIKEN and the PRIMEHPC FX1000. It is the perfect system for customers that wish to easily take advantage of the high performance of the A64FX. It has a minimum hardware configuration of 2 nodes in Japan and 128 nodes overseas.

A64FX, the newly developed Arm CPU

The A64FX, developed by Fujitsu, is the world's first CPU to implement a Scalable Vector Extension (SVE), an extension of the Armv8.2-A instruction set architecture for supercomputers. Manufactured using the state-of-the-art 7nm process, the A64FX has 48 computing cores, can provide a theoretical peak double-precision floating-point operations performance of 2.7648 TFLOPS or 3.072 TFLOPS. Furthermore, it is capable of high-throughput single-precision/half-precision computation and 8bit/16bit integer operations using its 512-bit wide SIMD units. This calculation performance shines in processing applications such as AI.

Each node consists of one processor, and uses HBM2 (High Bandwidth Memory 2), a world first for a general-purpose CPU. Each node has a tremendous 1,024 GB/s of memory bandwidth.

Microarchitecture with high processing performance

The A64FX's microarchitecture was developed using technologies that Fujitsu has refined through its experience with supercomputers, mainframes, and UNIX servers. The A64FX carries on from the CMG (Core Memory Group) of the PRIMEHPC series, which enables scalable performance improvement when using multiple cores, as well as VISIMPACT (Virtual Single Processor by Integrated Multi-core Parallel Architecture), which realizes highly efficient hybrid parallel processing. It also enhances functions such as SIMD functions.

Easy-deployment form factor and air cooled design

The PRIMEHPC FX700 has a 2U chassis that can be mounted in standard 19-inch racks and can hold up to four blades. Each blade contains two nodes, and each unit can consist of up to eight nodes. It is air cooled, making it easy to deploy high-performance Arm servers in environments without specialized water-cooling equipment.

Industry-standard interconnect and OS

The interconnect among compute nodes is the industry-standard InfiniBand. InfiniBand is widely used as an interconnect in PC clusters, and can be used to construct equivalent topologies. The FUJITSU Supercomputer PRIMEHPC FX700 uses the Red Hat Enterprise Linux OS, offering a high level of software migratability.

Development environment that leverages the performance of the A64FX


Development environments such as compilers are supplied by Fujitsu, providing powerful support for the development and optimization of applications for the A64FX CPU.

HPC software support

Bright Computing's Bright Cluster Manager, a cluster management software, and Altair's Altair PBS Professional, a job scheduler are supported.



FUJITSU Supercomputer PRIMEHPC FX700 Specifications

	CPU	Name	A64FX
		Instruction set architecture	Armv8.2-A SVE
		Number of cores	48 cores
		Clock	1.8 GHz or 2.0 GHz
		Theoretical peak performance	2.7648 TFLOPS or 3.072 TFLOPS (double precision)
	Node	Architecture	1 CPU/node
		Memory capacity	32 GiB (HBM2, 4 stacks)
		Memory bandwidth	1,024 GB/s
		Interconnect (option setting)	InfiniBand EDR / HDR100 ^(*1) ^(*1) EDR and HDR100 cannot be mixed
		Internal storage (option setting)	M.2 SSD Type 2280 slot (NVMe)
	Main unit	Form factor	2U rack-mount chassis
		Maximum number of nodes	8 nodes/chassis
		Cooling method	Air cooling
		PSU (option setting for redundancy)	2+1 redundancy Input voltage: 200 to 240 VAC \pm 10%, single phase Input frequency: 50/60 Hz \pm 3 Hz
		FANU	4 units/chassis (2 FANs/unit, FAN: 7+1 redundancy)
	Software	OS	Red Hat Enterprise Linux 8
		HPC middleware	<ul style="list-style-type: none"> FUJITSU Software Compiler Package FUJITSU Software Technical Computing Suite ^(*2) ^(*2) Only distributed file system (FEFS) is supported Bright Cluster Manager (Bright Computing) Altair PBS Professional (Altair)



Website: www.fujitsu.com

© Copyright 2023 Fujitsu and the Fujitsu logo are trademarks or registered trademarks of Fujitsu Limited in Japan and other countries. Other company, product and service names may be trademarks or registered trademarks of their respective owners. Technical data subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.