# High performance document capture



FUJITSU Image Scanners fi-7600 / fi-7700

The fi-7600 and fi-7700 help you reliably produce digital information from paper documents content, in back-office applications, specific line-of-business processes and right across the organisation. These models combine heavy-duty durability and high volume mixed batch capture within a single device.

### Highlights at a glance:

- Fast processing at 100 ppm/200 ipm (A4, landscape, colour, 200/300 dpi)
- Mixed batch scanning from A8-A3, 20-413 g/m<sup>2</sup>, folded documents up to A1 and longer
- PaperStream platform performance
  - Patch code, barcode, blank page batch separation
  - Barcode, matrix code and zonal OCR indexing included
  - File/Folder Name Rules based on barcode, OCR, multilevel folder hierarchy supported

### Flexible – durable – high volume scanning

With scanning speeds of 100 ppm/200 ipm (200/300 dpi), the fi-7600 and fi-7700 greatly improve process efficiency. Large volumes of information can be captured from various media, including thin paper, plastic cards, envelopes and long page documents.

### Smooth paper flow

The fi-7600 and fi-7700 automatically adjust to paper weights from 20-413 g/m<sup>2</sup>. The straight paper path reduces the load on a document and assures reliable scanning regardless of the condition and type of a document. By simply sliding a lever to non-separation mode, you can easily scan thick and long documents folded in half, multi-layered document sets and envelopes.



Straight paper path

### Innovative paper feeding mechanisms

Skew Reducer automatically handles sheets of paper in a stack individually, so that if one sheet is fed-in skewed, subsequent sheets are not forced into physical skew. This ensures that all information in the documents is captured correctly, even in batches with mixed document formats. The Paper Protection function monitors document movement and automatically stops feeding when any irregularities are detected.

### Form follows function

Both scanner models feature a unique market proven design concept that adjusts to individual user preferences and requirements. The fi-7700's ADF unit slides to either side or rotates by 180 degrees.



180 degrees movable ADF

The fi-7600 is equipped with an operation panel on both sides allowing for right and left handed use.

The LCD on the operation panel reveals the scanner status at a glance and enables instant operation.




Lower workload before and after scanning The Automatic Document Feeder's (ADF) independent side guides move to exactly the position required for each batch. The adjustable stacker side guides support neat alignment of processed documents.

The fi-7700 flatbed consecutively scans thick, fragile or bound documents even with the document cover open.

FUĨTSU

Fi-7700 can be configured and operated remotely from workstation.



## PaperStream

# Bundled software

### Fujitsu best-in-class scanner driver and document capturing software



### PaperStream IP

#### Scanner driver for high-quality image enhancement

- TWAIN and ISIS compliant scanner driver
- Industry leading integrated image enhancement capabilities
- Patch code and barcode recognition
- Pre-defined and custom scanning profiles for routine tasks
- Supports the user when needed with visual guidance through "Assisted Scan"
- Auto cropping, auto deskew, auto colour detecting, auto blank page detection and deletion



### PaperStream Capture

### Efficient, high-quality front-end capture solution

- One-stop batch scanning application that simplifies and accelerates the routine task of document capture through its 'One Click Capture' concept
- High-speed, high volume scanning with real-time image display, bar code detection and indexing
- PaperStream IP is an integral part of PaperStream Capture and ensures high-guality images
- Scan-verify-index-release in a single, streamlined routine that every user can easily perform
- Supports ad hoc scanning requirements for exception handling through "Assisted Scan" and, where required, instantly changing settings

## Specifications

Model		fi-7600	fi-7700	
Supported operating systems		Windows 7,8.1,10 (32/64 bit), Server 2008 (32/64 bit), Server 2008 R2, 2012, 2012 R2, 2016 (64 bit)		<sup>*1</sup> The fi-7600 and fi-7700 are capable of
Scanner type		ADF (automatic document feeder)	ADF (automatic document feeder) and Flatbed	scanning documents that exceed A4 in length:
Scanning modes		Abr (automatic document reeder) Abr (automatic document reeder) and riatbed		Documents up to 5,588 mm in length can be
Image sensor type		Colour CCD (charge-coupled device) x 2	Colour CCD (charge-coupled device) x 3	scanned at resolutions up to 200 dpi.
Light source		White LED Array x 4	White LED Array x 6	<sup>*2</sup> The paper weight only applies to using the ADF.
Multi-feed detection				*3 Capable of scanning up to 3 cards at a time when using the ADF. (Note: only one embossed
		Ultrasonic multi-feed detection sensor, paper detection sensor		card can be scanned at a time)
Document size		ADF Minimum: 50.8 x 69 mm portrait / Maximum: 304.8 x 431.8 mm Long page scanning: 5,588 mm <sup>*1</sup>		*4 Actual scanning speeds are affected by data
		– Flatbed Maximum: 304.8 x 457.2 mm		transmission and software processing times.
Recommended paper weight*2		20 to 413 g/m²/ supports 128 to 209 g/m² for A8 size ID card types, Embossed card 1.4 mm or less <sup>3</sup>		*5 JPEG compressed figures.
11 0				*6 TIFF G4 compressed figures.
Scanning speed (A4 Landscape) <sup>*4</sup> Colour <sup>*5</sup> / Greyscale <sup>*5</sup> / Mono <sup>*6</sup>		Simplex: 100 ppm (200/300 dpi) Duplex: 200 ipm (200/300 dpi)	Simplex: 100 ppm (200/300 dpi), Duplex: 200 ipm (200/300 dpi) Flatbed: 0.6 seconds (200/300 dpi)	*7 Maximum capacity varies, depending upon paper weight.
Scanning speed (A4 Portrait)*4 Colour*5 / Greyscale*5 / Mono*6		Simplex: 80 ppm (200/300 dpi) Duplex: 160 ipm (200/300 dpi)	Simplex: 80 ppm (200/300 dpi), Duplex: 160 ipm (200/300 dpi) Flatbed: 0.9 seconds (200/300 dpi)	*8 Maximum output resolutions may vary, depending upon the size of the area being
Paper chute capacity <sup>*7</sup>		300 sheets (A4: 80 g/m²)		scanned and whether the scanner is scanning
Background colours		White / Black (Selectable) ADF: White / Black (Selectable) / Flatbed: White (Black is optional)		in simplex or duplex.
Optical resolution		600 dpi		*9 Scanning limitations due to scanning mode,
Output resolution*8 Colour / Greyscale / Mono		50 to 600 dpi (adjust by 1 dpi increments), 1,200 dpi (driver)*9		document size and available memory may occur when scanning at high resolutions
Output resolution Colour / Greyscale / Mono		Colour: 24 bit. Grevscale: 8 bit. Mono: 1 bit		(600 dpi or higher).
Standard output files		PDF, PDF/A, PDF with OCR, TIFF, multipage TIFF, JPG or BMP		<sup>*10</sup> Excluding the ADF paper chute and Stacker.
Interface / Connector shape		USB 3.1 Gen 1 / USB 3.0 / USB 2.0 / USB 1.1 / Type B		* <sup>11</sup> The software can be downloaded from the
Interface / Connector shape				website designated in the Setup DVD-ROM. <sup>12</sup> PFU LIMITED, a Fujitsu company, has determined that this product meets RoHS requirements (2011/65/EU) <sup>13</sup> Geographic Limitations may apply to Service
Image processing functions		Multi image output, Automatic colour detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, De-Screen,Emphasis, Halftone, Dropout colour (None /RGB/ White /Saturation /Custom), sRGB output, Hole punch removal, Index tab cropping, Split image, De-Skew, Edge correction, Vertical streaks reduction, Cropping, Dither, Static threshold, Divide Long Page, Brightness, Color, Shadow and Sharpness Adjustment, Automatic Rotation, Automatic Page Size Detection		
Power requirements		AC 100 to 240 V, ±10%		Plans and Service Levels in some countries.
Power consumption		Operating: 64W or less (Sleep mode: 1.7W or less) Auto standby (OFF) mode: 0.35W or less		Please contact us for more information.
Operating environment		Temperature: 5 to 35°C, Relative humidity: 20 to 80% (Non-condensing)		*14 Included PaperStream Capture software can
Dimensions (W x D x H base unit)*10 / Weight		236 x 432 x 214 mm / 11 kg 706 x 500 x 345 mm / 35 kg		recognize 1D barcodes (UPC-A/EAN/JAN, Code 3 of 9, Code 128/EAN128, Codabar (NW7),
Included software / drivers		PaperStream Capture, PaperStream IP Driver (TWAIN/TWAIN x64/ISIS™), WIA driver, 2D Barcode for PaperStream <sup>*14</sup> , Software Operation Panel, Error Recovery Guide, ScanSnap Manager for fi Series <sup>*11, *14</sup> Scan to Microsoft SharePoint <sup>*11</sup> , ABBYY FineReader for ScanSnap <sup>*11</sup> , Scanner Central Admin tools		ITF), but with this addition it can recognize 2D barcodes, such as PDF417, Aztec, Datamatrix and QR code
Environmental compliance		ENERGY STAR® / RoHS*12		
Standard Warranty (included in the price of the product)		1 Year Standard Warranty: Onsite Service - Next Business Day Response		
Expected Daily Duty Cycle 44,000 Pages				
Consumables and Options	Order by Part Num	hor	Remarks	l i i i i i i i i i i i i i i i i i i i
Consumable Kit	CON-3740-500		2x Brake Rollers. Up to 500K scans.	
Cleaning Kit	CON-CLE-K75		Pack of 75x lint-free cloths for 75+ applications.	
Post Imprinter (fi-760PRB)	PA03740-D101		racters on back side of scanned documents	
Print Cartridge	CA00050-0262		1 characters; fi-760PRB print head	
Black Document Pad	PA03338-D960		flatbed unit	
Extended Warranty	U3-EXTW-LVP			All names, manufacturer names, brand and
Bronze Service Plan	U3-BRZE-LVP		ervice - 8 Hour Response + 8 Hour Fix	product designations are subject to special trademark rights and are manufacturer's
Silver Service Plan	U3-SILV-LVP		onse + 8 Hour Fix +1 Preventative Maintenance per year	trademark rights and are manufacturers trademarks and/or registered brands of their
Gold Service Plan	U3-GOLD-LVP		onse + 8 Hour Fix +2 Preventative Maintenance per year	respective owners.
Platinum Service Plan	U3-PLAT-LVP		onse + 8 Hour Fix +3 Preventative Maintenance per year	All indications are non-binding. Technical data is subject to change without
<b>Onsite Service</b> = A visit by a technician with a spare parts kit to repair the product at your premises. <b>Preventative Maintenance</b> = A scheduled visit by a technician to disassemble, clean, lubricate, recalibrate, reassemble and test.				prior notification.



Madrid Spain



http://emea.fujitsu.com/scanners

PFU (EMEA) Limited

Frankfurter Ring 211

Tel: +49 (0)89 32378 0

80807 Munich

Germany

PFU (EMEA) Limited

Viale Monza, 259

Italy

20126 Milano (MI)

Tel: +39 02 26294 1

PFU (EMEA) Limited

Hayes End Road, Hayes Middlesex UB4 8FE

Tel: +44 (0)20 8573 4444

Hayes Park Central

United Kingdom