

Fujitsu recommends Windows 10 Pro.

# Data Sheet

## FUJITSU Desktop ESPRIMO P758

### Excellent Performance, Expandability and Efficiency

The FUJITSU ESPRIMO P758 Desktop provides high expandability and solid performance for your challenging business applications. The 8th Gen Intel® Core™ processor combined with the DeskView manageability suite support advanced manageability capabilities. Its energy-efficient power supply and the innovative Low Power Active Mode feature help reduce your power bills while ensuring instant communication in your workplace. The optional Intel® Standard Manageability keeps administration costs low. Finally, EraseDisk ensures secure system retirement.

#### Expandability

Most expandable microtower business PC with rich configuration options

- Full-height PCIe slots for more add-on cards, more drives, along with a full-sized DVD

#### Easy serviceability and usability

Features designed for easy access, control and use of the system

- Tool-less access to components; front connectors and interfaces for ease of use with USB Type-C (USB 3.1 Gen2) front connector

#### Always Available Office PC - stay connected and save power

Be ready for instant communication and a significantly reduced energy bill

- Innovative Low Power Active Mode and energy-efficient integrated power supply

#### Advanced system management

Simple system administration for complex IT infrastructures

- Intel® Standard manageability technology (ISM) optional and DeskView manageability suite

#### Robust Security

Designed to protect data and hardware components against manipulation and theft

- Cable cover with lock option at the back to protect ports, cables and components from theft.
- Embedded Trusted Platform Module (TPM), Fujitsu Workplace Protect software with full disk encryption and system-level passwords. EraseDisk software and SmartCard are available as options



# Components

	ESPRIMO P758/E85+	ESPRIMO P758/E94+
<b>Processor</b>	Intel® Celeron® processor G4900 (2 Cores / 2 Threads, 3.10 GHz, 2 MB, Intel® UHD Graphics 610) Intel® Pentium® Gold G5400 processor (2 Cores / 4 Threads, 3.70 GHz, 4 MB, Intel® UHD Graphics 610) Intel® Core™ i3-8100 processor (4 Cores / 4 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630) Intel® Core™ i5-8400 processor (6 Cores / 6 Threads, 2.80 GHz, up to 4.0 GHz, 9 MB, Intel® UHD Graphics 630) * Intel® Core™ i5-8500 processor (6 Cores / 6 Threads, 3.00 GHz, up to 4.1 GHz, 9 MB, Intel® UHD Graphics 630) * Intel® Core™ i5-8600 processor (6 Cores / 6 Threads, 3.10 GHz, up to 4.3 GHz, 9 MB, Intel® UHD Graphics 630) * Intel® Core™ i7-8700 processor (6 Cores / 12 Threads, 3.20 GHz, up to 4.6 GHz, 12 MB, Intel® UHD Graphics 630) *	
	*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)	
<b>Operating systems</b>		
<b>Operating system pre-installed</b>	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home
	ESPRIMO P758/E85+	ESPRIMO P758/E94+
<b>Memory modules</b>	4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM	4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,666 MHz, UDIMM
	ESPRIMO P758/E85+	ESPRIMO P758/E94+
<b>Graphics</b>	Entry 3D: NVIDIA® Quadro® P400 , 2 GB, 3x miniDP Entry 3D: AMD® Radeon RX 460, 4 GB, 1x Dual Link DVI-D, 3x DisplayPort, 1x HDMI Entry 3D: AMD® Radeon R7 340, 2 GB, 1x Dual Link DVI-I, 1x DisplayPort Others: VGA Extension Card	Entry 3D: NVIDIA® Quadro® P400 , 2 GB, 3x miniDP Entry 3D: AMD® Radeon R7 340, 2 GB, 1x Dual Link DVI-I, 1x DisplayPort Others: VGA Extension Card
	ESPRIMO P758/E85+	ESPRIMO P758/E94+
<b>Hard disk drive</b>	HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch Intel Optane Memory (16 GB) SSD PCIe, 1024 GB M.2 NVMe Highend module SSD PCIe, 1024 GB M.2 NVMe module SSD PCIe, 1024 GB M.2 NVMe module, SED SSD PCIe, 256 GB M.2 NVMe Highend module SSD PCIe, 256 GB M.2 NVMe module SSD PCIe, 256 GB M.2 NVMe module, SED SSD PCIe, 512 GB M.2 NVMe Highend module SSD PCIe, 512 GB M.2 NVMe module SSD PCIe, 512 GB M.2 NVMe module, SED SSD SATA III, 1024 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch SSD SATA III, 256 GB, 2.5-inch SSD SATA III, 512 GB, 2.5-inch	HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch Intel Optane Memory (16 GB) SSD PCIe, 1024 GB M.2 NVMe Highend module SSD PCIe, 1024 GB M.2 NVMe module SSD PCIe, 1024 GB M.2 NVMe module, SED SSD PCIe, 256 GB M.2 NVMe Highend module SSD PCIe, 256 GB M.2 NVMe module SSD PCIe, 256 GB M.2 NVMe module, SED SSD PCIe, 512 GB M.2 NVMe Highend module SSD PCIe, 512 GB M.2 NVMe module SSD PCIe, 512 GB M.2 NVMe module, SED SSD SATA III, 1024 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch SSD SATA III, 256 GB, 2.5-inch SSD SATA III, 512 GB, 2.5-inch
<b>Hard disk notes</b>	SSD (Solid State Disk) SED (Self-Encrypting Drive)	

	ESPRIMO P758/E85+	ESPRIMO P758/E94+
<b>Optical drive</b>	MultiCard Reader 24in1 USB 2.0 3.5", USB 2.0 DVD-ROM DVD Super Multi, SATA DVD Super Multi ultra slim (tray), SATA BD Triple Writer SATA ultra slim (tray), SATA	MultiCard Reader 24in1 USB 2.0 3.5", USB 2.0 DVD-ROM DVD Super Multi, SATA DVD Super Multi ultra slim (tray), SATA BD Triple Writer SATA ultra slim (tray), SATA
	ESPRIMO P758/E85+	ESPRIMO P758/E94+
<b>Interfaces add on cards / components</b>	WLAN 802.11ac (2x2) PCIe x1 and BT 5 (dedicated regions only) WLAN 802.11ac (2x2) PCIe x1 (dedicated regions only) Gigabit Ethernet PCIe x1 eSATA Interface Dual serial card PCIe x1	WLAN 802.11ac (2x2) PCIe x1 and BT 5 (dedicated regions only) WLAN 802.11ac (2x2) PCIe x1 (dedicated regions only) Gigabit Ethernet PCIe x1 eSATA Interface Dual serial card PCIe x1
<b>Base unit</b>	ESPRIMO P758/E85+	ESPRIMO P758/E94+
<b>Mainboard</b>		
<b>Mainboard type</b>	D3601	
<b>Formfactor</b>	proprietary	
<b>Chipset</b>	Intel® Q370	
<b>Processor socket</b>	LGA 1151	
<b>Processor quantity maximum</b>	1	
<b>Supported capacity RAM (max.)</b>	64 GB	
<b>Memory slots</b>	4 DIMM (DDR4)	
<b>Memory frequency</b>	2,666 MHz	
<b>Memory notes</b>	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2666 MHz may be clocked down to 2400 MHz depending on processor and memory configuration	
<b>LAN</b>	10/100/1,000 MBit/s Intel® I219V	
<b>BIOS version</b>	AMI Aptio V UEFI Specification 2.6	
<b>BIOS features</b>	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)	
<b>Audio type</b>	On board	
<b>Audio codec</b>	Realtek ALC671	
<b>Audio features</b>	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound	
<b>I/O controller on board</b>		
<b>Serial ATA total</b>	5	
<b>thereof SATA III</b>	5	
<b>thereof eSATA</b>	2	
<b>Controller functions</b>	Serial ATA III (6 Gbit) NCQ AHCI	
<b>Interfaces</b>		
<b>Audio: line-in</b>	1	
<b>Audio: line-out</b>	1	
<b>Front audio: microphone</b>	1	
<b>Front audio: headphone</b>	1	
<b>USB 2.0 total</b>	6	
<b>USB 3.1 Gen1 (USB 3.0) total</b>	4	
<b>USB 3.1 Gen2 total</b>	3 and 2 optional via add on card	
<b>USB front</b>	2x USB 2.0; 2x USB 3.1 (gen2), 1x USB 3.1 (gen2) Type C; optional: 1x USB 3.1 Type-C (Gen2) via add on card and front adapter bay	
<b>USB rear</b>	2x USB 2.0; 4x USB 3.0; optional: additional 1x USB 3.1 Type C (Gen2) via add on card	

**Interfaces**

USB internal	2x USB 2.0
VGA	optional: via adapter card
DisplayPort	2
DVI	1 (DVI-D)
Serial (RS-232)	optional: serial port (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality, USB Typ C connector supports up to 15W

**Input device / components**

Input devices (optional)	Keyboard Mouse KBPC PX ECO Mouse M440 ECO
--------------------------	----------------------------------------------------

**Drive bays**

Drive bays total	6
2.5-inch internal bays	1
3.5-inch internal bays	2
3.5-inch external bays	1
5.25-inch external bays	2
Drive bay notes	5,25" bays: one bay in HH format, one bay for slim optical disc drive only; internal 3.5" bays: 3.5" drive (screwless) or 2.5" drive (screws; optional screwless). drive cage for external 3.5" bay and internal 2.5" bay: optional
M.2-2280	1 x on mainboard for SSD NVMe (PCIe 3.0 x4; up to 32Gbit/s; supports Intel® Optane™ technology)

**Slots**

PCI-Express 3.0 x1	1 x (174 mm / 6.85 inch)
PCI-Express 3.0 x4 (mech. x16)	1 x (210 mm / 8.27 inch)
PCI-Express 3.0 x16	1 x (240 mm / 9.45 inch) Full height

**Graphics on board**

Graphics brand name	Intel® UHD Graphics 610, Intel® UHD Graphics 630
Shared video memory	Up to half size of total system memory
TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel
TFT resolution (DVI)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel

**Graphics on board**

<b>TFT resolution (DisplayPort)</b>	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,440 x 1,440 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel	
<b>Graphics features</b>	Support for up to three independent displays DirectX® 12 HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.4 For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output for HDMI monitors	
<b>Graphics notes</b>	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz	
<b>Base unit</b>	ESPRIMO P758/E85+	ESPRIMO P758/E94+

**Electrical values**

<b>Power efficiency note</b>	power supply efficiency at 10% / 20% / 50% / 100% load for 230V: 80% / 85% / 88% / 87%; for 115V: 79% / 84% / 87% / 84%	power supply efficiency at 10% / 20% / 50% / 100% load for 230V: 87% / 91% / 94% / 93%; for 115V: 86% / 90% / 92% / 90%
<b>Rated voltage range</b>	100 V - 240 V	100 V - 240 V
<b>Rated frequency range</b>	50 Hz - 60 Hz	50 Hz - 60 Hz
<b>Operating voltage range</b>	90 V - 264 V	90 V - 264 V
<b>Operating line frequency range</b>	47 Hz - 63 Hz	47 Hz - 63 Hz
<b>Max. output of single power supply</b>	210 W	280 W
<b>Power factor correction/active power</b>	active	active
<b>Monitor outlet</b>	No	Switched
<b>Base unit</b>	ESPRIMO P758/E85+	ESPRIMO P758/E94+

**Power consumption**

<b>Power consumption note</b>	See white paper Energy Consumption
-------------------------------	------------------------------------

**Noise emission**

<b>Related Processors for noise</b>	Intel® Core™ i7 8700	Intel® Core™ i7 8700
<b>Standard noise emission</b>	2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74	2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
<b>Standard noise notes / description</b>	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
<b>Standard noise operation mode: CPU 50% load</b>	tbd	tbd
<b>Standard noise operation mode: HDD load</b>	tbd	tbd
<b>Standard noise operation mode: Idle mode</b>	tbd	tbd
<b>Standard noise operation mode: ODD load</b>	tbd	tbd

**Noise emission**

Standard noise operation mode: Office applications 2.0	tbd	tbd
--------------------------------------------------------	-----	-----

**Dimensions / Weight / Environmental**

Dimensions (W x D x H)	180 x 304 x 375 mm 7.09 x 11.97 x 14.76 inch
Operating position	Vertical
Weight	7 kg
Weight (lbs)	15.50 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

**Compliance**

Product	ESPRIMO P758/E85+	ESPRIMO P758/E94+
Model	MI6W	
Germany	GS (planned)	
Europe	CE	
USA/Canada	FCC Class B cTUVus	
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® in progress EPEAT® in progress (dedicated regions)	
China	CCC (planned) CCC (depending on configuration) CEL (Chinese energy label) TPM 2.0 for China (optional)	
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>	

**Additional Software**

Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Microsoft Office (buy license to activate the pre-installed Microsoft Office)	
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL	
Base unit	ESPRIMO P758/E85+	ESPRIMO P758/E94+

**Security**

Physical Security	Kensington Lock support Eye for padlock Integrated cabinet lock (optional) Cable Cover (optional); covers and secures the ports and cables on rear side)	Kensington Lock support Eye for padlock Integrated cabinet lock (optional) Cable Cover (optional); covers and secures the ports and cables on rear side)
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk (optional) Credential Guard Ready and Device Guard Capable (Windows 10, v. 1709) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces	Embedded security (TPM 2.0) EraseDisk (optional) Credential Guard Ready and Device Guard Capable (Windows 10, v. 1709) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces

<b>Security</b>		
<b>User Security</b>	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution)	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution)
<b>Workplace Embedded Tools</b>	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server Easy PC Protection	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server Easy PC Protection
<b>Manageability</b>		
<b>Manageability technology</b>	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) Intel® Standard Manageability (ISM) as option	
<b>Manageability software</b>	DeskView Client DeskView Instant BIOS Management	
<b>DeskView components</b>	BIOS Management incl. Security Inventory Management Driver Management Alarm Management	
<b>Supported standards</b>	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)	
<b>Manageability link</b>	<a href="http://www.fujitsu.com/fts/manageability">http://www.fujitsu.com/fts/manageability</a>	
<b>Miscellaneous</b>		
	Keyboard on (Special Fujitsu keyboard required) Keyboard on with one key (KBPX Eco, KB521) Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards Keyboard on with any key (USB) Thermal management Low Power Active Mode	Keyboard on (Special Fujitsu keyboard required) Keyboard on with one key (KBPX Eco, KB521) Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards Keyboard on with any key (USB) Thermal management Low Power Active Mode Extended lifetime
<b>Warranty</b>		
<b>Warranty period</b>	1 year (for countries in EMEIA)	
<b>Warranty type</b>	Bring-In / Onsite Service (for countries within region EMEIA, for all other countries depending on local regulations)	
<b>Warranty Terms &amp; Conditions</b>	<a href="http://support.ts.fujitsu.com/warranty">http://support.ts.fujitsu.com/warranty</a>	
<b>Product Related Services - the perfect extension</b>		
<b>Recommended Service</b>	- 9x5, Onsite Response Time: Next Business Day	
<b>Spare Parts availability</b>	5 years after end of product life	
<b>Service Weblink</b>	<a href="http://www.fujitsu.com/fts/services/support">http://www.fujitsu.com/fts/services/support</a>	

## Recommended Accessories

Order Code:  
BDL:BFS-B24-8-TE

**Display B24-8 TE Pro**



The FUJITSU Display B24-8 TE Pro is made for intensive office work. With visual and mechanical ergonomics this marble-grey display enables fatigue-free working for hours in front of the screen. The large 60.5 cm (23.8-inch) screen allows you to keep always track of all open applications. This high-quality display works unfailingly around the clock. Easy connectivity, manageability and usability help you increase your productivity.

Order Code:  
S26361-K1577-V140

**Wireless Mouse Touch WI910**



The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive surface that recognizes when your hand touches the mouse even before you move it. This provides nearly instantaneous wake-up from the intelligent energy saving sleep mode. Unbeatable responsiveness combines with features like switchable resolution, and three programmable buttons for a unique user experience.

Order Code:  
S26381-K465-L100

**Wireless Keyboard Set LX901**



The Wireless Keyboard LX901 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption.

S26381-K565-L4\*\* (\*\*:  
Country specific variation)



# More information

## Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO P758, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about FUJITSU Desktop ESPRIMO P758, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/fts/ESPRIMO](http://www.fujitsu.com/fts/ESPRIMO)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2018 Fujitsu Technology Solutions GmbH

## Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

## Contact

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)  
2018-07-04 EM-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2018 Fujitsu Technology Solutions GmbH