

# PalmSecure-F Pro



FUJITSU Biometric  
Authentication PalmSecure

## Award-Winning biometric authentication technology

- FAR: under 0.00001% and FRR: 0.01% (with 1 retry)
- PalmSecure-F Pro sensor is 50% smaller than legacy sensors
- Exposure time reduced to prevent blurring when capturing palm vein data which improves enrollment and authentication
- Frame rate is increased to capture a slowly moving palm
- Improvement in environmental tolerances especially temperatures and exposure to sunlight

## Fujitsu biometric authentication technology for any application.

Fujitsu PalmSecure technology is a palm vein based authentication solution that utilizes industry-leading vascular pattern biometric technology. The Fujitsu PalmSecure sensor uses near-infrared light to capture a person's palm vein pattern, generating a unique biometric template that is matched against pre-registered user palm vein biometric templates. And now Fujitsu has raised the bar with the PalmSecure-F Pro suite that enhances the capture and authentication of templates.

System integrators who want to provide their customers with the ultimate in biometric identification can now leverage F Pro products. The F Pro sensor is 50% smaller than the legacy sensor, making it easier to install when and where footprint really matters. Reduced exposure time enables the F Pro sensor to capture and authenticate templates more quickly, even the ability to capture a slowly moving palm. And changes to environmental tolerances enable F Pro to operate in higher ambient sunlight and a wider range of temperature conditions.

The palm vein device can only recognize the pattern if the blood is actively flowing within the individual's veins, which means that forgery is virtually impossible. This advanced, vascular pattern recognition technology provides highly reliable authentication. The PalmSecure technology false accept rate is just 0.00001 percent with an exceptional false reject rate of 0.01 percent, all in a small form factor that generates extremely fast authentication, usually under one second.

The PalmSecure-F Pro suite consists of the enhanced F Pro, the F Pro and U-Guide for enrollment, the PalmSecure-F Pro Mouse and hand guide that eliminates the need to enter passwords and the F Pro Standard and hand guide.






PalmSecure V2  
sensor  
<35 x 35 x 27mm>



PalmSecure-F Pro  
sensor  
<29 x 29 x 13mm>



## PalmSecure-F Pro Sensor Specifications

Item		Specifications		
Product Name		PalmSecure-F Pro	PalmSecure-F Pro Standard	PalmSecure-F Pro Mouse
Outlook				
Dimensions		29(W)×29(D)×13(H) mm	46(W)×46(D)×16(H) mm	50(W)×90(D)×26(H) mm
Weight		Below 12g	Below 25g (without cable)	Below 80g (with cable)
Host interface		USB2.0 (only Hi Speed) (USB3.0 port is required when using high-power mode)		
Interface cable		USB Cable (up to 4m)		
Mouse type		-		laser mouse (1,000 dpi)
Sensor surface		Glass		
Voltage/current		DC5V, 500mA (max at normal-power mode)		
		DC5V, 900mA (max at high-power mode)		
		50 mA (max at power saving mode)		
power source		USB bus power		
Temperature		-40 to 85 degrees Celsius	5 to 35 degrees Celsius	
Humidity		20 to 90%RH (Non-condensing)	20 to 80%RH (Non-condensing)	
Lighting environment	Authentication	<Normal-power mode> Natural light (sunlight): under 45,000lu		
		<Normal-power mode> Incandescent/Halogen lights: under 9,000lux		
		<High-power mode> Natural light (sunlight): under 80,000lu		
		<High-power mode> Incandescent/Halogen light: under 18,000lux		
	Enrollment	Natural light (sunlight): under 5,000lux		
Incandescent/Halogen lights: under 1,700lux				
Authentication rate		When FRR is 0.01% (with 1 retry), FAR is Below 0.00001%		



### Contact

FUJITSU LIMITED

Shiodome City Center, 5-2, Higashi-shimbashi

1-chome, Minato-ku, Tokyo 105-7123, Japan

Tel: +81-3-6252-2662

URL: <https://www.fujitsu.com/global/services/security/offerings/biometrics/palmsecure/>

FUJITSU FRONTECH LIMITED

1776 Yanokuchi, Inagi-shi, Tokyo 206-8555, Japan

URL: <http://www.fujitsu.com/jp/group/frontech/en/>

Contact: <http://www.fujitsu.com/jp/group/frontech/en/contact/>

© Copyright 2018 Fujitsu Limited. Fujitsu, the Fujitsu logo, and the PalmSecure logo are trademarks or registered trademarks of Fujitsu Limited in Japan and other countries. Other company, product and service names may be trademarks or registered trademarks of their respective owners. Technical data subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.