

Data Sheet

FUJITSU Display V24T-2R LED

Display

Value display: 60.4cm (23.8-inch) widescreen

The FUJITSU Display V24T-2R LED comes in a 16:9 format with a trendy style. There is no compromise in picture quality and energy efficiency. It is the best choice to get high pixel density with restricted desk space. It is easy-to-use and once it is installed you never have to adjust it again – proven Fujitsu quality.

Plane to Line Switching (PLS) technology with 1,920 x 1,080 pixels high resolution for pin sharp pictures.

< 1W/inch typical power consumption

Includes both Analog (VGA) or HDMI display inputs

Low blue light mode

Flicker-free backlight

Color: ■



Technical details

Special Features	Plane to Line Switching (PLS) technology; Frameless design; Low blue light mode; Flicker-free backlight
Stand details	
Stand	removable
Picture height over desk (mm)	80 mm
Tilt angle	-5° / +20°
Picture performance	
Panel and backlight	Plane to Line Switching (PLS) technology /LED
Screen Surface Treatment	Anti-glare, 3H hard coating
Contrast – typical	1000:1
Contrast – advanced	30,000,000:1
Viewing angle (h/v) - typical	178°/178° (CR>10)
Color performance	16.7 million colors (Hi-FRC)
Brightness – typical	250 cd/m ²
Low blue light mode	Supported
Flicker-free backlight	Supported
Size and Resolution	
Aspect ratio	16:9
Diagonal Size	60.4 cm (23.8-inch)
Resolution (native)	1920 x 1080 (recommended)
Resolution (interpolated)	1680 x 1050 pixel, 1440 x 900 pixel, 1366 x 768 pixel, 1280 x 1024 pixel, 1280 x 720 pixel, 1024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture Size	527.04 x 296.46 mm
Pixel Pitch	0.2745 mm
Connectivity	
VGA/D-SUB	1 x D-SUB
DVI	N/A
HDMI	1 x HDMI
Audio signal input	3.5 mm stereo phone jack
Audio sound output	2 x 2 W
OSD Languages and setting options	
Languages	English, French, German, Italian, Japanese, Korean, Espanola, Portuguese, Russian, Turkish, Simplified Chinese, Traditional Chinese
Brightness / Contrast / Color	Brightness, Contrast, Color Temperature
Image adjust	H-Position, V-Position, Clock, Phase
On Screen Display (OSD)	Language, H-Position, V-Position, Timer, Transparency
Setup	Picture Mode, Signal Source, Aspect Ratio, DCR
Factory Reset	Reset
Power consumption (typical)	
Soft switch off	<0.5 W
Operating maximum brightness	<30W
Power supply display	External power supply
Electrical values	
Rated voltage range	100 V – 240 V
Rated frequency range	50 Hz – 60 Hz
Protection class	1
Compliance	
Global	CB (planned to have)
Quality and Reliability	
MTBF (demonstrated)	30,000h
Dimensions / Weight / Environmental	
Dimension with stand (W x D x H)	541mm x 201mm x 418.7mm
Weight (Monitor only)	2.76 kg

Miscellaneous	
Miscellaneous	VESA DDC/CI, Flat Display Mounting Interface VESA MIS-D 75C, Kensington lock
Color	Black
Package content	
Display delivered accessories	Power cable for wall socket (UK) 1.5m, D-SUB Data cable 1.5m, User Manual
Display delivered accessories notes	Data cables and power cable detachable on display
Order information	
Order Code	HLMNR13UKB-R1 (Black)
EAN Code	888851249374 (Black)
Warranty	
Standard Warranty	3 years (depending on country)
Service level	Carry In
