Datasheet Fujitsu Interactive Panel IW652 Pro/ IW752 Pro/IW862 Pro



Fujitsu recommends Windows 11 Pro

New way achieves excellence

Fujitsu Interactive Panel is the essential hub for modern meeting spaces as well as digitize classrooms. Compared to projector-based systems, the Fujitsu Interactive Panel offers unparalleled visual performance and fosters collaboration to elevate meeting and teaching efficiency.

Interactive display with 4k resolution

• Available In 65" / 75" / 86", offers big viewing experience

High accuracy touch experience

- Intuitive 20 points of touch
- Resistant to optical interference (use as usual under direct sunlight)
- Resistant to shielding
- Rapid response, fluent in writing & demonstration

Durable whiteboard surface

• Anti-glare 9H tempered glass

Multi OS + multi modules

- Seamless switching between OS
- Built-in Android + Pluggable PC module
- Concealed WIFI module compatible with WIFI 6 Standard



Specification

Picture performance	
Panel backlit	DLED
Screen surface treatment	AG 9H tempered glass
Contrast – typical	65", 75", 86": 1200:1
Viewing angle (h/v) - typical	178°
Color performance	1.07 billion colors
Brightness	400 cd/m² (w Glass, max), 350 cd/m² (w Glass, typ)
Flicker-free technology	Support
Low Blue Light	Support
Anti-glare filter	Support
Built-in Ambient Light Sensor	Yes
Picture in Picture (PIP) mode	Support, with touch
Size and resolution	
Aspect ratio	16:9
Resolution (native)	3840 (H) x 2160 (V)
Picture size (H x V)	65": 1,428.48 x 803.52 mm / 75": 1,649.664 x 927.936 mm / 86": 1,895.04 x 1,065.96 mm
Pixel pitch	65": 0.37 2mm / 75": 0.4296 mm / 86": 0.4935 mm
Response time	8 ms (Typ)
Refreshing frequency	60 Hz
Connectivity	
VGA / D-SUB IN	1 x D-SUB
HDMI	1 x HDMI OUT (4K), 3 x HDMI IN (HDMI 2.0)
USB	1 x USB 2.0
	6 x USB 3.0 (including 2 USB ports in front, Touch out)
USB Type-C®	1 x USB Type-C®
Audio in	1 x 3.5 mm stereo phone jack
Audio output	1 x Audio out
RS232 control	1 x RS232
Built-in speaker	Yes, 2 x 16 W
LAN IN	1 x GIGABIT LAN (RJ45)
LAN OUT	1 x GIGABIT LAN (RJ45)
TOUCH OUT	2 x TOUCH OUT (USB 3.0)
SPDIF	1 x SPDIF
Wi-Fi	Yes, dual band, support Wi-Fi 6
Bluetooth	5.0
Touch system	
Sensing type	Infrared recognition
Touch point	20 points touches, 10 points writing
Minimum object size	3 mm
Writing height	≤2 mm
Writing double colors with double pens simultaneously	Support
Touch tool	Finger / Passive infrared pen / Active infrared pen
Response time	≤10 ms

Communication mode	Full-speed USB (driver free)
Realtime 4k screen capture and	Support
annotation	
Wireless screen mirroring	
Wireless screen mirroring	Support
PIN code connection mode	Support both static and dynamic pin codes
Maximum number of split screens /	9
devices projecting to the panel	
simultaneously (Panel Standalone Android	
Mode) Self-Hotspot screen mirroring	Cumport
Native AirPlay protocol for screen	Support
mirroring	Support
Native Chromecast protocol for screen mirroring	Support
Native Miracast protocol for screen	Support
mirroring	
Mirroring of panel display to client devices	Support
Reversely control Windows / MacOS	Support, Client software required
during screen mirroring	
Multi-Panels synchronization	Support
Built-in moderator console	Yes
Power consumption (typical)	
Soft switch off	≤0.5 W
Overall power (max power)	65": 450 W / 75": 550 W / 86": 650 W
Electrical values	
Rated voltage range	100 V – 240 V
Rated frequency range	50 Hz – 60 Hz, 65": 4.5 A / 75": 5.5 A / 86":6.5 A
Quality and reliability	
MTBF	50,000 h
System	
CPU (Central Processing Unit)	Quad core A73 x 4 (1.8Ghz)
GPU (Graphics Processing Unit)	Quad core Mali G52
System memory	8 GB
Storage	64 GB
OS	Android 11.0
Dimensions / Weight / Environmental	
Key location & number	Front physical keys, 1
Dimension L x H x D	65": 1,488.4 x 896.6 x 86.4 mm / 75": 1,709.1 x 1,019.5 x 85.7 mm / 86": 1,957 x 1,159 x 86 mm
Dimension (package) L x W x H	65": 1,628 x 208 x 1,005 mm / 75": 1,863 x 225 x 1,140 mm / 86": 2,110 x 225 x 1,283 mm
Net weight	65": 38 kg / 75": 49.5 kg / 86": 64.6 kg
Gross weight	65": 48.5 kg / 75": 63.4 kg / 86": 82.28 kg
Thickness of machine and wall mount	65": 116.4 mm (9,060G) / 75": 115.7 mm (9,060G) / 86": 116 mm (9,060G)
Wall-hanging screw spec	M8 x 25 mm
VESA	65": 600 x 400 mm / 75": 800 x 400 mm / 86": 800 x 600 mm
Miscellaneous	
Color	Black
Password lock	Support
USB key Panel lock	Support
Magnetic pen holder	Yes

Datasheet Fujitsu Interactive Panel IW652 Pro/ IW752 Pro/ IW862 Pro

Fujitsu recommends Windows 11 Pro

Smart shared USB	Support, all USB 3.0 ports
Switch sources	Support
Scheduled power up / shutdown	Support
Multiple-windows	Support
Cross Platforms and Cross Applications	Built-in, Realtime and not required same network/ Wi-Fi
Accessories	
AC power cable	British Standard Power Cord (3 meters), EU Power Cord (3 meters)
USB cable	1 x USB 2.0 (5 meters)
HDMI cable	1 x HDMI (3 meters)
Writing pen	2
Remote control	1
Operation instruction	1
Order information	
Order code	65": HLIWB0024A-01 / 75": HLIWB0027A-01 / 86": HLIWB0029A-01
EAN code	65": 8888551427536 / 75": 8888551427543 / 86": 8888551427567
Warranty	
Standard warranty	3 years (depending on country)
Service level	On-site

More information

Moving forward for a sustainable world - Fujitsu Uvance



The word "Uvance" embodies a concept of "Making all (Universal) things move forward (Advance) in a sustainable direction.

Fujitsu Uvance will leverage Fujitsu's technological capabilities and problem-solving expertise across seven key focus areas, including Sustainable Manufacturing, Consumer Experience, Healthy Living, Trusted Society, Digital Shifts, Business Applications, and Hybrid IT, to offer unprecedented value to customers, while contributing to the achievement of its

ultimate purpose —"to make the world more sustainable by building trust in society through innovation."

Through Fujitsu Uvance, we are committed to transforming the world into a place where people can live their lives, enjoying prosperity and peace of mind. Empowering each other to make the world more sustainable.

For more information of Fujitsu Uvance, please visit https://www2.fujitsu.com/global/uvance

Driving customer success with Fujitsu's complete portfolio of service offering

To grow in an uncertain world, it is imperative to stay resilient and agile to respond complex and unforeseen challenges.

Under the global business brand – Uvance, Fujitsu provides a full range of reliable and best-in-class product, service, and solution offerings with digital innovation, from sustainable manufacturing to smart city ecosystem, to create a more sustainable world and resolve social issues. This empowers customers to strengthen resilience through Fujitsu's trusted solutions using cutting-edge technologies, while increasing their business agility and improving the reliability of their IT operations.

For more information, please visit https://www.fujitsu.com/global

Contact Us

HONG KONG

Fujitsu Business Technologies Asia Pacific Ltd.

Tel: (852) 3910-8228

Email: fpca.hksales@hk.fujitsu.com

hk.fujitsu.com/pc

INDONESIA

PT Fujitsu Indonesia

Tel: (62) 21-570-9330

Email: marketing@id.fujitsu.com

id.fujitsu.com/pc

TAIWAN

Fujitsu Taiwan Ltd.

Tel: (886) 2-2311-2255

Email: ftl.lifebook@fujitsu.com

tw.fujitsu.com/pc

SINGAPORE

Fujitsu Asia Pte Ltd.

Tel: (65) 6512-7555

Email: fapl.info@fujitsu.com

sg.fujitsu.com/pc

PHILIPPINES

Fujitsu Philippines, Inc.

Tel: (63) 2-8841-8488

Email: fpi-dl-fpp.pre-sales@fujitsu.com

ph.fujitsu.com/pc

THAILAND

Fujitsu (Thailand) Co., Ltd.

Tel: (66) 0-2302-1500

Email: info.th@fujitsu.com

th.fujitsu.com/pc

Note: For countries not listed above, please contact Hong Kong office.

CHINA

Fujitsu (China) Holdings Co., Ltd. -

PC China Division

Tel: 86 (21) 58871000-8721

Email: fpcacn.support@cn.fujitsu.com

cn.fujitsu.com/pc

MALAYSIA

Fujitsu (Malaysia) Sdn. Bhd

Tel: (60) 3-8230-4188

Email: askfujitsu.my@fujitsu.com

my.fujitsu.com/pc

VIETNAM

Fujitsu Vietnam Limited

Tel: (84-24) 2220-3113

Email: sales-vn@fujitsu.com

vn.fujitsu.com/pc

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/global/about/resources/terms/.

© 2024 Fuiitsu Business Technologies Asia Pacific Limited