

製品名		Catalys9500シリーズ									
		C9500-32C	C9500-32QC	C9500-48Y4C	C9500-24Y4C	C9500-24Q	C9500-12Q	C9500-40X	C9500-16X	C9500-48X	C9500-24X
手配型名		LCD95E***	LCD95F***	LCD95G***	LCD95H***	LCD95C***	LCD95B***	LCD95A***	LCD95D***	LCD95D***	LCD95A***
インターフェース	1G port density	-	-	48 (96*)	24 (48*)	-	-	48 (96)**	24 (48)**	48	24
	10G port density	-	-	48 (96*)	24 (48*)	-	-	48 (96)**	24 (48)**	48	24
	25G port density	-	-	48 (96*)	24 (48*)	-	-	-	-	-	-
	40G port density	32 (64*)	32 (64*)	4 (8*)	4 (8*)	24 (48)	12 (24)	2 (4)	2 (4)	-	-
	100G Port Density	32 (64*)	16 (32*)	4 (8*)	4 (8*)	-	-	-	-	-	-
	10G port density with breakout cable	-	-	-	-	48 (96)	48 (96)	8 (16)	8 (16)	-	-
	25G port density with breakout cable	-	-	-	-	-	-	-	-	-	-
諸元	ラックユニット数	1RU									
	外形寸法 (W×D×H)	444.5 x 538.5 x 43.9 mm			444.5 x 457.2 x 43.9 mm			444.5 x 546.6 x 43.9 mm			
	重量	11.63kg	9.91kg	9.96kg	9.52kg	11.68kg	11.68kg	11.68kg	10.7kg	12.18kg	11.2kg
	入力電源	90 to 264 VAC									
	周波数	50Hz~60Hz									
	電源容量	1600W	650W	650W	650W	950W	950W	950W	950W	950W	950W
	消費電力(最大)	1600W	650W	650W	650W	950W	950W	950W	950W	950W	950W
温度	発熱量	1064BTU/H	532BTU/H	544BTU/H	426BTU/H	2900BTU/H	1536BTU/H	1467BTU/H	941BTU/H	941BTU/H	1467BTU/H
	動作時	0° to 40°C									
	保管時	-20° to 65°C									
湿度	動作時	5~90%以下 (結露しないこと)									
	保管時	5~95%以下 (結露しないこと)									
適合規格	安全基準 及びEMC (電磁適合性)	C9500-12Q, C9500-24Q, C9500-40X, C9500-16X ● UL 60950-1 ● CAN/CSA-C22.2 No. 60950-1 ● EN 60950-1 ● IEC 60950-1 ● AS/NZS 60950-1 ● GB4943				47 CFR Part 15 Class A CNS13438: 2006 Class A EN 300 386 V1.6.1 EN61000-3-2: 2014 EN61000-3-3: 2013 ICES-003 Issue 6: 2016 Class A KN 32: 2015 Class A TCVN 7189: 2009 Class A EN 55032:2012/ AC:2013 Class A EN 55032:2015 Class A CISPR 32 Edition 2 Class A-2/2015.04 Class A V-3/2015.04 Class A CISPR24: 2010 + A1: 2015 EN 300 386 V1.6.1 EN55024: 2010 + A1: 2015 KN35: 2015 TCVN 7317: 2003					
		C9500-32C, C9500-32QC, C9500-24Y4C, C9500-48Y4C ● IEC 60950-1 plus Am1, Am2 Am9, Am10, Am11, Am12 and all deviations and differences ● AS/NZS 60950.1.2011 ● CAN/CSA-C22.2 No. 60950-1-07 ● GB 4943-95 ● EN 60950-1; 2006 plus Am1, Am 2, Am9, Am10, Am11, Am12 and all deviations and differences ● NOM-019-SCFI-1998 ● UL 60950-1, Second Edition									

\* Feature not available at FCS, will be available in future software releases  
 \*\* with uplink module.