

Fujitsu Optical Components Line-up



Part Number	Data Rate [Gbps]	Wavelength [nm]	Max Power Consumption [W]	Tc [°C]	Size (L x W x H) [inches]	Distance [km]	Dispersion [ns/nm]	400Gbps	300Gbps	200Gbps	100Gbps
OIF 168pin Coherent Transceiver											
FIM85200	127.156	Full C-band Tunable (50GHz spacing)	(*1)	0 to 70	5.0 x 4.0 x 0.59	±40ns/nm					
CFP2 ACO Transceiver											
(Class2) FIM38550/110	(*2)	Full C-band Tunable	12	0 to 70	4.23 x 1.63 x 0.49	(*2)					
CFP2 DCO Transceiver											
FIM38750(*3)	400(*2)	Full C-band Tunable	(*1)	0 to 70	4.23 x 1.63 x 0.49	Metro Regional (*1)					
QSFP56-DD / OSFP DCO Transceiver											
FIM38800(*3)	400	Full C-band Tunable	(*1)	0 to 70	OSFP	120km					
FIM38850(*3)	400(*2)		(*1)	0 to 70	OSFP	(*2)					
FIM38900(*3)	400		(*1)	0 to 70	QSFP56-DD	120km					
FIM38950(*3)	400(*2)		(*1)	0 to 70	QSFP56-DD	(*2)					

(*1) Available upon request (*2) Depends on modulation format and FEC (*3) Under development

Part Number	Baud Rate (Gbaud)	Drive Method	Wavelength [nm]	Drive Voltage (V _π) [V]	Alpha Parameter	RF Connector	Tc [°C]	Size (L x W x H) [inches]	DP-16QAM	DP-QPSK	
LiNbO₃ Modulator											
FTM7992HM	64	Single - Ended	C-band	≤4.2 (at 64Gbps)	0	G3PO	-5 to 75	3.22 x 0.49 x 0.26			
FTM7995HN	45		C-band	≤4.5 (at 45Gbps)		GPP0		3.56 x 0.52 x 0.27			
FTM7979HKA (SFF type)	32		C-band L-band	≤ 3.5 (at 32Gbps)		FPC		3.23 x 0.39 x 0.22			
FTM7977HQA			GPP0	3.56 x 0.52 x 0.27							

● 400G ● 300G ● 200G ● 150G ● 100G

Part Number	Baud Rate (Gbaud)	3dB Cut-off Freq. [GHz]	Wavelength [nm]	Output Volt. Swing [mV _{p-p}]	Power Consumption [W]	RF Connector	Tc [°C]	Size (L x W x H) [inches]	DP-16QAM	DP-QPSK	
Integrated Coherent Receiver											
FIM24902 (VOA Integrated)	64	Typ. 40	1528 to 1567	300 to 700	Typ. 1.4	CPW	-5 to 85	0.91 x 0.47 x 0.22			
FIM24725 (VOA Integrated)	32	Typ. 22		300 to 900	Typ. 1.4	CPW		0.91 x 0.47 x 0.22			

● 400G ● 200G ● 100G

Part Number	Data Rate [Gbps]	Wavelength [nm]	Max Power Consumption [W]	T _c [°C]	Size (L x W x H) [inches]	Distance [km]	Dispersion [ps/nm]	400G Ethernet	100G OTN (OTU-4)	100G Ethernet
100G QSFP28 Transceiver										
FIM37801/112	103.1	L0: 1294.53 to 1296.59 L1: 1299.02 to 1301.09 L2: 1303.54 to 1305.63 L3: 1308.09 to 1310.19	4.8	0 to 70	2.8 x 0.72 x 0.33	40 (*2)				
FIM37801/162	103.1/111.8		4.7							
FIM37801/172	103.1		4.7							
FIM37811/112	103.1		5	-40 to 85	40 (*2)					
400G QSFP56-DD / OSFP Transceiver										
FIM39110(*4)	400	L0: 1264.5 to 1277.5 L1: 1284.5 to 1297.5 L2: 1304.5 to 1317.5 L3: 1324.5 to 1337.5	12	0 to 70	QSFP56-DD	2				
FIM39310(*4)						6				
FIM39510(*4)						10				
FIM39210(*4)						2				
FIM39410(*4)						6				
FIM39610(*4)						10				

- (*1) 30km interoperability w/ existing ER4 (w/o FEC)
40km w/ host card's RS(528, 514) FEC
- (*2) 40km w/ host card's RS(528, 514) FEC
- (*3) 103.1Gbps : 30km interoperability w/ existing ER4 (w/o FEC)
40km w/ host card's RS(528, 514) FEC
111.8Gbps : 30km w/ host card's RS(528, 514) FEC
- (*4) Under development

■ All of Fujitsu's transceivers, modulators and receivers are RoHS10 compliant.

Fujitsu Optical Components America, Inc
1280 East Arques Ave,
Sunnyvale, CA 94085-4701, USA
Phone: +1 408-746-6000

Fujitsu Optical Components Italy S.p.A.
Viale Monza 259, 20126 Milano, Italy
Phone: +39 02 26294 283

Asia Business Unit
Room 06, 28/F, Greenfield Tower, Concordia Plaza,
No.1 Science Museum Road, Tsim Sha Tsui East,
Kowloon, Hong Kong
Phone: +852-2881-8495

Fujitsu Optical Components Limited

4-1-1 Kamikodanaka, Nakahara-ku
Kawasaki-shi, Kanagawa, Japan 211-8588
Phone: +81-44-754-3757
Web: <http://www.fujitsu.com/jp/group/foc/>