Specifications

TeamPoS8000			Model C300 and Cs300
	СРИ		Intel® Core™ i3-12100 series
Main Unit	Supported OS		Windows [®] 10 IoT Enterprise 2021 LTSC (64 bit)
	Memory		8GB (standard)
	Storage		SSD (M.2) 128GB x1
	Operator display		15.6 inch LCD 16:9, Full HD (1,920 x 1,080)
	Touch panel		P-CAP (projected capacitive)
	I/O basic		USB-A x4 Powered USB (24V) x1, (12V) x3 RS232C (COM, RJ45) x2 LAN(RJ45) x1 For drawer I/F x1 For 2nd display (HDMI) x1 USB-C x1 (only for "2nd LCD") (Some ports are used for integrated printer and camera scanner)
	LAN		10 BASE-T/100 BASE-TX/1000 BASE-T
	Power supply		AC power brick (100-240V)
	Cooling		Fan
	Color		Two-tone
	Dimensions		369 (W) x 265 (D) x 382 (H) mm (LCD tilt 0°)
	Weight		Approximately 11 kg (C series) / 15kg (Cs series)
	1 station thermal printer (Integrated)		Paper width: 58 mm (default) and 80 mm, Printing speed: Max. 350 mm/sec.
	Camera scanner (Integrated on Cs series)		Cs series JAN/EAN-13/8, UPC-A/E, NW-7, CODE39, CODE128, ITF, GS1 DataBar QR code
Peripherals (Options)	2nd LCD		15.6 inch LCD 16:9, Full HD (1,920 x 1,080) Touch panel: P-CAP (projected capacitive)
	Customer display		ANK (20 digits x 2 lines) or Graphic (16 digits x 3 lines)
	Keyboard		88 keys with/without key cylinder and key set
	MSR on LCD		ISO 1/2/3
	Touch scanner		CCD Touch scanner JAN/EAN-13/8, UPC-A/E, NW-7, CODE39, CODE128, ITF, GS1 DataBar Readable barcode width: Up to 65 mm (including left and right margin)
	Cash drawer	Standard type	5 bill compartments, 6 coin compartments with media slot
		Compact type	3 bill compartments, 6 coin compartments with media slot

* Product specifications are subject to change without notice. All data is based on internal testing, and results may vary with the conditions.

รบรู้ทรง TeamPoS8000 Model C300 and Cs300

All-in-one POS combining sophistication and flexibility with a stylish design



Use only the Fujitsu Frontech-specified supplies listed above for this POS terminal.

If any other supplies are used, personal injury to the user or property damage may result, and the Fujitsu POS terminal may have a shortened life or fail. Windows is a trademark or registered trademark of Microsoft Corporation in the United States and/or other countries. Intel is a trademark or registered trademark of Intel Corporation or its subsidiaries in the United States and other countries.

QR Code is registered trademark of DENSO WAVE INCORPORATED.

All other brand names and product names are the trademarks or registered trademarks of their respective owners.

Fujitsu Frontech Limited

Frontline Solution Business Unit 1776 Yanokuchi, Inagi-shi, Tokyo 206-8555, Japan https://www.fujitsu.com/jp/group/frontech/en/ Inquiry : https://www.fujitsu.com/jp/group/frontech/en/contact/



TeamPoS8000 Model C300 and Cs300

All-in-one POS combining sophistication and flexibility with a stylish design

- Large display with thin and slim bezel
- Accommodate a variety of checkout styles and installation layouts
- □ Safe and secure operation
- **D** High-performance processors and rich peripherals

Minimum All in one

This slim integrated model has a vertically integrated receipt printer and scanner



Model C300



Model Cs300

Different checkout styles are possible with the same model



Human Centric




Layout with operation area close at hand



Easy maintenance

Easy tool-free maintenance and user-friendly structure





High-performance processor Intel® Core™ i3-12100 series



