

ObettPOS495

[Major Characteristics]

- Borderless Design with Tru Flat, P-Cap multi-touch Technology
- Stylish and rugged housing
- Compact design to application requirement
- Powerful technology

[Easy and Simple Service]

- Slide in/out HDD replacement
- Rich I/O ports provides excellent peripheral Connectivity.



■ Features




P-Cap Multi-Touch



Wide Selection of Peripherals



100*100 mm
vesa mounting holes in center



Pan Angle 0°to90°



Rich I/O Ports provide
excellent Peripheral connectivity



Slide in/out HDD replacement

■ Specification

Model Name	OBETT 495
Motherboard	C48
Processor	Intel D525 Duo Core 1.8G/L2/1M
Chipset	CPU with Graphic built in + ICH 8M
System Memory	2x SO-DIMM slot up to 4GB DDR3 800MHz
Graphic Memory	Share system memory up to 256MB
LCD / Touch Panel	
LCD Size	15" TFT LCD
Brightness	250 cd/m²
Resolution	1024x768
Touch Screen	True-Flat Resistive touch or True-Flat Projected-Capacitive touch
Tilt Adjustment	0°~ 90°(right to left)
Storage Device	
Hard Drive	One 2.5" SATA HDD bay
Flash Memory	SATA pSSD flash card (option)
Expansion	
Mini PCI-E Slot	1
External I/O Ports	
USB 2.0	4
Serial Port	4 x RJ45 COM ports (COM1 & COM2 standard RS-232; COM3 & COM4 powered COM with power enable / disable by BIOS setting COM3 default 5V/ COM4 default 12V)
Parallel Port	1
LAN	1 x RJ-45 (10/100/1000Mbps Giga LAN)
Second Display	1 (Female)
Cash Drawer Port	1 x RJ-11 (12V / 24V)
DC Jack	1
Audio Jack	1 x Line Out, 1 x MIC-in
Power	
Power Supply	Adapter(DC90W, 19V, 4.7A)
Control / Indicator	
Power Button	1
Peripheral	
MSR	3 Tracks MSR (USB)
Finger Printer	1 (USB)
iButton	1(COM), choose either i-Button or Fingerprint
Second display	Optional 8.4" / 15" 2 nd display without touch
Customer display	Flush mount VFD display 2 x 20 characters (COM)
Certificate	
EMC & Safety	FCC Class A / CE Mark / LVD
Environment	
Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	20% ~ 85% RH non-condensing
Storage Humidity	20% ~ 85% RH non-condensing
Color	Black/Shiny White
Dimensions (W x D x H)	LCD 90° tilt angle: 363 x 206 x 315mm (14.3" x 8.1" x12.4")
Weight	7kg (15.4lbs)
Mouning	100 x 100 mm VESA mounting hole for panel PC type
OS Supported	Windows XP Professional, Window Embedded POS Ready 2009, XP Embedded, XP professional for Embedded, WinCE, Windows 2000 Professional for Embedded, Windows 7, Linux

FUJITSU KOREA LIMITED

Jongno1, Jongno-gu, Seoul, Republic of Korea
 URL: www.fujitsu.com/kr
 Phone: +82-2-3787-5762 FAX : +82-2-738-1355