

PalmSecure-F Pro

FUJITSU Biometric
Authentication PalmSecure



Award-Winning biometric authentication technology

- FAR: below 0.00001% and FRR: 0.01% (with 1 retry)
- PalmSecure-F Pro sensor is 50% smaller than the prior generation sensor
- Exposure time reduced to prevent blurring when capturing palm vein data which improves enrollment and authentication
- Frame rate is increased to capture a slowly moving palm
- Improvement in environmental tolerances especially temperatures and exposure to sunlight

Fujitsu biometric authentication technology for any application.

Fujitsu PalmSecure technology is a palm vein-based authentication solution that utilizes industry-leading vascular pattern biometric technology. The Fujitsu PalmSecure sensor uses near-infrared light to capture a person's palm vein pattern, generating a unique biometric template that is immediately encrypted in the sensor before transmission. And now Fujitsu has raised the bar with the PalmSecure-F Pro suite that enhances the capture and authentication of templates. System integrators who want to provide their customers with the ultimate in biometric identification can now leverage F Pro products. The F Pro sensor is 50% smaller than the prior generation sensor, making it easier to install when and where a footprint really matters. Improved capture time enables the F Pro sensor to capture and authenticate more quickly, even the ability to capture a slowly moving palm. And changes to environmental tolerances enable F-Pro to operate in higher ambient sunlight and temperature conditions. This advanced, vascular pattern recognition technology provides highly reliable authentication. The PalmSecure technology false acceptance rate is below 0.00001 percent with an exceptional false rejection rate of 0.01 percent, all in a small form factor that generates extremely fast authentication, usually under one second. The PalmSecure-F Pro suite consists of the enhanced F Pro sensor, F Pro Mouse and F Pro Standard.



PalmSecure V2
sensor
<35 x 35 x 27mm>



PalmSecure-F Pro
sensor
<29 x 29 x 13mm>



PalmSecure-F Pro Sensor Specifications

Item	Specifications		
Product Name	PalmSecure-F Pro	PalmSecure-F Pro Standard	PalmSecure-F Pro Mouse
Outlook			
Dimensions	29(W)×29(D)×13(H) mm	46(W)×46(D)×16(H) mm	50(W)×90(D)×26(H) mm
Weight	Below 12g	Below 25g (without cable)	Below 80g (with cable)
Host interface	USB2.0 (only Hi Speed) (USB3.0 port is required when using high-power mode)		
Interface cable	USB Cable (up to 4m)		
Mouse type			laser mouse (1,000 dpi)
Sensor surface	Glass		
Voltage/current	DC5V, 500mA (max at normal-power mode)		
	DC5V, 900mA (max at high-power mode)		
	50 mA (max at power saving mode)		
power source	USB bus power		
Temperature	-40 to 85 degrees Celsius	5 to 35 degrees Celsius	
Humidity	20 to 90%RH (Non-condensing)	20 to 80%RH (Non-condensing)	
Lighting environment	Authentication	<Normal-power mode> Natural light (sunlight): under 45,000lu	
		<Normal-power mode> Incandescent/Halogen lights: under 9,000lux	
	Enrollment	<High-power mode> Natural light (sunlight): under 80,000lu	
		<High-power mode> Incandescent/Halogen light: under 18,000lux	
Authentication rate	When FRR is 0.01% (with 1 retry), FAR is Below 0.00001%		



Contact

FUJITSU LIMITED
 Shiodome City Center, 5-2, Higashi-shimbashi
 1-chome, Minato-ku, Tokyo 105-7123, Japan
 Tel: +81-3-6252-2662
 URL: <https://www.fujitsu.com/global/services/security/offerings/biometrics/palmsecure/>

FUJITSU FRONTECH LIMITED
 1776 Yanokuchi, Inagi-shi, Tokyo 206-8555, Japan
 URL: <http://www.fujitsu.com/jp/group/frontech/en/>
 Contact: <http://www.fujitsu.com/jp/group/frontech/en/contact/>

© Copyright 2019 Fujitsu Limited Fujitsu, the Fujitsu logo, and the PalmSecure logo are trademarks or registered trademarks of Fujitsu Limited in Japan and other countries. Other company, product and service names may be trademarks or registered trademarks of their respective owners. Technical data subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.