

Value for You RLP Prijslijst



December 2013

FUJITSU DESKTOP PC



FUJITSU NOTEBOOKS



FUJITSU SERVERS



LIFEBOOK Notebooks / STYLISTIC Tablets

LIFEBOOK A512



Your Everyday Partner

Processor, Chipset, Memory

Intel® Core™ i3-3110M processor (2.4 GHz), 3 MB, Intel® HM75
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SATA, 5400 rpm, 320 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

Bluetooth: v4.0 + EDR
LAN: 10/100/1000 MBit/s Realtek RTL 8111F

Display, Grafic

39.6 cm (15.6-inch), TFT, (HD), LED backlight, anti-glare, 1366 x 768 pixel, 300:1 (min), 200 cd
Intel® HD Graphics or HD Graphics 3000 (depending on CPU), up to 1695 MB

Keyboard and pointing devices

Touchpad, Status LED
Keyboard, N/A

Power supply

Li-Ion battery 6-cell, 4400 mAh, 48 Wh
Runtime 1st battery: up to 6 h

Dimensions / Weight / Environmental

2.5 kg
378 x 252 x 36.5 mm
Matt Matte black

Operating system

Win8Pro+Win7Load

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 (34 mm and 54 mm supported) x ExpressCard slots, 1 x HDMI, N/A x , 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x SD-Card Reader (SD/SDHC) x Memory card slots, 3 (1 x Anytime USB Charge functionality) x USB 2.0 total, 1 x VGA, Intel® Centrino® Wireless N2230 (IEEE 802.11b/g/n) x Integrated WLAN

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 449

VFY:A5120M7311NL

LIFEBOOK A532



Your Essential Partner

Processor, Chipset, Memory

Intel® Core™ i5-4200M processor
Intel® HM76
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SATA, 5400 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

Bluetooth: v4.0 + EDR
LAN: 10/100/1000 MBit/s Realtek RTL 8111F

Display, Grafic

39.6 cm (15.6-inch), TFT, (HD), LED backlight, anti-glare, 1366 x 768 pixel, 300:1 (min), 200 cd
Intel® HD Graphics 3000 or 4000 (depending on CPU), up to 1695 MB

Keyboard and pointing devices

Touchpad, Status LED
Keyboard, N/A

Power supply

Li-Ion battery 6-cell, 4400 mAh, 48 Wh
Runtime 1st battery: Up to 6:20 h (productivity mode)

Dimensions / Weight / Environmental

2.4 kg
378 x 252 x 34.2 mm
Matt Black/silver

Operating system

Win8Pro+Win7Load

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 (34 mm) x ExpressCard slots, 1 x HDMI, N/A x , 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x 4in1 Card Reader (SD/SDHC/MS/MS Pro) x Memory card slots, 1 x USB 2.0 total, 3 (1 x Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA, Intel® Centrino® Wireless N2230 (IEEE 802.11b/g/n) x Integrated WLAN

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 549

VFY:A5440M7501NL

LIFEBOOK U574 Ultrabook™



Your Ultra-thin Mobile Companion

Processor, Chipset, Memory

Intel® Core™ i5-i5-4200U processor
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 128 GB, 2.5-inch

Communication, Network

WLAN: Intel® Wireless-N 7260 2x2 BGN + BT
Bluetooth: Integrated V4.0 + HS
LAN: USB to LAN (with USB to LAN adapter)

Display, Grafic

33.8 cm (13.3-inch), LED backlight, (HD), Anti-glare touchscreen, 1366 x 768 pixel, 220 cd/m2
Intel® HD Graphics 4400

Keyboard and pointing devices

Keyboard, Multi gesture touchpad with integrated mouse button functionality

Power supply

Lithium polymer battery 4-cell, 2840 mAh, 48.8 Wh
Runtime 1st battery: up to 11 h

Dimensions / Weight / Environmental

Approx. 1.6 kg
322 x 225 x 19.5 mm
Aluminum lid Black with red details

Operating system

Win8Pro+Win7Load

Interfaces

1 (HP/MIC Comb Jack) x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DC-in, 1 x HDMI, 1 digital x Internal microphones, 1 x Kensington Lock support, via USB (with USB to LAN adapter - PXE Boot capable) x Ethernet (RJ-45), 1 x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS), 1 (incl. 1x Anytime USB Charge functionality) x USB 2.0 total, 2 x USB 3.0 total, Intel® Centrino Wireless-N7260 a/b/g/n

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 889

VFY:U5740M7512NL

LIFEBOOK N532



Boost uw multimedia prestaties

Processor, Chipset, Memory

Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, sep-13
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SATA, 5400 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2200 b/g/n
Bluetooth: Integrated V4.0 + HS
LAN: 10/100/1000 MBit/s

Display, Grafic

43.9 cm (17.3-inch), LED backlight, (HD+), Anti-glare display, 1600 x 900 pixel, 300:1, 220 cd/m2
NVIDIA® GeForce® GT 620M, 1 GB (DDR3 VRAM)

Keyboard and pointing devices

Touchpad, Status LED
Keyboard, N/A

Power supply

Li-Ion battery 6-cell, 5200 mAh, 57 Wh
Runtime 1st battery: up to 7 hours

Dimensions / Weight / Environmental

Approx. 3.0 kg
410 x 270 x 20.4 (front) / 35 (back) mm
Black/anthracite

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, N/A x , 1 x DC-in, 1 (34 / 54 mm) x ExpressCard slots, 1 x HDMI, N/A x , 1 (digital) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x 4in1 Card Reader (SD/SDHC/MS/MS Pro) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS), 1 (incl. 1x eSATA/USB combo) x USB 2.0 total, 3 (incl. 1x Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 669

VFY:N5320M4501NL

LIFEBOOK E752

Your Professional Desktop Replacement
Processor, Chipset, Memory

Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, Intel® HM76
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SATA, 7200 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2200 b/g/n
Bluetooth: Bluetooth 4.0
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 V

Display, Grafic

39.6 cm (15.6-inch), LED backlight, (HD), Anti-glare display, compound, 1366 x 768 pixel, 300:1, 220 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad with two mouse buttons, Optional: Fingerprint sensor, Optional: TouchStick, Application buttons
Keyboard, N/A

Power supply

Runtime 1st battery: up to 12 h

Dimensions / Weight / Environmental

2.5 kg
372 x 245 x 35 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 (V1.1a) x DisplayPort, 1 x Docking connector for Port Replicator, 1 x eSATA & USB combo, 1 (34 / 54 mm supported) x ExpressCard slots, N/A x , 2x digital (array) microphones as option x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB, MS Pro, MS Pro Duo) x Memory card slots, 1 (optional) x Modem (RJ-11), 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x SmartCard slot, 2 (1x with Anytime USB Charge functionality) x USB 2.0 total, 2 (1 thereof is the E-SATA & USB combo) x USB 3.0 total, 1 x VGA

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 779

VFY:E7520M4501NL

LIFEBOOK E733

Elegant Design and Functionality without Compromises
Processor, Chipset, Memory

Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SATA, 5400 rpm, 500 GB, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2230 b/g/n
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

33.8 cm (13.3-inch), LED backlight, (HD), Anti-glare display, magnesium, 1366 x 768 pixel, 300:1 (t.b.d.), 200 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad (93mmx55mm) with 2 integrated mouse buttons, Optional: Fingerprint sensor, Application buttons
Keyboard, N/A

Power supply

Runtime 1st battery: up to 13 h (tbd)

Dimensions / Weight / Environmental

1.7 kg
321 x 228 x 20 (f) - 27 (r) mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x DisplayPort, 1 x Docking connector for Port Replicator, N/A x , 2x digital microphones (array) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 (optional) x SmartCard slot, x USB 2.0 total, 3 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 889

VFY:E7330M55A1NL

LIFEBOOK E753

Elegant Design and Functionality without Compromises
Processor, Chipset, Memory

Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSHD, 5400 rpm, 500 GB / 8 GB SSD Cache, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2230 b/g/n
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

39.6 cm (15.6-inch), LED backlight, (HD), Anti-glare display, magnesium, 1366 x 768 pixel, 300:1 (t.b.d.), 200 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad (105mmx66mm) with 2 integrated mouse buttons, Optional: Fingerprint sensor, Application buttons
Keyboard, N/A

Power supply

Runtime 1st battery: up to 13 h (tbd)

Dimensions / Weight / Environmental

2.0 kg
374 x 250 x 20 (f) - 27 (r) mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x DisplayPort, 1 x Docking connector for Port Replicator, 1 x HDMI, N/A x , 2x digital microphones (array) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 (optional) x SmartCard slot, 1 x USB 2.0 total, 3 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 999

VFY:E7530MXE11NL

LIFEBOOK E743

Elegant Design and Functionality without Compromises
Processor, Chipset, Memory

Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSHD, 5400 rpm, 500 GB / 8 GB SSD Cache, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2230 b/g/n
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

35.6 cm (14-inch), LED backlight, (HD+), Anti-glare display, magnesium, 1600 x 900 pixel, 300:1 (t.b.d.), 250 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad (93mmx55mm) with 2 integrated mouse buttons, Optional: Fingerprint sensor, Application buttons
Keyboard, N/A

Power supply

Runtime 1st battery: up to 13 h (tbd)

Dimensions / Weight / Environmental

1.8 kg
338 x 231 x 20 (f) - 27 (r) mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x DisplayPort, 1 x Docking connector for Port Replicator, N/A x , 2x digital microphones (array) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 (optional) x SmartCard slot, 1 x USB 2.0 total, 3 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 999

VFY:E7430MXE11NL

LIFEBOOK E733

Elegant Design and Functionality without Compromises
Processor, Chipset, Memory

Intel® Core™ i5-3230M processor (2.6 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSHD, 5400 rpm, 500 GB / 8 GB SSD Cache, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2230 b/g/n
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

33.8 cm (13.3-inch), LED backlight, (HD), Anti-glare display, magnesium, 1366 x 768 pixel, 300:1 (t.b.d.), 200 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad (93mmx55mm) with 2 integrated mouse buttons,
Optional: Fingerprint sensor, Application buttons
Keyboard, N/A

Power supply

Runtime 1st battery: up to 13 h (tbd)

Dimensions / Weight / Environmental

1.7 kg
321 x 228 x 20 (f) - 27 (r) mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x DisplayPort, 1 x Docking connector for Port Replicator, N/A x , 2x digital microphones (array) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 (optional) x SmartCard slot, x USB 2.0 total, 3 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

RPL (Recommended List Price):

€ 999

VFY:E7330MXE11NL

LIFEBOOK U772 Ultrabook™

Business Elegance in Style
Processor, Chipset, Memory

Intel® Core™ i5-3337U processor (1.8 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 128 GB, 2.5-inch

Communication, Network

WLAN: Intel® Centrino® 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

35.6 cm (14-inch), LED backlight, (HD), Anti-glare frameless display, magnesium, 1366 x 768 pixel, 200:1, 220 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad with integrated mouse button functionality, Fingerprint sensor, EcoButton
Keyboard, N/A

Power supply

Runtime 1st battery: Up to 10:00 h

Dimensions / Weight / Environmental

1.4 kg
327 x 225 x 15.6 mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, N/A x , 2 (digital) x Internal microphones, 1 x Kensington Lock support, 1 (mini LAN connector, Adapter included) x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x USB 2.0 total, 2 (1 with Anytime USB Charge functionality) x USB 3.0 total

Warranty

2 year Bring-in Service

RPL (Recommended List Price):

€ 1.149

VFY:U7720M4501NL

LIFEBOOK E733

Elegant Design and Functionality without Compromises
Processor, Chipset, Memory

Intel® Core™ i7-3632QM processor (2.2 GHz), 6 MB, Intel® QM77
2 x 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 256 GB, 2.5-inch
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Advanced-N 6235 802.11 a/b/g/n with Bluetooth
UMTS Modul: LTE Sierra Wireless MC7710
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

33.8 cm (13.3-inch), LED backlight, (HD), Anti-glare display, magnesium, 1366 x 768 pixel, 300:1 , 200 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Multi gesture touchpad (93mmx55mm) with 2 integrated mouse buttons,
Optional: Fingerprint sensor, Application buttons, Status LED

Power supply

Runtime 1st battery: up to 13 h

Dimensions / Weight / Environmental

1.6 kg
321 x 228 x 20 (f) - 27 (r) mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows®

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DC-in, 1 x DisplayPort, 1 x Docking connector for Port Replicator, 2x digital microphones (array) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (only for models with integrated 3G/UMTS or 4G/LTE module), 1 (optional) x SmartCard slot, 3 (1 with Anytime USB Charge functionality) x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

RPL (Recommended List Price):

€ 1.499

VFY:E7330MXP41NL

STYLISTIC T902

Your Excellent Flexible Companion
Processor, Chipset, Memory

Intel® Core™ i5-3340M processor (2.7 GHz), 3 MB, Intel® QM77
4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSHD, 5400 rpm, 500 GB / 8 GB SSD Cache, 2.5-inch, S.M.A.R.T.
DVD Super Multi

Communication, Network

WLAN: Intel® Centrino® Wireless-N2200 b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

33.8 cm (13.3-inch), TFT, (HD+), Anti-glare touchscreen, 1600 x 900 pixel, 500:1, 300 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Fingerprint sensor, Launch keys, Application buttons, Tablet Pen, Touchscreen, Multi gesture touchpad with two mouse buttons

Power supply

Li-Ion battery 6-cell, 72 Wh (6.700mAh battery) mAh
Runtime 1st battery: up to 7h 40m

Dimensions / Weight / Environmental

1.89 kg
326 x 244 x 27.1 mm front / 31 mm back (without foot) mm

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, 2 (digital) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x SmartCard slot, 2 (1 left side with Anytime USB Charge functionality) x USB 2.0 total, 2 x USB 3.0 total, 1 x VGA

Warranty

2 year Bring-in Service

RPL (Recommended List Price):

€ 1.499

VFY:T9020MXE21NL

LIFEBOOK U772 Ultrabook™
STYLISTIC T902
STYLISTIC M532
STYLISTIC M702

Business Elegance in Style
Your Excellent Flexible Companion
Perfect Choice for Business and Private Use
Designed for the toughest businesses
Processor, Chipset, Memory

Intel® Core™ i7-3687U processor (2.1 GHz), 4 MB, Intel® QM77
8 GB (1 module(s) 8 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Processor, Chipset, Memory

Intel® Core™ i7-3540M processor (3.0 GHz), 4 MB, (), 512 KB, Intel® QM77
2 x 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Processor, Chipset, Memory

NVIDIA® Tegra® 3
NVIDIA® Tegra® 3 T30S, Quad-Core ARM Cortex A9, 1.4 GHz

Processor, Chipset, Memory

NVIDIA® Tegra® 3
NVIDIA® Tegra® 3 AP37, Quad-Core ARM Cortex A9, 1 MB, 1.7 GHz

Drives

SSD SATA III, 256 GB, 2.5-inch

Drives

SSD SATA III, 256 GB, 2.5-inch
DVD Super Multi

Drives

32GB eMMC flash memory
64GB eMMC flash memory

Drives

32GB eMMC 4.4.1 Flash Memory

Communication, Network

WLAN: Intel® Centrino® 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: LTE Sierra Wireless MC7710
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Communication, Network

WLAN: Intel® Centrino® Wireless-N2200 b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000
LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Communication, Network

AzureWave AW-AH663 802.11 a/b/g/n
2x dual band WLAN, 1x UMTS, 1x GPS
Bluetooth 3.0

Communication, Network

Texas Instruments WL1283

Display, Grafic

35.6 cm (14-inch), LED backlight, (HD), Anti-glare frameless display, magnesium, 1366 x 768 pixel, 200:1, 220 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Display, Grafic

33.8 cm (13.3-inch), TFT, (HD+), Anti-glare touchscreen, 1600 x 900 pixel, 500:1, 300 cd/m²
Intel® HD Graphics 4000 with 3rd generation Core i processors

Display, Grafic

25.7 cm (10.1-inch), TFT, (WXGA), 1280 x 800 pixel, 800:1, max. 550 cd/m²

Display, Grafic

25.7 cm (10.1-inch), TFT, (WUXGA), 1920 x 1200 pixel, 500:1, max. 300 cd/m²

Keyboard and pointing devices

Multi gesture touchpad with integrated mouse button functionality, Fingerprint sensor, EcoButton
Keyboard, N/A

Keyboard and pointing devices

Fingerprint sensor, Launch keys, Application buttons, Tablet Pen, Touchscreen, Multi gesture touchpad with two mouse buttons
Keyboard, N/A

Keyboard and pointing devices

Keyboard, N/A

Keyboard and pointing devices

Keyboard, N/A

Power supply

Runtime 1st battery: Up to 10:00 h

Power supply

Li-Ion battery 6-cell, 72 Wh (6.700mAh battery) mAh
Runtime 1st battery: up to 7h 40m

Power supply

video playback 8.4 h

Power supply

video playback up to 15 h

Dimensions / Weight / Environmental

1.4 kg
327 x 225 x 15.6 mm

Dimensions / Weight / Environmental

1.89 kg
326 x 244 x 27.1 mm front / 31 mm back (without foot) mm

Dimensions / Weight / Environmental

560 g
262.6 x 175.4 x 8.6 mm

Dimensions / Weight / Environmental

590 g
259 x 169 x 9.9 mm

Operating system

Windows 8 Pro

Operating system

Windows 8 Pro

Operating system

Android 4.0, upgrade to Android 4.1 available

Operating system

Android 4.0 (Ice Cream Sandwich)

Interfaces

1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, N/A x , 2 (digital) x Internal microphones, 1 x Kensington Lock support, 1 (mini LAN connector, Adapter included) x Ethernet (RJ-45), 1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 64GB) x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x USB 2.0 total, 2 (1 with Anytime USB Charge functionality) x USB 3.0 total

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, N/A x , 2 (digital) x Internal microphones, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x SmartCard slot, 2 (1 left side with Anytime USB Charge functionality) x USB 2.0 total, 2 x USB 3.0 total, 1 x VGA

1 x Audio: line-in / line-out, 1 (digital) x Internal microphones, 1 x Micro USB 2.0, 1 x Docking connector for Port Replicator, 1 x SIM card slot, 1 x Memory card slots

Interfaces

1 x Audio: line-in / line-out, N/A x , N/A x , 1 (digital) x Internal microphones, 1 x Memory card slots, 1 x Micro USB 2.0, 1 x SIM card slot (Micro-SIM), Texas Instruments WL1283 x Integrated WLAN

Warranty

3 year Bring-in Service

Warranty

2 year Bring-in Service

Warranty

1 year Collect Return Service

Warranty

1 year Collect Return Service

RLP (Recommended List Price):

€ 1.699

VFY:U7720MXP42NL

RLP (Recommended List Price):

€ 1.666

VFY:T9020MXP41NL

RLP (Recommended List Price):

€ 333

VFY:M5320MPAD1IN

RLP (Recommended List Price):

€ 888

VFY:M7020MPAD1IN

STYLISTIC Q572

STYLISTIC Q702



Your Professional BusinessPad

Attach or Touch - The Hybrid Business Talent

Processor, Chipset, Memory
AMD A68M FCH

Processor, Chipset, Memory
Intel® Core™ i5-3437U processor (1.9 GHz), 3 MB,
Intel® QM77

Drives
mSATA, 128 GB, FDE

Drives
SSD mSATA, 256 GB

Communication, Network
UMTS Modul: Sierra Wireless Gobi 3000
10/100 Mbit/s (via cradle only)

Communication, Network
WLAN: Intel® Centrino® 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: LTE Sierra Wireless MC7710
Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Graphic

AMD Radeon™ HD 6250

Display, Graphic

Intel® HD Graphics 4000 with 3rd generation Core i processors

Keyboard and pointing devices

Keyboard and pointing devices

Power supply

Dimensions / Weight / Environmental

0.732 kg
273.5 x 176 x 13.9 mm

Dimensions / Weight / Environmental

0.850 kg
302 x 195 x 12.7 mm

Operating system

Windows 8 Pro

Operating system

Windows 8 Pro

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, 2 (digital) x Internal microphones, 1 x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x SmartCard slot, 2 x USB 2.0 total

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DC-in, 1 x Docking connector for Port Replicator, 1 x HDMI, N/A x , 2 (digital) x Internal microphones, 1 x Memory card slots, 1 x SIM card slot (usable only with 3G/UMTS, 4G/LTE), 1 x USB 2.0 total, 1 x USB 3.0 total

Warranty

2 year Bring-in Service

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 999

VFY:Q5720M3001NL

RLP (Recommended List Price):

€ 1.599

VFY:Q7020MXP41NL

ESPRIMO P410 E85+



Your Immediately Deliverable Office PC

Processor, Chipset, Memory

Intel® Pentium® processor G2020 (2.90 GHz), 3 MB, Intel® H61
2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 250 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU), up to 1759 MB

Dimensions / Weight / Environmental

9 kg
175 x 425 x 353 mm

Operating system

Win8Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, N/A x , 1 x Ethernet (RJ-45), 1/1 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 329

VFY:P0410P5211NL

ESPRIMO E420 E85+



Your Immediately Deliverable Office PC

Processor, Chipset, Memory

Intel® Core™ i3-4130 processor (3.40 GHz)
Intel® H81
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor), up to 1782 MB

Dimensions / Weight / Environmental

9 kg
330 x 405 x 104 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, N/A x , 1 x Ethernet (RJ-45), 1/1 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 449

VFY:E0420P7321NL

ESPRIMO P420 E85+



Your Immediately Deliverable Office PC

Processor, Chipset, Memory

Intel® Core™ i3-4130 processor (3.40 GHz), 3 MB
Intel® H81
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor), up to 1782 MB

Dimensions / Weight / Environmental

9 kg
175 x 425 x 353 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, N/A x , 1 x Ethernet (RJ-45), 1/1 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 449

VFY:P0420P7321NL

ESPRIMO P420 E85+

Your Immediately Deliverable Office PC
Processor, Chipset, Memory

Intel® Core™ i5-4440 processor (3.10 GHz), 6 MB, Intel® H81
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Realtek RTL 8111E

Display, Grafic

Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor), up to 1782 MB

Dimensions / Weight / Environmental

9 kg
175 x 425 x 353 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (DVI-D) x DVI, 1 x Front audio: headphone, 1 x Front audio: microphone, 2 x USB front, N/A x , 1 x Ethernet (RJ-45), 1/1 x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, optional USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x16, 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 499

VFY:P0420P7511NL

ESPRIMO Q520

The Mini with More PC per cm
Processor, Chipset, Memory

Intel® Core™ i3-4130T processor (2.90 GHz), 3 MB Intel® H81
4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO

DIMM
Drives

HDD SATA II, 5400 rpm, 500 GB, 2.5-inch
DVD Super Multi Slot-in slim

Communication, Network

Bluetooth: 1 (optional)
LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

1.6 kg
185 x 188 x 54 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, 1 (DVI-I) x DVI, 2x 2.0 x USB front, 1 x HDMI, 1 x Kensington Lock, support, 1 x Ethernet (RJ-45), 1 x Multicardreader, 6 x USB 2.0 total, 4x 2.0 x USB rear, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional) x Integrated WLAN

Slots, Bays

1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 539

VFY:Q0520P7311NL

ESPRIMO E520 E85+

Your Flexible and Economic PC
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB Intel® B85
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

10 kg
330 x 405 x 104 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0 x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 8 x USB 2.0 total, 4x 2.0/ 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0/ 2x 3.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 549

VFY:E0520P7551NL

ESPRIMO P520 E85+

Your Flexible and Economic PC
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® B85
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

10 kg
175 x 425 x 353 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0 x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 8 x USB 2.0 total, 4x 2.0/ 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0/ 2x 3.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 1 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 549

VFY:P0520P7551NL

ESPRIMO C720

Your Ultra Small Form Factor PC
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® Q85
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD SuperMulti SATA slim

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

9 kg
265 x 315 x 88 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-out, N/A x , 1 x DisplayPort, 1 (DVI-I) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 2x 2.0/ 2x 3.0 x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 2 x Serial (RS-232) (powered, 9pin, 16 byte FIFO, 16550 compatible), 8 x USB 2.0 total, 4x 2.0/ 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 (via DVI to VGA adapter, part of shipment) x VGA

Slots, Bays

1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 649

VFY:C0720P7501NL

ESPRIMO E720 E90+

Combines High Efficiency with Manageability
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® Q85
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

10 kg
340 x 382 x 98 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 649

VFY:E0720P7501NL

ESPRIMO P720 E90+

Excellent Performance, Expandability and Efficiency
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® Q85
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LV

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

11 kg
175 x 419 x 395 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

1 year Bring-in Service

RLP (Recommended List Price):

€ 649

VFY:P0720P7501NL

ESPRIMO E920 0-Watt

The Innovative 0-Watt PC
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® Q87
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LM

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

10 kg
340 x 382 x 98 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 1 x 3.5-inch external bays, 1 x 3.5-inch internal bays, 1 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 699

VFY:E0920PXG11NL

ESPRIMO P920 0-Watt

The Innovative 0-Watt PC
Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB, Intel® Q87
2 x 2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LM

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

11 kg
175 x 419 x 395 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0 (optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 699

VFY:P0920PXG21NL

ESPRIMO Q920


The Mini with More PC per cm³

Processor, Chipset, Memory

Intel® Core™ i5-4570T processor (2.90 GHz), 4 MB, Intel® Q87
4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM

Drives

SSHD SATA III, 5400 rpm, 500 GB, 2.5-inch
DVD Super Multi Slot-in slim

Communication, Network

Bluetooth: 1 (optional with WLAN together)
LAN: 10/100/1000 MBit/s Intel® L217LM

Display, Grafic

Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

1.6 kg
185 x 188 x 54 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DisplayPort, 1 (DVI-I) x DVI, 2x 3.0 x USB front, N/A x , 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 1 (SD, MMC) x Multicardreader, 2 x USB 2.0 total, 2x 2.0 and 2x 3.0 x USB rear, 4 x USB 3.0 total, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional with Bluetooth together) x Integrated WLAN

Slots, Bays

1 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 799

VFY:Q0920PXP11NL

ESPRIMO X913


Evolutionary PC for the Modern Office

Processor, Chipset, Memory

Intel® Core™ i5-3470T processor (2.90 GHz), 3 MB, Intel® Q77
4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM

Drives

HDD SATA II, 5400 rpm, 500 GB, 2.5-inch

Communication, Network

Bluetooth: 1 (optional with WLAN module)
LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics Intel® HD Graphics 2000 Intel® HD Graphics 2500, up to 1759 MB

Dimensions / Weight / Environmental

5.94 kg
554 x 225 x 433 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DVI, N/A x , optional with camera module x Internal microphones, 2 x Kensington Lock support, 1 x Ethernet (RJ-45), 2 x USB 2.0 total, 2x2.0 2x3.0 x USB rear, 4 x USB 3.0 total, 2x3.0 x USB left side, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional) x Integrated WLAN

Slots, Bays

0 x 2.5-inch bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 949

VFY:X9130P7511NL

ESPRIMO X913-T


Evolutionary PC for the Modern Office

Processor, Chipset, Memory

Intel® Core™ i5-3470T processor (2.90 GHz), 3 MB, Intel® Q77
2 x 2 GB (1 module(s) 2 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM

Drives

SSHD SATA III, 5400 rpm, 500 GB, 2.5-inch

Communication, Network

Bluetooth: 1 (optional with WLAN module)
LAN: 10/100/1000 MBit/s Intel® 82579 LM

Display, Grafic

Intel® HD Graphics#Intel® HD Graphics 2000#Intel® HD Graphics 2500, up to 1759 MB

Dimensions / Weight / Environmental

8.62 kg
533 x 224 x 419 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in / microphone, 1 x Audio: line-out / headphone, N/A x , 1 x DVI, N/A x , optional with camera module x Internal microphones, 2 x Kensington Lock support, 1 x Ethernet (RJ-45), 2 x USB 2.0 total, 2x2.0 2x3.0 x USB rear, 4 x USB 3.0 total, 2x3.0 x USB left side, 1 (via DVI to VGA adapter, part of shipment) x VGA, 1 (optional) x Integrated WLAN

Slots, Bays

0 x 2.5-inch bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.099

VFY:X9130P7511NL

ESPRIMO P920 E90+



Excellent Performance, Expandability And Efficiency

Processor, Chipset, Memory

Intel® Core™ i7-4770 processor (3.40 GHz), 8 MB,
Intel® Q87
2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800,
DIMM

Drives

SSHD SATA III, 7200 rpm, 1000 GB, 3.5-inch

MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® L217LM

Display, Grafic

AMD® Radeon R9 255 FH 2GB, Intel® HD Graphics, HD Graphics 4400, HD
Graphics 4600 (depending on processor), up to 1782 MB

Dimensions / Weight / Environmental

11 kg
175 x 419 x 395 mm

Operating system

Win8.1Pro+Win7Load

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x , 1
(second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI, 1 (optional) x eSATA,
1 x Front audio: headphone, 1 x Front audio: microphone, 4x 2.0 or 2x 2.0/ 2x 3.0
(optional) x USB front, N/A x , 1 x Ethernet (RJ-45), 1 (optional) x Parallel (25pin
with EPP and ECP), 2 x Mouse / Keyboard (PS/2), 1 x Serial (RS-232) (9pin, 16
byte FIFO, 16550 compatible), 10 x USB 2.0 total, 4x 2.0 / 2x 3.0 x USB rear, 4 x
USB 3.0 total, 2 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external
bays, 2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.099

VFY:P0920PXP51NL

FUTRO Thin Clients



FUTRO S700



De betaalbare Thin Client

Processor, Chipset, Memory

AMD A55E Controller Hub

2 GB (1 module(s) 2 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM

Drives

mSATA, 2 GB, Flash drive

Communication, Network

LAN: Built-in 10/100/1000 MBit/s

Display, Graphics

ATI Radeon™ HD 6250 , up to 256 MB

Dimensions / Weight / Environmental

1,2 kg

97 x 191 x 266 mm

Operating system

eLux® RL - Embedded Linux

Interfaces

1 x Audio: line-in, 1 x Audio: line-out, 1 x DC-in, 1 DP x DisplayPort,
1 DVI-I (integrated VGA can be used with DVI-VGA adapter) x DVI,
1 x Front audio: headphone, 1 x Front audio: line-in / microphone,
2 x USB front, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 2
x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, 2 x USB
internal

Warranty

2 year Bring-in Service

FUTRO S700



De betaalbare Thin Client

Processor, Chipset, Memory

AMD A55E Controller Hub

2 GB (1 module(s) 2 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM

Drives

mSATA, 4 GB, Flash drive

Communication, Network

LAN: Built-in 10/100/1000 MBit/s

Display, Graphics

ATI Radeon™ HD 6250 , up to 256 MB

Dimensions / Weight / Environmental

1,2 kg

97 x 191 x 266 mm

Operating system

Windows® Embedded Standard 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-out, 1 x DC-in, 1 DP x DisplayPort,
1 DVI-I (integrated VGA can be used with DVI-VGA adapter) x DVI,
1 x Front audio: headphone, 1 x Front audio: line-in / microphone,
2 x USB front, 1 x Kensington Lock support, 1 x Ethernet (RJ-45), 2
x Mouse / Keyboard (PS/2), 8 x USB 2.0 total, 4 x USB rear, 2 x USB
internal

Warranty

2 year Bring-in Service

RLP (Recommended List Price):

€ 299

VFY:S0700PF045NL

RLP (Recommended List Price):

€ 349

VFY:S0700PX011NL

PRIMERGY TX100 S3p



Enter the world of PRIMERGY TX servers

The PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. It also offers high availability (dual onboard gigabit LAN), a choice of two highly energy efficient power supply units and high data safety (optional RAID 5/6 with battery backup).

Processor, Chipset, Memory

Intel® Xeon® processor E3-1220v2# (4C/4T, 3.10 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202
2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3009

Drives, Controller

2 x HDD SATA, 7200 rpm, 500 GB, 3.5-inch, economic
DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
4x 3.5" easy change SATA

Dimensions / Weight / Environmental

175 x 419 x 395 mm
up to 14 kg

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server Essentials 2011, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 (2x front, 6x rear, 1x internal for backup device), 1 x RS232, 1 x VGA (ATI ES1000 (64MB) on board)

Warranty

1 year
On-site Service

RLP (Recommended List Price):
€ 549

VFY:T1003SC070IN

PRIMERGY TX100 S3p



Enter the world of PRIMERGY TX servers

The PRIMERGY TX100 S3p is ideal for SMEs, looking for a first server with Intel® Xeon® support. It also offers high availability (dual onboard gigabit LAN), a choice of two highly energy efficient power supply units and high data safety (optional RAID 5/6 with battery backup).

Processor, Chipset, Memory

Intel® Xeon® processor E3-1230v2# (4C/8T, 3.30 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 69 W)
Intel® C202
2 x 4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3009

Drives, Controller

2 x HDD SATA, 7200 rpm, 1 TB, 3.5-inch, business critical
DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
4x 3.5" easy change SATA

Dimensions / Weight / Environmental

175 x 419 x 395 mm
up to 14 kg

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server Essentials 2011, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 (2x front, 6x rear, 1x internal for backup device), 1 x RS232, 1 x VGA (ATI ES1000 (64MB) on board)

Warranty

1 year
On-site Service

RLP (Recommended List Price):
€ 849

VFY:T1003SC090IN

PRIMERGY TX120 S3p



For small environments with high demands

PRIMERGY TX120 S3p: For small environments with high demands. It is the perfect server for environments where space, high server functionality and low TCO are crucial. The unique combination of ultra-compact form factor, Intel® Xeon® processor performance, low TCO and high TX120 S3p ideal for demanding environments where space is scarce. availability features, make the PRIMERGY

sep-13

Intel® Xeon® processor E3-1265Lv2# (4C/8T, 2.50 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 45 W)
Intel® C202
4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D3049

Drives, Controller

DVD Super Multi, slimline, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
1 x PCI-Express 2.0 x4 (mech. x8)
4 x 2.5-inch hot-plug SAS/SATA or 2x 3.5-inch non hot-plug SATA.
Not upgradeable in the field.
None
1 x 3.5/1.6-inch for backup devices#1 x 5.25/0.5-inch for CD-RW/DVD

Dimensions / Weight / Environmental

98 x 399 x 340 mm
up to 10 kg - Actual weight may vary depending on configuration

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server Essentials 2011, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

10 x USB 2.0 (2x front, 6x rear, 2x internal; the 2 internal ports cannot be used in parallel), 1 x RS-232-C, 1 x VGA, 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Optional front service LAN port (10/100 Mbit/s)

Warranty

1 year
On-site Service

RLP (Recommended List Price):
€ 669

VFY:T1203SXG10IN

PRIMERGY TX140 S1p



Expandable SME all-round server

PRIMERGY TX140 S1p: the expandable SME all-rounder. It is ideal for SME or branch customers looking for a classic file, print, mail, or database server, with high scalability, Intel® Xeon® E3 series-based performance, and optional redundant power supplies. Storing up to 12 TB, and offering an optional rack conversion kit, the TX140 S1p is an attractive long-term investment.

Processor, Chipset, Memory

Intel® Xeon® processor E3-1265Lv2# (4C/8T, 2.50 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 45 W)
Intel® C202
4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D3049

Drives, Controller

DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
1 x PCI-Express 2.0 x4 (mech. x8)
3.5-inch or 2.5-inch hot-plug SAS/SATA

Dimensions / Weight / Environmental

482 x 570 x 220 mm
205 x 584 x 444 mm
21-28 kg - Actual weight may vary depending on configuration

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows Server® 2008 R2 Foundation, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server Essentials 2011, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

10 x USB 2.0 (2x front, 6x rear, 2x internal; the 2 internal ports cannot be used in parallel, 1 x serial RS-232-C, usable for iRMC or system or shared, 1 x VGA, 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

1 year
On-site Service

RLP (Recommended List Price):
€ 749

VFY:T1401SXG10IN

PRIMERGY TX150 S8



The one-processor tower server - maximized!

The PRIMERGY TX150 S8: the right system for SMEs, branch offices or virtualized environments where the main focus is on expandability and availability. With processors of the Intel® Xeon® E5-1400 and E5-2400 family, the TX150 S8 delivers excellent energy-efficient performance. PRIMERGY TX150 S8: the one processor tower server – maximized!

Processor, Chipset, Memory

Intel® Xeon® processor E5-2420# (6C/12T, 1.90 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s, Mem bus: 1333 MHz, 95 W)
Intel® C602
8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3079

Drives, Controller

DVD Super Multi, half height, SATA I

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x8)
3.5-inch or 2.5-inch hot-plug SAS/SATA

Dimensions / Weight / Environmental

483 x 611 x 177 mm
177 x 651 x 456 mm
16 - 29 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server Essentials 2011, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Windows Server® 2012 Essentials, Windows Server® 2012 Foundation, Hyper-V Server 2012, Windows Storage Server 2012 Standard

Interfaces

2 x Gbit/s Ethernet, 9 x USB 2.0 (2x front, 4x rear, 3x internal for backup, UFM and internal USB), 1 x serial RS-232-C, usable for iRMC or system or shared, 1 x VGA, 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

1 year
On-site Service

RLP (Recommended List Price):
€ 1,099

VFY:T1508SC040IN

PRIMERGY TX200 S7

Well-balanced price- performance

The PRIMERGY TX200 S7 is a perfect server for SMEs, branch offices or virtualized infrastructures. The tower server offers dual processor performance combined with expandability and energy efficiency. Its feature set makes the TX200 S7 a great virtualization, database or communication server. The PRIMERGY TX200 S7 strikes the right balance between price and performance.

Processor, Chipset, Memory

..Intel® Xeon® processor E5-2420# (6C/12T, 1.90 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)

..Intel® C602

..8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

..D 3099

Drives, Controller

..DVD Super Multi, half height, SATA I
 ..RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int.#RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)

Slots, Bays

..1 x PCI-Express 2.0 x4 (mech. x8)
 ..3.5-inch or 2.5-inch hot-plug SAS/SATA

Dimensions / Weight / Environmental

..483 x 611 x 177 mm
 ..177 x 651 x 456 mm
 ..16 kg - 29 kg - Actual weight may vary depending on configuration

Software

..XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Hyper-V Server 2012, Windows Server® 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

..2 x Gbit/s Ethernet (Intel Hartwell), 9 x USB 2.0 (2 x front USB, 4 x rear USB 3 x internal for backup, UFM and internal USB), 1 x serial RS-232-C (9 pin), usable for iRMC S3 or system or common use, 1 x VGA, 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

.. 3 years
 .. On-site Service

RLP (Recommended List Price):

€ 1.449

VFY:T2007SC040IN

PRIMERGY TX300 S7

No compromise tower server

PRIMERGY TX300 S7: a no compromise tower server offering maximum performance, expandability and availability. It combines the latest Intel® Xeon® processors E5 family, with up to two 6 GB GPGPUs and up to 2x 10 Gb LAN cards. Its 10 slots guarantee excellent expandability. Up to 4 hot-plug power supplies assure business continuity. It is ideal for database, virtualization or HPC scenarios.

Processor, Chipset, Memory

Intel® Xeon® processor E5-2630# (6C/12T, 2.30 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)

Intel® C600 (Intel® Patsburg A)

8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM

Mainboard type

D2949

Drives, Controller

DVD Super Multi, half height, SATA I
 RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int.#RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x8)
 3.5-inch or 2.5-inch hot-plug SAS/SATA

Dimensions / Weight / Environmental

177 x 777 x 456 mm
 up to 35 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows HPC Server® 2008 R2 Suite, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Hyper-V Server 2012, Windows Storage Server 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

x Gbit/s Ethernet, 10 x USB 2.0 (2x front, 4x rear, 2x internal for backup devices, 1x USB stick, 1x USSD), 1 x serial RS-232-C, usable for iRMC S3 or system or shared, 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port or optional Modular LAN 2x10Gbit controller, Front management LAN

Warranty

3 years
 On-site Service

RLP (Recommended List Price):

€ 1.999

VFY:T3007SC020IN

PRIMERGY RX100 S7p proGREEN selection

Small in size and low in cost – rich in optional features

The Fujitsu PRIMERGY RX100 S7 is an entry mono socket rack server designed to meet small budgets by delivering highest energy efficiency of its class and a rich set of optional expansions to meet individual demands. Optimized for infrastructure and communication applications, this 1U server delivers up to 32GB RAM, up to 3 PCIe slots and up to 4 hard disk drives.

Processor, Chipset, Memory

Intel® Xeon® processor E3-1265Lv2# (4C/8T, 2.50 GHz, TLC: 8 MB, Turbo: Yes, 1600 MHz, 45 W)

Intel® C202

4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Mainboard type

D 3034

Drives, Controller

DVD Super Multi, slimline, SATA I

Slots, Bays

1 x PCI Exp 2.0 x1 mech x4
 1 x PCI-Express 2.0 x4 (mech. x8)
 4x 2.5-inch hot-plug SAS/SATA
 PRIMERGY RX100 S7p proGREEN selection:
 4 x 2.5-inch drive bays pre-configured
 1 x 5.25/0.5-inch for CD-RW/DVD#1 x
 3.5/0.5-inch for ServerView Local Service Panel or front VGA + front Service LAN

Dimensions / Weight / Environmental

482.6 mm (Bezel) / 431mm (Body) x 572 x 42.5 mm
 up to 14 kg - Actual weight may vary depending on configuration

Software

Enterprise Linux 5, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 11, vSphere™ 4.0 Embedded, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows HPC Server® 2008 R2 Suite, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Web Server 2008, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011

Interfaces

2 x Gbit/s Ethernet, 7 x (2x front, 4x back, 1x internal for UFM), 1 x serial RS-232-C, usable for iRMC or system or shared, 1 x VGA (15-pin), 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port

Warranty

1 year
 On-site Service

RLP (Recommended List Price):

€ 849

VFY:R1007SXG10IN

PRIMERGY RX200 S7

Maximum productivity in a 1U housing

The Fujitsu PRIMERGY RX200 S7 is a rack server that provides high performance of the new Intel® Xeon® E5 product family, expandability up to 768GB of memory and up to 94% energy efficiency - all in 1U space saving housing. Thus, the PRIMERGY RX200 S7 is ideal for virtualization and cloud, small databases as well as for high performance computing.

Processor, Chipset, Memory

Intel® Xeon® processor E5-2620# (6C/12T, 2.00 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)

Intel® C600 (Intel® Patsburg A)

8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM

Mainboard type

D3032

Drives, Controller

DVD Super Multi, slimline, SATA I

Slots, Bays

4 x 2.5-inch base unit or 8 x 2.5-inch base unit
 1 x 5.25/0.5-inch for DVD-RW/Blu-ray (only for base unit 4x 2.5-inch HDD)

Dimensions / Weight / Environmental

482 mm (Bezel) / 431mm (Body) x 762 mm x 43 mm
 up to 18 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows HPC Server® 2008 R2 Suite, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Web Server 2008, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Hyper-V Server 2012, Windows Storage Server 2012 Standard, Windows Storage Server 2012 Standard, ,

Interfaces

6 x USB 2.0 (2x front, 3x rear, 1x uSSD), 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port or optional Modular LAN 2x10Gbit controller, Front management LAN port as option

Warranty

3 years
 On-site Service

RLP (Recommended List Price):

€ 1.449

VFY:R2007SC010IN

PRIMERGY RX300 S7

The versatile 2U powerhouse

The Fujitsu PRIMERGY RX300 S7 is a 2U dual socket rack server, optimized for all types of business applications by focusing on versatility and scalability that supports up to 16 harddisk drives, up to 7 PCIe Gen 3 cards and up to 768GB RAM. Thanks to top performance of the new Intel® Xeon® E5 product family and the available upgrade kits, the RX300 will also ensure the demands of tomorrow are met.

Processor, Chipset, Memory

Intel® Xeon® processor E5-2630# (6C/12T, 2.30 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)

Intel® C600 (Intel® Patsburg A)

8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM

Mainboard type

D2939

Drives, Controller

DVD Super Multi, slimline, SATA I

Slots, Bays

2.5-inch base unit (max. 16 x 2.5) or 3.5-inch base unit (max. 6 x 3.5)
 1 x 5.25/0.5-inch for ODD#1 x 5.25/1.6-inch for ODD or backup devices #1 x 5.25/0.5-inch for Local Service Display

Dimensions / Weight / Environmental

482.6 mm (Bezel) / 445mm (Body) x 770 x 86.9 mm
 up to 25 kg - Actual weight may vary depending on configuration

Software

XenServer®, Enterprise Linux 5, Enterprise Linux 5 with XEN, Enterprise Linux 6, SUSE Linux Enterprise Server 10, SUSE Linux Enterprise Server 10 with XEN, SUSE Linux Enterprise Server 11, vSphere™ 4.1, vSphere™ 4.1 Embedded, vSphere™ 4.1 Installable, vSphere™ 5.0 Embedded, vSphere™ 5.0, Windows Server® 2008 R2 Datacenter, Windows Server® 2008 R2 Enterprise, Windows HPC Server® 2008 R2 Suite, Hyper-V™ Server 2008 R2, Windows Server® 2008 R2 Standard, Windows® Web Server 2008 R2, Windows® Server 2008 Datacenter, Windows® Server 2008 Enterprise, Windows® Server 2008 Standard, Windows® Web Server 2008, Windows® Small Business Server 2011 Premium Add-On, Windows® Small Business Server Standard 2011, Windows Server® 2012 Datacenter, Hyper-V Server 2012, Windows Storage Server 2012 Standard, Windows Storage Server 2012 Standard

Interfaces

10 x USB 2.0 (2x front, 4x rear, 2x internal for backup devices, 1x USB stick, 1x uSSD), 1 x serial RS-232-C, usable for iRMC or system or shared, 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s), Service LAN traffic can be switched to shared onboard Gbit LAN port or optional Modular LAN 2x10Gbit controller, Front management LAN

Warranty

3 years
 On-site Service

RLP (Recommended List Price):

€ 1.699

VFY:R3007SC020IN

PRIMERGY RX350 S7



Maximum expandability in a 2 way server

PRIMERGY RX350 S7: a 4U dual socket rack server offering maximum performance, expandability and availability. It combines the latest Intel® Xeon® processors E5 family, with up to two 6GB GPGPUs, up to 24 hard drives and up to 768GB RAM. Its 10 PCI slots guarantee excellent expandability. Up to 4 hot-plug power supplies assure business continuity. It is ideal for database, virtualization or HPC scenarios.

Processor, Chipset, Memory

Intel® Xeon® processor E5-2630# (6C/12T, 2.30 GHz, TLC: 15 MB, Turbo: Yes, 7.2 GT/s , Mem bus: 1333 MHz, 95 W)
Intel® C600 (Intel® Patsburg A)
8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1333 MHz, PC3-10600, DIMM

Mainboard type

D2949

Drives, Controller

DVD Super Multi, half height, SATA I
RAID 5/6 Ctrl., SAS/SATA 6 Gbit/s, Fujitsu RAID Ctrl SAS 6G 5/6 512MB (D2616), 8 ports int.#RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x8)
2.5-inch or 3.5-inch hot-plug SAS/SATA
1 x 5.25/0.5-inch for ODD#1 x 5.25/1.6-inch for ODD or backup devices #1 x 5.25/0.5-inch for Local Service Display

Dimensions / Weight / Environmental

482.6 mm (Bezel) / 448 mm (Body) x 736 x 177 mm
up to 35 kg - Actual weight may vary depending on configuration

Interfaces

10 x USB 2.0 (2x front, 4x rear, 2x internal for backup devices, 1x USB stick, 1x USSD), 1 x serial RS-232-C, usable for iRMC S3 or system or shared, 2 x VGA (thereof 1x front optional), 1 x dedicated management LAN port for iRMC S3 (10/100/1000 Mbit/s). Service LAN traffic can be switched to shared onboard Gbit LAN port or optional Modular LAN 2x10Gbit controller, Front management LAN port as option

Warranty

3 years
On-site Service

RLP (Recommended List Price):

€ 2.149

VFY:R3507SC020IN

CELSIUS W530



Performance That Boosts Your Productivity

Processor, Chipset, Memory

Intel® Core™ i5-4570 processor (3.20 GHz), 6 MB,
Intel® C226

4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 500 GB, 3.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® I217LM

Display, Grafic

NVIDIA® Quadro® 410, 512 MB
Intel® HD Graphics P4600#Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

approx. 11 kg
175 x 419 x 395 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x ,
1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI,
1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio:
microphone, 2x 2.0/ 2x 3.0 x USB front, N/A x , 1 x Ethernet (RJ-45),
1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2),
1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 9 x USB 2.0 total,
4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0 + 1x 2.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays,
2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 755

VFY:W5300WXE11NL

CELSIUS W530



Performance That Boosts Your Productivity

Processor, Chipset, Memory

Intel® Core™ i5-4670 processor (3.40 GHz), 6 MB,
Intel® C226

8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM

Drives

SSHD SATA III, 5400 rpm, 500 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® I217LM

Display, Grafic

AMD FirePro™ V3900, 1 GB
Intel® HD Graphics P4600#Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

approx. 11 kg
175 x 419 x 395 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x ,
1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI,
1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio:
microphone, 2x 2.0/ 2x 3.0 x USB front, N/A x , 1 x Ethernet (RJ-45),
1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2),
1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 9 x USB 2.0 total,
4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0 + 1x 2.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays,
2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 833

VFY:W5300WVG11NL

CELSIUS W530



Performance That Boosts Your Productivity

Processor, Chipset, Memory

Intel® Xeon® processor E3-1245v3 (3.40 GHz), 8 MB,
Intel® C226

8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
SSD SATA III Premium, 128 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® I217LM

Display, Grafic

NVIDIA® Quadro® K600, 1 GB
Intel® HD Graphics P4600#Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

approx. 11 kg
175 x 419 x 395 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x ,
1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI,
1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio:
microphone, 2x 2.0/ 2x 3.0 x USB front, N/A x , 1 x Ethernet (RJ-45),
1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2),
1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 9 x USB 2.0 total,
4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0 + 1x 2.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays,
2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.099

VFY:W5300W6881NL

CELSIUS W530



Performance That Boosts Your Productivity

Processor, Chipset, Memory

Intel® Xeon® processor E3-1270v3 (3.50 GHz), 8 MB,
Intel® C226

8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
SSD SATA III Premium, 128 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 10/100/1000 MBit/s Intel® I217LM

Display, Grafic

NVIDIA® Quadro® K2000, 2 GB
DP to DVI-D (single link) Adapter Cable
Intel® HD Graphics P4600#Intel® HD Graphics 4600, up to 1782 MB

Dimensions / Weight / Environmental

approx. 11 kg
175 x 419 x 395 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: line-in, 1 x Audio: line-in / microphone, 1 x Audio: line-out, N/A x ,
1 (second DisplayPort optional) x DisplayPort, 1 (DVI-D) x DVI,
1 (optional) x eSATA, 1 x Front audio: headphone, 1 x Front audio:
microphone, 2x 2.0/ 2x 3.0 x USB front, N/A x , 1 x Ethernet (RJ-45),
1 (optional) x Parallel (25pin with EPP and ECP), 2 x Mouse / Keyboard (PS/2),
1 x Serial (RS-232) (9pin, 16 byte FIFO, 16550 compatible), 9 x USB 2.0 total,
4x 2.0 / 2x 3.0 x USB rear, 4 x USB 3.0 total, 2x 2.0 + 1x 2.0 x USB internal, 1 x VGA

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI-Express x1, 2 x 3.5-inch external bays,
2 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.499

VFY:W5300WXP11NL

CELSIUS M720

Your "Thoroughbred" Workstation
Processor, Chipset, Memory

Intel® Xeon® processor E5-1620 (3.60 GHz), 10 MB, Intel® C602
4 x 2 GB (1 module(s) 2 GB) DDR3, ECC, 1600 MHz, PC3-12800

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Graphics

AMD FirePro™ V4900, 1 GB

Dimensions / Weight / Environmental

18 kg
186 x 481 x 430 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: in (rear), 1 x Audio: out (rear), 1 x Audio: in, 1 x Audio: out, 4 (2x USB 3.0) x USB front, 1 x Internal speakers, 1 x Ethernet (RJ-45), 1 / 1 x Mouse / Keyboard (PS/2), 11 x USB 2.0 total, 6 x USB rear, 2 x USB 3.0 total, 3, thereof 1 type A x USB internal

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI slots, 8 x 2.5-inch bays, 2 x 3.5-inch external bays, 4 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.249

VFY:M7200WXG11NL

CELSIUS M720

Your "Thoroughbred" Workstation
Processor, Chipset, Memory

Intel® Xeon® processor E5-1620 (3.60 GHz), 10 MB, Intel® C602
4 x 4 GB (1 module(s) 4 GB) DDR3, ECC, 1600 MHz, PC3-12800

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
SSD SATA III, 128 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: Built-in 10/100/1000 MBit/s Intel® 82579 LM

Display, Graphics

DP to DVI-D (single link) Adapter Cable
NVIDIA® Quadro® K2000, 2 GB

Dimensions / Weight / Environmental

18 kg
186 x 481 x 430 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: in (rear), 1 x Audio: out (rear), 1 x Audio: in, 1 x Audio: out, 4 (2x USB 3.0) x USB front, 1 x Internal speakers, 1 x Ethernet (RJ-45), 1 / 1 x Mouse / Keyboard (PS/2), 11 x USB 2.0 total, 6 x USB rear, 2 x USB 3.0 total, 3, thereof 1 type A x USB internal

Slots, Bays

1 x PCI-Express 2.0 x4 (mech. x16), 2 x PCI slots, 8 x 2.5-inch bays, 2 x 3.5-inch external bays, 4 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.799

VFY:M7200WXP21NL

CELSIUS R920

Uncompromising Workstation Performance for Extreme Requirements
Processor, Chipset, Memory

Intel® Xeon® processor E5-2640 (2.50 GHz), 15 MB, 7.2 GT/s Intel® C602
4 x 4 GB (1 module(s) 4 GB) DDR3, ECC, 1600 MHz, PC3-12800

Drives

HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch
SSD SATA III, 256 GB, 2.5-inch
MultiCard Reader 24in1 USB 2.0 3.5"
DVD Super Multi

Communication, Network

LAN: 2x Built-in 10/100/1000 MBit/s Intel® 82579 LM and Intel®

Display, Graphics

No graphics in system

Dimensions / Weight / Environmental

20 kg
186 x 618 x 430 mm

Operating system

Pre-installed: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7 Professional 64-bit
Rec-DVD: Windows® 7

Interfaces

1 x Audio: in (rear), 1 x Audio: out (rear), 1 x eSATA, 1 x Audio: in, 1 x Audio: out, 4 (2x USB 3.0) x USB front, 1 x Internal speakers, 2 x Ethernet (RJ-45), 1 / 1 x Mouse / Keyboard (PS/2), 11 x USB 2.0 total, 6 x USB rear, 2 x USB 3.0 total, 3, thereof 1 type A x USB internal

Slots, Bays

1 x PCI slots, 8 x 2.5-inch bays, 2 x 3.5-inch external bays, 4 x 3.5-inch internal bays, 2 x 5.25-inch external bays

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 2.999

VFY:R9200WXP41NL

CELSIUS H720

Workstation Power on-the-Go
Processor, Chipset, Memory

Intel® Core™ i7-3740QM processor (2.7 GHz), 6 MB, Intel® QM77
2 x 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 256 GB, 2.5-inch
DVD-RW Dual Double Layer Super Multi

Communication, Network

WLAN: Intel® Centrino® Advanced-N 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000 module
10/100/1000 MBit/s Intel® 82579 LM

Display, Gratic

39.6 cm (15.6-inch), LED backlight, (Full HD), Anti-glare display, magnesium, 1920 x 1080 pixel, 300:1, 220 cd/m
NVIDIA® Quadro® K1000M#NVIDIA® Quadro® K2000M, 2 GB (GDDR3 VRAM)

Dimensions / Weight / Environmental

2.8 kg
379.8 x 257.0 x 35.5 mm

Operating system

Win8P lic./ Win7P load / RDVD TWIN-Pack

Interfaces

1 x DC-in, 1 x DisplayPort, 1 x eSATA, 1 (34 mm) x ExpressCard slots, 1 x Audio: in, 1 x Audio: out, 2 digital array microphones x Internal microphones, 1 x Ethernet (RJ-45), 1 (SD up to 2 GB, SDHC up to 32 GB, SDXC up to 64 GB) x Multicardreader, 1 x SIM card slot (), 1 x SmartCard slot, 1 x USB 2.0 total, 3 x USB 3.0 total, 1 x VGA

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 1.999

VFY:H7200WXP41NL

CELSIUS H920

High-End Workstation Power on-the-Go
Processor, Chipset, Memory

Intel® Core™ i7-3740QM processor (2.7 GHz), 6 MB, Intel® QM77
4 x 4 GB (1 module(s) 4 GB) DDR3, 1600 MHz, PC3-12800, SO DIMM

Drives

SSD SATA III, 128 GB, 2.5-inch
DVD-RW Dual Double Layer Super Multi

Communication, Network

WLAN: Intel® Centrino® Advanced-N 6205 802.11 a/b/g/n
Bluetooth: Bluetooth 4.0
UMTS Modul: Sierra Wireless Gobi 3000 module
10/100/1000 MBit/s Intel® 82579 LM

Display, Gratic

43.9 cm (17.3-inch), LED backlight, (Full HD), Anti-glare display, 1920 x 1080 pixel
NVIDIA® Quadro® K3000M, 2 GB (GDDR5 VRAM)
NVIDIA® Quadro® K3000M#NVIDIA® Quadro® K4000M, 2 / 4 GB (GDDR5 VRAM)

Dimensions / Weight / Environmental

4.25 kg
417 x 287 x 33/44 mm

Operating system

Win8P lic./ Win7P load / RDVD TWIN-Pack

Interfaces

1 x DC-in, 1 x DisplayPort, 1 x eSATA, 1 (34/54 mm) x ExpressCard slots, 1 x Audio: out, 1 digital array microphone x Internal microphones, 1 x Ethernet (RJ-45), 1 (SD up to 2 GB, SDHC up to 32 GB, SDXC up to 64 GB) x Multicardreader, 1 x SIM card slot (), 1 x SmartCard slot, 3 x USB 2.0 total, 1 x USB 3.0 total, 1 x VGA

Warranty

3 year Bring-in Service

RLP (Recommended List Price):

€ 2.499

VFY:H9200WXP41NL