

Fujitsu TP8A All-In-One PoS

- Future-Proof Performance: Intel 6th & 7th Generation Processors and the fastest PCIE NVME SSD storage
- The Most Modular All-In-One PoS Terminal, with field swappable LCD (15", 18.5") and PC module
- Super Sleek AIO suits any counter on adjustable stand or with built-in VESA pole-mount support
- Highly Reliable and Serviceable: External access to memory and storage; quick release from stand
- Maximum Flexibility. Common design supports same software image on AIO and Modular PoS
- Low TCO over a reliable 10+ years' Service Life, 5+ Years' Make plus extra 5+ Years' Service

INTRODUCTION

Fujitsu's new TP8A All-In-One (AIO) PoS terminal is a next generation point-of-sale solution for retailers who want the best performance, functionality, reliability, serviceability, and maximum ROI to create an attractive world-class shopping environment.

The TP8A with Intel 6th Generation "Skylake" CPUs, from Celeron to Core i5; protects investments in Windows 7 & 8.x environments with migration to Windows 10. The TP8A with 7th Generation "Kaby Lake" CPUs up to Core i5, gives maximum Windows 10 performance. With up to 32GB RAM, options for 2.5" SATA3 heritage drives and the new, ~3x faster M.2 PCIE NVME SSD drives, the TP8A is a future-proof PoS platform or even a genuine store server. The TP8A combines leading performance, peripheral and network connectivity in a super sleek package.

The TP8A PoS is a family of AIO and Modular systems, sharing key parts so the same software image runs on both, for flexible deployment and reduced support costs. The TP8A is one of the most modular AIOs available, with easily field-swappable LCDs (15", 18.5") and PC module, further reducing support costs and simplifying migration to future modules and technology – all while extending the life of existing components like the LCD.

The sleek and stylish design of the TP8A AIO has modern aesthetics that easily blend with a range of retail environments - from fashionable and sophisticated to extremely rugged. The dual-hinge stand enables flat-folding for clean counters, adjustability to suit variable height operators and 150° tilting from vertical to past horizontal for easy cable/connector access, whilst hiding cables for best aesthetics and security. Retailers want the flexibility of a single platform that supports multiple in-store touch points, reducing installation and service costs, and providing fast, easy customer transactions for the ultimate shopping experience. The TP8A AIO installs easily on counter-top, pole, wall-mount and in kiosks.

The TP8A continues the TeamPoS tradition of superior quality and reliability. Intelligent power management and advanced thermal designs, including blade-server heat-sink and fan, ensure cool reliable operation in the harshest retail conditions. High quality drives protect data and boost uptime, e.g. 1x 2.5" SATA3, or up to 2x M.2 PCIE SSDs with RAID1 mirroring. The TP8A is easy to service with fast tool-free access to many key parts and a screw-driver to access the rest, e.g. external access to RAM & storage, thumb-screw removal of AIO from stand. Support for Intel Active Management Technology (AMT), vPro and SMBIOS enables remote management by leading enterprise suites.

Customer-focused applications such as registration, promotions, and loyalty programs can be deployed easily with the TP8A AIO customer-facing display that can be integrated or dispersed for maximum flexibility. Fujitsu offers a full set of leading-edge PoS peripheral options that have gone through extensive compatibility and reliability testing to maximize system scalability and flexibility. This robust peripheral portfolio gives retailers the ability to extend the useful life of the TP8A AIO through incremental modifications as business requirements change.

High Performance and Connectivity:

- Latest Intel® processors, Celeron to Core i5; Q170 chipset
- 32GB RAM max. 2x high speed DDR4 SO-DIMM
- Up to 2x M.2 PCIE NVME SSD, up to 3x faster than SATA3
- 1 x 2.5" bay for optional SATA3 drive
- Gigabit LAN. Optional WLAN
- Peripheral Ports: 2x Video, 10 USB (6x5V, 3x12V, 1x24V), 1x Serial DB9 0/5/12V, Audio, Cash Drawer

Versatility:

- Sleek contemporary design
- Counter-top and VESA options available
- 15" and 18.5" modular PCap Touch LCD (field swappable)

- Open architecture; wide operating system support

Green:

- Processor and LED backlight power-saving modes
- Efficient power supply supporting multiple peripherals
- Green recyclable materials: WEEE & ROHS compliant
- Eco-friendly packaging and minimal documentation

Reliability, Serviceability, Manageability:

- Secure data with long-life SSDs or HDDs & RAID support
- External access to memory and storage for fast repair
- LCD and PC Module are field replaceable, lower servicing costs and preserving components during future upgrades
- Remote-management support (AMT, vPro, SMBIOS)



TECHNICAL DETAILS

TP8A AIO

General Specifications

Processor	Intel 6 th Generation "Skylake" 35W, supporting Windows 7, 8.x and 10 : <ul style="list-style-type: none"> - A610: Celeron G3900TE 2.3GHz, 2 core / 2 threads, 2MB, No AMT - A630: Core i3-6100TE 2.7GHz, 2 core / 4 threads, 4MB, AMT Standard Manageability - A650: Core i5-6500TE 2.3-3.3GHz, 4 core / 4 threads, 6MB, AMT & vPro Intel 7 th Generation "Kaby Lake" 35W, supporting Windows 10 only : <ul style="list-style-type: none"> - A710: Celeron G3930TE 2.5GHz, 2 core / 2 threads, 2MB, No AMT - A730: Core i3-7101TE 3.4GHz, 2 core / 4 threads, 3MB, AMT Standard Manageability - A750: Core i5-7500T 2.7-3.3GHz, 4 core / 4 threads, 6MB, AMT & vPro
Chipset	Intel Q170 Express, Intel Active Management Technology (Intel® AMT v11.6) & vPro on Core i5, TPM v2.0
Operator Display	15" 4:3 and 18.5" 16:9 LCD size options, with Projected Capacitive Multi-Touch. Top spec 500cd/m ² 15" LCD panel.
Memory	4GB memory in all base models. 32GB max supported; 2 slots total. Optional 4GB, 8GB and 16GB modules
BIOS	AMI µEFI BIOS with Remote BIOS Flash
Audio	AC97-compliant high-definition audio
Graphics	Integrated Intel high-definition graphics controller
Connectivity	High-speed Gigabit LAN RJ-45 10/100/1000 Mbps with Wake On LAN.
Storage	Standard 1x 2.5" 128 / 256 / 512GB SATA3 SSD in base models Optional: 1x or 2x M.2 PCIe NVME SSD 128 or 256GB w/ RAID 0/1; or 2.5" 500GB SATA3 HDD
I/O Ports	10 USB (4x 5W USB 3.1 gen1, USB2: 2x5V, 3x12V, 1x24V), 1x Serial DB9 0/5/12V, 2x DisplayPort, 1x cash drawer RJ-12 (Y-cable option for 2 nd cash drawer), 1x line out, 1x mic in
Power Supply	220W AC Adapter supporting maximum powered peripheral configuration
System Management	Intel Active Management Technology (AMT) & vPro, Desktop Management Interface (DMI), Pre-boot Execution Environment (PXE), Advanced Power Management (APM), Advanced Configuration and Power Interface (ACPI), Wake on LAN (WOL), System Management BIOS, TPM v2.0
Color	Black
Dimensions	AIO 15" head unit: 366.9mm W x 66.5mm D x 300.9mm H (14.44" x 2.6" x 11.85") AIO 15" + stand: 366.9mm W x 246.8mm D x 351.1mm H (14.44" x 9.71" x 13.82")
Weight	5.4 Kg 11.92 lb (excluding stand) ; 8.88 Kg 19.58 lb (including stand)
Certifications	FCC, CSA, CB, CE, TUV, RCM, CCC (TBA), VCCI (TBA)
Green Compliance	WEEE, ROHS

Options Supports all popular standard retail peripherals

AIO Mounting	Countertop Stand, dual hinge for excellent adjustability, with connector & cable covers. 3 rd party VESA stands also.
Connectivity	Wireless LAN 802.11 a/b/g/n/ac. USB Dongle or Mini PCIe Card with Wake On LAN
Customer Display	Optional 15" colour customer-facing LCD, XGA 1024x768. Top spec LCD panel: Non-Touch 500cd/m ² , PCap Touch 450cd/m ² .
Customer VFD	Alpha-numeric (20 digits x 2 lines) 245 (W) x 40 (D) x 100 (H) mm non-integrated pole/remote mount (tilt/swivel)
Printers	Epson: TM-H6000, TM-H2000, TM-T88, TM-T70. Fujitsu CT-11, FP510II and FP-2000 series
Keyboards	Fujitsu 133-key and 110-key keyboards. Fujitsu AIO or Screen attached keypad.
AIO/LCD Attachments	3-Track Magnetic Stripe Reader (MSR), Numeric & Fn Keypad, Fingerprint scanner
Cash Drawers	Standard, Compact and Flip-Top

Software

Operating Systems	POSReady7 32/64bit, Windows 7 Pro, Windows8.1, Windows 10 IoT Ent. 2016/2019 LTSC Value, SUSE Linux 12
API's	Supports UPOS 1.14 (OPOS, JPOS) and ESC-POS based applications.

ASK FUJITSU

Fujitsu Australia, Head Office
 118 Talavera Rd, Macquarie Park, NSW 2113 +61 2 9776 4555 or
 visit www.fujitsu.com/au or askus@au.fujitsu.com

© Copyright Fujitsu Australia Limited 2019. Updated 18 Jul 2019. Fujitsu endeavors to ensure that the information in this document is correct and fairly stated, but does not accept liability for any errors or omissions. Specifications are subject to change without notice. All trademarks acknowledged.