

Fujitsu TP8 LCD Touch & Non-Touch Displays

MODELS

- TP8-D15PA 15" Projected capacitive touch screen, superior Anti-glare
- TP8-D15 15" non-touch screen
- TP8-D18WP 18.5" Wide Projected capacitive touch screen

D15 FEATURES

- Best 15" LCD for Retail POS, 1024 x 768 resolution, 16.7M colours
- 500 cd/m2 (NIT) high brightness LCD panel
- 70,000-hour Longest-life low-power LED backlight, 8yrs to ½ bright, 24x7 usage
- Widest viewing angles, Typ. 88°/88°/88°/88° up/down/L/R
- Best Contrast Ratio = 2500 : 1
- Best Anti-glare on market with superior AG glass cover on D15PA model

D18 FEATURES

- 18.5" 16:9 Wide, 1366 x 768 resolution, 16.7M colours
- 300 NIT bright LCD panel & 50,000-hour LED backlight, 6yrs to ½ bright, 24x7 usage

ALL MODELS

- Projected Capacitive with 10 point multi-touch gesturing support
- DisplayPort & HDMI ports
- Stereo speakers, 2x 2W on all models.
- Options: MSR, keypad, finger-print reader.
- Same LCD module as TP8A AIO for reduced Spares cost & fast easy field repair
- 1-hinge or 2-hinge height-adjust stand, with 0° to 150° tilt, Full cable routing & Quick release



PRODUCT SPECIFICATION

LCD Panels	TP8-D15/D15PA:	Active matrix TFT colour	User Controls	Menu: display the menu pages (Contrast, Brightness, Volume, Mute, Input Select, Display mode, OSD Off-Time, Language, and Reset)
	Size, aspect ratio:	15 inch diagonal, 4:3	Multimedia	Speakers: 2x 2W on all models
	Display area:	304mm W x 228mm H	IO Connectors	DisplayPort & HDMI. Adapter/cable: DVI, VGA. 12V Powered USB for display power and touch data on one cable (inc. USB type A connector)
	Resolution:	XGA 1024 x 768 pixels		Hidden USB LHS, RHS - MSR, Keypad, finger reader
	Brightness:	500 Cd/m ²	Touchscreen	Projected Capacitive, 10pt multi-touch gesturing
	Backlight:	Longest life LED, 70,000 hrs, 8 years to half-brilliance, 24x7 use	Environmental	Anti-reflective hardened glass filter. IP53 on front 0° to 40° Celsius operation, 10-95% Humidity
	Viewing angle:	Typ. 88°/88°/88°/88° up/down/L/R	Colour	Fujitsu black with silver trim
	Contrast Ratio:	Typ. 2500 : 1	Stand & Mounting Options	1-hinge or 2-hinge height-adjust stand, 0° to 150° tilt, Full cable routing & Quick release
	Response time:	7ms	Dimensions	VESA mount (100mm x 100mm)
				D15: 367 x 55.5 x 301 mm WDH, ex-stand
				D18: 470.8 x 55.5 x 301.6 mm WDH, ex-stand
			Power Consumption	Operational: D15PA <12.8W, D18WP <18.2W
				Standby: <3W
			Options	3 track MSR, keypad, finger-print reader. Left or right-hand mounting. External AC Adapter
			Certifications	FCC, CCC, VCCI, CE, CB, UL, RCM (Aust & NZ) ROHS, WEEE and REACH Compliant
Common across both displays:				
	Bezel:	Flat – Zero bezel design		
	Colours:	16.7M (8 bit)		

ASK FUJITSU

Fujitsu Australia, Head Office
118 Talavera Rd, Macquarie Park, NSW 2113 +61 2 9776 4555 or
visit www.fujitsu.com/au or askus@au.fujitsu.com

© Copyright Fujitsu Australia Limited 2019. Updated 1 Jun 2019. Fujitsu endeavors to ensure that the information in this document is correct and fairly stated, but does not accept liability for any errors or omissions. Specifications are subject to change without notice. All trademarks acknowledged.