

Fujitsu recommends Windows 11 Pro.

# Data Sheet

## Fujitsu Desktop ESPRIMO G9012

### A smart and ultra-compact Mini PC for advanced office needs

The Fujitsu ESPRIMO G9012 is a smart Mini PC which offers advanced Desktop PC functionality in an ultra-compact, space-saving design. Making it a perfect device for working from home or in flexible workplaces with its single cable Type-C connection. Provided with Intel vPro® with 12th or 13th Gen Intel® Core™ processors, the devices empowers impressive performance/volume ratio.

A smart Mini PC with ultra-compact design  
Eye-catching exclusive modern design

- Low noise Mini PC thus providing ergonomic, clean and clutter-free working environment
- Offers advanced desktop PC functionality with a volume of only ~0.87 liters
- Impressive performance/volume ratio and is easy to set up in minutes

Small in size but grand in performance

High performance in a small Mini PC design

- Intel chipset technology with 12th or 13th Generation Intel® Core™ processor family
- Intel® vPro™ Enterprise and Intel® vPro™ Essentials technology as BTO
- Next generation Intel integrated graphics

Flexibility without limits

Pleasant working environment due to quiet system

- Concept with different heights allows ODD and upgrade options like power supply and PCIe slot
- Flexibility for later device upgrades
- Various mounting options

Ultimate usability - Perfect fit for modern offices and workplaces

Flexible mounting options and wide range of usage scenarios

- Can be used for horizontal or vertical operations and easy upgrade of major components
- VESA mount for attaching the PC to displays, stands or walls
- Ideal device to use for home office scenarios due to its mobility and one cable solution

Reduced environmental impact and reduced energy bills

- High efficient AC adapter or internal 80Plus PLATINUM power supply as option
- Sum of post-consumer recycled content for plastic per weight is up to 50% (min. 11% are from ITE derived post-consumer material and min. 35% are any other post-consumer material)



# Components

	ESPRIMO G9012	ESPRIMO G9012 ESTAR
<b>Processor</b>	Intel® Core™ i7-12700 processor (12 Cores (8+4) / 20 Threads, 2.1 GHz, 25 MB, Intel® UHD Graphics 770) ** Intel® Core™ i7-13700 processor (16 cores (8+8) / 24 Threads, 5.1 GHz 30MB, Intel® UHD Graphics 770) Intel® Core™ i5-12500 processor (6 Cores / 12 Threads, 3.0 GHz, 18 MB, Intel® UHD Graphics 770) * Intel® Core™ i5-13500 processor (14 Cores (6+8) / 24 Threads, 5.10 GHz, 30 MB, Intel® UHD Graphics 770) Intel® Core™ i5-12400 processor (6 Cores / 12 Threads, 2.5 GHz, 18 MB, Intel® UHD Graphics 730) * Intel® Core™ i5-13400 processor (10 Cores (6+4) / 16 Threads, 2.5 GHz, 20 MB, Intel® UHD Graphics 730) Intel® Core™ i3-12100 processor (4 Cores / 8 Threads, 3.3 GHz, 12 MB, Intel® UHD Graphics 730) * Intel® Core™ i3-13100 processor (4 Cores / 8 Threads, 3.4 GHz, 12 MB, Intel® UHD Graphics 730)	Intel® vPro® Platform Logo (optional) with Intel® Core™ i5-12500, Intel® Core™ i5-12600, Intel® Core™ i7 and Intel® Core™ i9 processors *with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and other variables) **with Intel® Turbo Boost Max Technology 3.0 (clock speed and performance will vary depending on workload and other variables)
<b>Operating systems</b>		
Operating system pre-installed	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home Windows 10 Pro. Fujitsu recommends Windows 11 Pro for business.	
Operating system compatible	Certified for Red Hat® Enterprise Linux	
Operating system notes	Windows 11 requires for first device setup: - Internet connectivity - Microsoft account for Home editions or organizational account (e.g. ADD) for Pro editions After product end of life, Fujitsu continues to test and support new Windows releases for max. 5 years, depending on extension of hardware services through warranty top ups. For more details please visit our Fujitsu Service Statement under <a href="https://support.ts.fujitsu.com/IndexProdSupport.asp?lng=com&amp;OpenTab=">https://support.ts.fujitsu.com/IndexProdSupport.asp?lng=com&amp;OpenTab=</a> The use of Windows Operating System is subject to acceptance of the End User License Agreement of Microsoft as applicable under the relevant Microsoft program. Thunderbolt 4 not part of Red Hat® certification	
	ESPRIMO G9012	ESPRIMO G9012 ESTAR
<b>Memory modules</b>	32 GB (1 module(s) 32 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM	
	ESPRIMO G9012	ESPRIMO G9012 ESTAR
<b>Graphics</b>	Entry 3D: NVIDIA® T400, 4 GB, PCIe x16, 3 x miniDP Entry 3D: NVIDIA® T600, 4 GB, PCIe x16, 4 x miniDP Others: MiniDP to DP Adapter Cable	
	ESPRIMO G9012	ESPRIMO G9012 ESTAR
<b>Mass storage 2.5 inch size</b>	HDD SATA III, 5,400 rpm, 1000 GB, 2.5-inch HDD SATA III, 5,400 rpm, 2000 GB, 2.5-inch SSD SATA III, 1.92 TB High Endurance, 1.5DWDP, 2.5-inch SSD SATA III, 960 GB High Endurance, 1.5DWDP, 2.5-inch	
<b>Mass Storage M.2 technology</b>	SSD PCIe, 1024 GB M.2 NVMe module (Gen4), SED SSD PCIe, 2048 GB M.2 NVMe module (Gen4), SED SSD PCIe, 256 GB M.2 NVMe Module (Gen4), Value, SED SSD PCIe, 512 GB M.2 NVMe module (Gen4), SED	

Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. SSD (Solid State Disk) SED (Self-Encrypting Drive) 2.5-inch bay for devices with 7mm height Durability in accordance with the manufacturer's indications on read and write cycles.	
Optical drive	ESPRIMO G9012 DVD Super Multi ultra slim (tray), SATA	ESPRIMO G9012 ESTAR
Interfaces add on cards / components	ESPRIMO G9012 Parallel Card (1 Port) Intel® Wi-Fi 6E AX211 (2x2/160) Gig+ and Bluetooth 5.2 vPro; SRD cat.1 (dedicated regions only) Dual serial card PCIe x1 LP	ESPRIMO G9012 ESTAR Parallel Card (1 Port) Intel® Wi-Fi 6E AX211 (2x2/160) Gig+ and Bluetooth 5.2 vPro; SRD cat.1 (dedicated regions only) Dual serial card PCIe x1 LP
LAN Notes	WI-FI 6E: The device does not operate in 6GHz band in all countries, due to national regulations. see flexible interface options Bluetooth 5.2: Bluetooth® 5.2 operation requires Microsoft OS support. Until Microsoft OS support is available, Bluetooth® 5.2 will function as Bluetooth® 5.1 or lower	
Component notes	ESPRIMO G9012 The listed product components and optional functions are not available in all region/countries;  System is available in 3 different housing versions: Small version (0.87 Liter) ODD bay version (1.23 Liter) Internal Power supply (1,85 Liter) Internal Power supply/ PCIe Slot version (1.85 Liter)	ESPRIMO G9012 ESTAR The listed product components and optional functions are not available in all region/countries; Energy Star certification only with Windows operating system Base unit for TCO Certified generation 9;  System is available in 3 different housing versions: Small version (0.87 Liter) ODD bay version (1.23 Liter) Internal Power supply (1,85 Liter) Internal Power supply/ PCIe Slot version (1.85 Liter)

## Base unit

Base unit	ESPRIMO G9012	ESPRIMO G9012 ESTAR
<b>Mainboard</b>		
Mainboard type	D4014-A (base system) resp. D4015-A (Thunderbolt 4 version)	
Formfactor	proprietary	
Chipset	Intel® Q670	
Processor socket	LGA1700	
Processor quantity maximum	1	
Supported capacity RAM (max.)	64 GB (32GB BTO at factory)	
Memory slots	2 DIMM (DDR4)	
Memory frequency	3,200 MT/s	
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 3200 MHz may be clocked down to 2933/2400 MHz depending on processor and memory configuration Internal Power supply/ PCIe Slot version is limited to max. 48 GB total memory (32 GB + 16 GB)	
LAN	10/100/1,000 MBit/s Intel® I219LM	
Integrated WLAN	optional	
BIOS version	AMI Aptio V UEFI Specification 2.8	

**Mainboard**

BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC257N
Audio features	Internal speaker supports audio playback, High Definition audio

**I/O controller on board**

Serial ATA total	2
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI RAID 1/0

**Interfaces**

Front audio: headset	1	1
Flexible Interface Options	One of following flexible Interface options can be added to the base system (not on Thunderbolt version) HDMI™ (supports 4k@60Hz as specified in HDMI™ 2.1) DisplayPort™ 1.4a (external HDMI- and DVI adapters not supported) Serial port (9pin, 16 byte FIFO, 16550 compatible) 2x USB 2.0 Type A	One of following flexible Interface options can be added to the base system (not on Thunderbolt version) HDMI™ (supports 4k@60Hz as specified in HDMI™ 2.1) DisplayPort™ 1.4a (external HDMI- and DVI adapters not supported) Serial port (9pin, 16 byte FIFO, 16550 compatible) 2x USB 2.0 Type A
USB front	1x USB 3.2 Gen 1 (5 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2x2 (20 Gbps) Type-C (provides up to 15W)	1x USB 3.2 Gen 1 (5 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2x2 (20 Gbps) Type-C (provides up to 15W)
USB rear	Base system: 1x USB 2.0 Type-A 3x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 Type-C (10 Gbps, supports DisplayPort 1.4 and power delivery sink**)	Base system: 1x USB 2.0 Type-A 3x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 Type-C (10 Gbps, supports DisplayPort 1.4 and power delivery sink**)
DisplayPort	1 (DisplayPort 1.4; DP++)	1 (DisplayPort 1.4; DP++)
HDMI	1 - Supports 4K@60Hz as specified in HDMI™ 2.1	1 - Supports 4K@60Hz as specified in HDMI™ 2.1
Ethernet (RJ-45)	1	1
Interface Module notes	**With power delivery sink support, the system is operated by the power from peripherals, e.g. port replicators or displays. An extra power supply for the system is not needed. Peripherals must provide min. 60 Watt or 90 Watt (for maximum CPU performance).	**With power delivery sink support, the system is operated by the power from peripherals, e.g. port replicators or displays. An extra power supply for the system is not needed. Peripherals must provide min. 60Watt or 90Watt (for maximum CPU performance).
Kensington Lock support	1	1

**Input device / components**

Input devices (optional)	Keyboard Mouse
--------------------------	-------------------

**Drive bays**

Drive bays total	2
2.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	5.25" bay: for slim optical disc drive only as option with ODD bay housing version;
M.2-2280	1 x on mainboard (PCIe 4.0 x4; up to 64Gbit/s) and 1 x optional (PCIe 3.0 x4; up to 32Gbit/s)

**Slots**

PCI-Express 3.0 x4 (mech. x16)	1 x (168 mm / 6.61 inch)
M.2-2230	on mainboard for WLAN module

**Graphics on board**

Graphics brand name	Intel® UHD Graphics 770, Intel® UHD Graphics 730, Intel® UHD Graphics 710	
Shared video memory	Up to half size of total system memory	
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel	
TFT resolution (HDMI)	Up to 4,096 x 2,304 pixel	
Graphics features	Support for up to four independent displays DirectX® 12.1 HDCP support OpenCL 3.0 OpenGL® 4.6 Vulkan™ DisplayPort interface supports Ver. 1.4 incl. Multi-Stream Digital audio formats are supported, including Dolby Digital Plus (7.1 channels) see flexible interface options	

Base unit	ESPRIMO G9012	ESPRIMO G9012 ESTAR
-----------	---------------	---------------------

**Electrical values**

Power efficiency note	90 Watt AC adapter: power supply efficiency at 115/230 V: 89% average efficiency 150 Watt internal PLATINUM power supply (optional): Power supply efficiency in % at 10% / 20% / 50% / 100% load for 230 V ; 90/93/94/94 for 115 V ; 90/91/93/92	90 Watt AC adapter: power supply efficiency at 115/230V: 89% average efficiency 150 Watt internal PLATINUM power supply (optional): Power supply efficiency in % at 10% / 20% / 50% / 100% load for 230V ; 90/93/94/94 for 115V ; 90/91/93/92
Rated voltage range	100 V - 240 V	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz	47 Hz - 63 Hz
Max. output of single power supply	AC Adapter: 90 W internal PLATINUM power supply (optional): 150 W	AC Adapter: 90 W internal PLATINUM power supply (optional): 150 W
Base unit	ESPRIMO G9012	ESPRIMO G9012 ESTAR

**Power consumption**

Power consumption note	See white paper Energy Consumption
------------------------	------------------------------------

**Noise emission**

Related Processors for noise	Intel® Core™ i5-12500T processor and 8GB, no ODD, Windows 11 (tower position)
Standard noise emission	According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	3.0 B / 17 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2)
Standard noise operation mode: HDD load	3.5 B / 22 dB(A) Bystander; 23 dB(A) Operator position (SSD M.2)
Standard noise operation mode: Idle mode	2.9 B / 16 dB(A) Bystander; 16 dB(A) Operator position (SSD M.2)
Standard noise operation mode: Office applications 2.0	

**Dimensions / Weight / Environmental**

Dimensions (W x D x H)	146.5 x 164.5 x 36 mm 5.77 x 6.48 x 1.42 inch
Dimension notes	With ODD drive bay, the dimensions are: 146.5 x 164.5 x 51 mm (5.77 x 6.48 x 2.01 inch) With internal power supply / PCIe slot version, the dimensions are: 146.5 x 176.9 x 71 mm (5.77 x 6.97 x 2.80 inch)
Operating position	Vertical / horizontal (feet included)

**Dimensions / Weight / Environmental**

Weight	Small Min:0.86kg; 1x mem,1xSDD Max:1.025kg; 2x mem,2xSSD,HDD,Flexi,WLAN ODD vers.: Min:1.2kg/Max:1.29kg int. PSU vers.: Min:1.45kg/Max:1.59kg AC adapt.(0.32kg), power cord(0.175kg) not part of min/max
Weight (lbs)	Small: Min: 1.89 lbs / Max: 2.246 lbs ODD version: Min:2.65 lbs / Max:2.84 lbs Int. PSU version: Min:3.2 lbs / Max:5.51 lbs AC adapter (0.71 lbs) and power cord 0.39 lbs) are not part of min/max lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

**Compliance**

Product	ESPRIMO G9012-1 (AC Adapter) ESPRIMO G9012-2 (Internal PSU)	ESPRIMO G9012 ESTAR1 (AC Adapter) ESPRIMO G9012 ESTAR2 (Internal PSU)
Model	MPCG	
Germany	GS TÜV NRTL	
Europe	CE	
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) Microsoft Secured-core PC certification (for selected configurations) ENERGY STAR® 8.0 TCO Certified, generation 9 EPEAT® Gold (dedicated regions)
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>	

**Additional Software**

Additional software (preinstalled)	McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) Nero Essentials XL Microsoft® Office Professional 2021 Microsoft® Office Home and Business 2021 (Need to buy license to activate the pre-installed Microsoft Office. Purchase and activation only in the region in which it was acquired.)
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.
Base unit	ESPRIMO G9012 ESPRIMO G9012 ESTAR

**Security**

Physical Security	Kensington Lock support Eye for padlock
-------------------	--

<b>Security</b>	
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME) Modern Standby (Windows 11 only) and Legacy Standby selectable Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces NIST SP800-147 BIOS Protection supported NIST SP800-155 BIOS Integrity Measurement supported NIST SP800-193 Platform Firmware Resiliency supported
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional)
Security Notes	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.
<b>Manageability</b>	
Manageability technology	Intel® vPro® Essentials (optional) Intel® vPro® Enterprise (optional) Intel AMT 16.0 (optional; depending on processor) DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	BIOS Management incl. Security Inventory Management Driver Management Alarm Management
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)
Manageability link	<a href="https://www.fujitsu.com/global/products/computing/pc/manageability/">https://www.fujitsu.com/global/products/computing/pc/manageability/</a>
<b>Miscellaneous</b>	
	Keyboard on with one key (Fujitsu Keyboards KB521, KB955) Keyboard on with two keys (CTRL+CTRL; special Fujitsu USB keyboards required) Keyboard on with any key (USB) Thermal management Extended lifetime (internal power supply version only)
Accessories information	Further helpful options  Desktop Accessories: <a href="http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/">http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/</a> <a href="http://www.fujitsu.com/global/products/computing/peripheral/accessories/connectivity/">http://www.fujitsu.com/global/products/computing/peripheral/accessories/connectivity/</a>  Stands and Mounting kits: <a href="http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/ums/index.html">http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/ums/index.html</a> Available Adapters: <a href="http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf">http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf</a>
<b>Packaging information</b>	
Packaging dimension (mm)	395 x 198 x 284 mm

**Packaging information**

Packaging dimension (inch)	15.55 x 7.8 x 11.18 inch
Max. quantity / pallet	42
Material - Weight (g) Carton	830 g
Material - Weight (lbs) Carton	1.83 lbs
Material - Weight (g) PE	15 g
Material - Weight (lbs) PE	0.03 lbs
Packaging notes	If keyboard is included in packaging: 1.)packaging dimension is increasing to: 497 x 206 x 293mm / (19.6 x 8.11 x 11.5 inch); 2.) material weight is increasing to: carton 1025g, PE 15g Internal PSU version: the material weight is: carton 638g (wo KB)/ 833g (w. KB), PE 93g printed user documentation is bleached in chlorin free process; Bulk packaging for projects (optional)

**Warranty**

Warranty period	3 years
Warranty type	Next Business Day Onsite Service (Metro areas only)
Warranty Terms & Conditions	<a href="http://www.fujitsu.com/warranty">http://www.fujitsu.com/warranty</a>
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: <a href="https://support.ts.fujitsu.com/">https://support.ts.fujitsu.com/</a> free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.

**Product Support - the perfect extension**

Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	at least 5 years after shipment, for details see <a href="https://support.ts.fujitsu.com/">https://support.ts.fujitsu.com/</a>
Service Weblink	<a href="http://www.fujitsu.com/emeia/products/product-support-services/">http://www.fujitsu.com/emeia/products/product-support-services/</a>

## Recommended Accessories

Thunderbolt™ 4 Port Replicator		First Thunderbolt™ Port Replicator on the market providing enhanced security and full support of Intel® AMT (vPro®). The universal port can easily connect almost everything with a single cable and high speed-data transfer. This smart workspace solution keeps your desk clean and tidy.	Order Code: FPCPR401BP
USB Type-C Port Replicator 2		Connect to your peripherals. Adapt to the task on demand. The universal USB Type-C interface supports you to get your peripheral devices connected easily. Multiply your USB ports to connect your peripherals as well as your external display via HDMI, DisplayPort or VGA. You also can charge your external USB devices without the need of any additional charger.	Order Code: S26391-F3327-L100

---

Mounting Kit for Height Adjustable Fujitsu Displays - up to 11th Gen. Display (2022)



The Fujitsu Mounting Kit for Height Adjustable Fujitsu Displays has been specifically (2022) designed for use with ESPRIMO Q/G Mini PCs, FUTRO Thin Clients and Fujitsu Displays. With this solution you can save space on the desk, reduce clutter on desk and realize a clean desk working environment.

Order Code:  
FPCSK834GP

---

Mounting Kit for Height Adjustable Fujitsu Displays - up to 10th Gen. Display



The Fujitsu Mounting Kit for Height Adjustable Fujitsu Displays has been specifically designed for use with ESPRIMO Q/G Mini PCs, FUTRO Thin Clients and Fujitsu Displays. With this solution you can save space on the desk, reduce clutter on desk and realize a clean desk working environment.

Order Code:  
S26361-F2542-L452

## More information

### Fujitsu products, solutions & services

In addition to Fujitsu Desktop ESPRIMO G9012, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about Fujitsu Desktop ESPRIMO G9012, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/emeia/products/computing/pc/desktops/](http://www.fujitsu.com/emeia/products/computing/pc/desktops/)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>  
Copyright 2023 Fujitsu Technology Solutions GmbH

### Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

### Contact

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com](http://www.fujitsu.com)  
2023-05-02 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>  
Copyright 2023 Fujitsu Technology Solutions GmbH