

Datasheet

Fujitsu

AIO Display

P2410



Universal widescreen 60.5 cm (23.8 inch) All-in-One display unit for Mini PC. Clean up your desk with space saving and secure solution.

The Fujitsu AIO Display P2410 is the universal display unit for Mini PC platform like ESPRIMO Gx012. Small to be connected via USB Type-C to enables All-in-One like usage. This all-rounder comes with front and side USB connectors for ergonomic comfort and optional side optical drive for wide range of usage.

Excellent and wide performance range fits customer needs

- Use of Mini PC platforms like ESPRIMO G system for ease of future upgrades
- Optional optical drive on right-hand side extends the possible usage scenario
- AIO display unit can be used as single display and supports Daisy Chain

Human-centric setup for efficient working

- Anti-glare Full HD display with 3 sides frameless display
- Wall mount via VESA standard
- Innovative housing by offering the right-hand USB hub

Ultimate usability and ergonomic comfort to increase productivity

- Easy access and flexible interfaces of used Mini PC
- Microphone and camera for instant office communication
- Flexible height adjustment, screen with a large swivel and tilt range
- Front USB for easy access and space saving on the sides
- Retina protection by low blue light panel without any loss or changes of color
- Integrated auto brightness display sensor to reduce eye strain

Robust security to protect data and hardware

- Secure and tidy system with integrated cable cover
- One lock can secure all removable parts
- Mechanical lever lock for Webcam

Low environmental impact and reduced bills

- Usable for more than one platform for long life time
- Energy saving with integrated auto brightness sensor



Components

Special features

Smart Power ON and LED function for AIO-type usage
 (in combination with a dedicated Fujitsu systems e.g. ESPRIMO G or selected LIFEBOOK models)
 Optical disk drive on right-hand side (optional)
 Cable cover with Kensington Lock preparation to secure complete system
 MS Hello compatible WebCam
 Integrated speakers
 In-Plane Switching (IPS) technology
 Eco button for Eco mode and 4-colored status LED
 Auto Brightness Control (ABC)
 Low blue light mode
 Presence sensor with PC security solution
 Color accuracy average DeltaE<2
 Workplace Lighting Guide
 DICOM Greyscale Standard Display Function compatible gamma preset
 Always available USB (in operating and standby mode)
 5-in-1 Stand
 Cable guide
 24/7 usage
 DisplayView™ Software

Ergonomic stand

Stand	5-in-1 Stand
Height adjust range	120 mm
Picture height over desk (min)	44.8 mm
Tilt angle	-5° / +35°
Swivel angle	345°

Picture performance

Panel and backlit	In-Plane Switching (IPS) technology/LED
Contrast - typical	1,000:1
Contrast-advanced	20,000,000:1
Response time gray to gray typical	5 ms (in Video mode)
Viewing angle (h/v) - typical	178°/178° CR10:1
Color performance	16.7 million colors (Hi-FRC)
High color gamut-typical	99% sRGB color space
Brightness - typical	250 cd/m ²

Size and resolution

Aspect ratio	16:9
Diagonal Size	60.5 cm (23.8-inch)
Resolution (native)	1,920 x 1,080 pixel
Resolution (interpolated)	1,680 x 1,050 pixel, 1,440 x 900 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel

Picture size	527 x 296 mm
Pixel Pitch	0.2745 mm
Frequencies	
Horizontal	30 - 82 kHz
Vertical	48 - 76 Hz
Connectivity	
DisplayPort	1 x DisplayPort Out (Daisy Chain), 1 x DisplayPort 1.2
HDMI	1 x HDMI 1.4
Audio signal output	3.5 mm stereo phone jack for head phone
Audio sound output	2 x 2 W
DisplayPort audio	Yes
HDMI audio	Yes
USB downstream	4 x USB 3.2 Superspeed 5Gbit (1x Type-C and 1x Type-A on side, 2x Type-A on bottom; additional 2x Type-A in front (if cable is connected to the Mini PC system))
USB upstream	1 x USB Type-C with alternate mode for video data and power delivery up to 95 W 1 x USB 3.2 Gen1 Type B Integrated KVM switch function
Ethernet (RJ-45)	1 x Gigabit LAN PXE, Wake on LAN (from S3), MAC Address Pass Through support with selected LIFEBOOK models
Ease-of-use menu	
Notes	6 tactile keys on front side
Direct Access Keys	Menu, ECO, Input, Mode, Audio, Brightness
Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto Brightness, ACR, Lighting Guide
Mode	D-Mode, sRGB, Low Blue Light, Office, Photo, Video, Custom
Color	5000K, 6500K, 7500K, Native, RGB Adjust
OSD	Language, OSD-Timeout, OSD rotation
Image adjust	Expansion, Saturation, Sharpness
Audio	Mute, Volume, Input for HDMI and DP interface
Information	Model name, Serial number, Signal input, Resolution/mode, Display mode, Color Temperature, ACR Status, ABC Status, Firmware version
Advanced settings	Presence Sensor, Proximity Adjust, Daisy Chain, Overdrive, DDC/CI, Factory Recall
Power consumption (Typical)	
Soft switch off	0.26 W
Power save mode	0.51 W
Operating with EPA settings	14.36 W
Total Energy Consumption (ETEC)	46.93 kWh/year

Operating maximum brightness	26 W
Power supply	integrated
Power notes	Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 8.0 Power save mode according to EEL test conditions
Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Model	P2410T
Global	TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TCO Certification in progress, EPEAT® Gold (dedicated regions) in progress, ENERGY STAR® in progress
Europe	EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration
Germany	TÜV GS
Russia	EAC
Singapore	S-Mark
Taiwan	BSMI
USA/Canada	FCC Class B, cTUVus
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	539.12 x 89.6 x 338.6 mm 21.23 x 3.52 x 13.33 inch
Dimension with stand (W x D x H)	539.12 x 275 x 490.53 mm 21.23 x 10.82 x 19.31 inch
Dimension (packed)	613 x 382 x 260 mm
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	10 - 85 % (non-condensing)
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Matt black

Additional Software

Package content

Display delivered accessories	Quickstart flyer
	Safety notes

Warranty

Warranty Terms & Conditions	https://www.fujitsu.com/hk/ap/warranty
-----------------------------	---

More information

Moving forward for a sustainable world – Fujitsu Uvance



The word “Uvance” embodies a concept of “Making all (Universal) things move forward (Advance) in a sustainable direction.

Fujitsu Uvance will leverage Fujitsu's technological capabilities and problem-solving expertise across seven key focus areas, including Sustainable Manufacturing, Consumer Experience, Healthy Living, Trusted Society, Digital Shifts, Business Applications, and Hybrid IT, to offer unprecedented value to customers, while contributing to the achievement of its

ultimate purpose —“to make the world more sustainable by building trust in society through innovation.”

Through Fujitsu Uvance, we are committed to transforming the world into a place where people can live their lives, enjoying prosperity and peace of mind. Empowering each other to make the world more sustainable.

For more information of Fujitsu Uvance, please visit <https://www2.fujitsu.com/global/uvance>

Driving customer success with Fujitsu's complete portfolio of service offering

To grow in an uncertain world, it is imperative to stay resilient and agile to respond complex and unforeseen challenges.

Under the global business brand – Uvance, Fujitsu provides a full range of reliable and best-in-class product, service, and solution offerings with digital innovation, from sustainable manufacturing to smart city ecosystem, to create a more sustainable world and resolve social issues. This empowers customers to strengthen resilience through Fujitsu's trusted solutions using cutting-edge technologies, while increasing their business agility and improving the reliability of their IT operations.

For more information, please visit <https://www.fujitsu.com/global>

Contact Us

HONG KONG

Fujitsu Business Technologies Asia Pacific Ltd.

Tel: (852) 3910-8228
Email: fbta.hksales@fujitsu.com
hk.fujitsu.com/pc

INDONESIA

PT Fujitsu Indonesia

Tel: (62) 21-570-9330
Email: marketing.fid@fujitsu.com
id.fujitsu.com/pc

TAIWAN

Fujitsu Taiwan Ltd.

Tel: (886) 2-2311-2255
Email: ftl.lifebook@fujitsu.com
tw.fujitsu.com/pc

SINGAPORE

Fujitsu Asia Pte Ltd.

Tel: (65) 6512-7555
Email: fapl.info@fujitsu.com
sg.fujitsu.com/pc

PHILIPPINES

Fujitsu Philippines, Inc.

Tel: (63) 2-8841-8488
Email: info-ph@fujitsu.com
ph.fujitsu.com/pc

THAILAND

Fujitsu (Thailand) Co., Ltd.

Tel: (66) 0-2302-1500
Email: info.th@fujitsu.com
th.fujitsu.com/pc

CHINA

Fujitsu (China) Holdings Co., Ltd. – PC China Division

Tel: 86 (21) 58871000-8721
Email: fbta.cs@fujitsu.com
cn.fujitsu.com/pc

MALAYSIA

Fujitsu (Malaysia) Sdn. Bhd

Tel: (60) 3-8230-4188
Email: askfujitsu.my@fujitsu.com
my.fujitsu.com/pc

VIETNAM

Fujitsu Vietnam Limited

Tel: (84-24) 2220-3113
Email: sales-vn@fujitsu.com
vn.fujitsu.com/pc

Note: For countries not listed above, please contact Hong Kong office.

Specification disclaimers

¹ Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 11 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. ² GB = 1 billion bytes. TB = 1 trillion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery. ³ Shared memory depending on main memory size and operating system.

Fujitsu shall not be liable for technical or editorial errors or omissions contained herein. Ultrabook, Celeron, Celeron Inside, Core Inside, Intel, Intel Logo, Intel Atom, Intel Atom Inside, Intel Core, Intel Inside, Intel Inside Logo, Intel vPro, Intel Evo, Itanium, Itanium Inside, Pentium, Pentium Inside, vPro Inside, Xeon, Xeon Phi, Xeon Inside, Intel Agilex, Arria, Cyclone, Movidius, eASIC, Enpirion, Iris, MAX, Intel RealSense, Stratix, and Intel Optane are trademarks of Intel Corporation or its subsidiaries. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. All other trademarks are the property of their respective owners.

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/global/about/resources/terms/.

© 2022 Fujitsu Business Technologies Asia Pacific Limited