

microSD/TF Card Connector

FCN-560 Series

RoHS compliant

microSD is currently the world's smallest memory card storage system, specifically designed for use with ultra-small mobile phones and other devices. Like the miniSD, the microSD/TransFlash is ideal for use in storing media-rich files such as music, videos, and photographs in compatible mobile phones.

Fujitsu's microSD connector offers the lowest profile height (1.65mm) currently available in the market.

Featuring Fujitsu's precise and insert molding technology, the FCN-560 series micro SD connector measures 15mm (D) x 14mm (W) x 1.6mm (H) and has a life cycle of ten thousand insertions/withdrawals.

Fujitsu's connector uses a proprietary push-push structure that provides positive tactile feedback during card insertion and withdrawal.

A card drop protection mechanism prevents the card from falling out during pre-insertion and forced card extraction after it's locked in. When ejected, the card travels 3.5mm from its locked position.



FEATURES


- Reduction in seize and weight (15 (D) x 14 (W) x 1.65 (H)mm) with unique push-push structure
- Half-lock to prevent forced card extraction, good operability with sense of click for insertion
- Smooth card inserion/withdrawl with unique drop-protection mechanism
- With card detections switch
- Card ejection distance 3.5mm
- FCN-568Z008-G/0M

Item	Specification
Operating temperature range	-20°C to +70°C
Current rating	AC 0.5A
Voltage rating	AC/DC 5V
Contact resistance	100mΩ maximum
Dielectric withstanding voltage	AC 500V for 1 minute
Insertion/Withdrawl life	10,000 cycles

Item	Specification
Insulating material	LCP, UL94 V-0
Contact	Copper Alloy Plating NiPdAu
Pin / Spring	SWPA
Metal Cover	Stainless steel

Tape and reel: 1, 500 pcs/reel

SPECIFICATIONS



注1 指示寸法は単位はmmとし、公差は±0.1とする。
 Note1 Unless otherwise specified dimensions are in mm and tolerances are 0.1 mm.
 注2 本規格はRHS各部の寸法について指示の公差を満足している。
 Note2 This product conforms to regulation of content concerning to six substance
 ⑬⑭⑮⑯⑰⑱ ハートが適切位置に装着してフックを行って、ハートが任意位置にフックの機能は満足している。
 Note3 The connector must be relocked in unlocked position, otherwise permanent

■ SPECIFICATIONS



Fujitsu Components Asia Ltd.
102E Pasir Panjang Road
#01-01 Citilink Warehouse Complex
Singapore 118529
Tel: (65) 6375-8560
Fax: (65) 6273-3021
Email: fcgal@fcgal.fujitsu.com
Web: <http://www.fujitsu.com/sq/services/micro/components/>

3