

# Datasheet FUJITSU Image Scanner SP-1125N

Simple and network compatible scanner for business



SP-1125N scans documents at 25 ppm/50 ipm (A4 portrait 200/300 dpi) and loads up to 50 sheets at a time. With a compact and network compatible design, the unit provides high-value performance as an entry-level model for all businesses.

## Assistance for safe and reliable scanning

SP-1125N comes with brake rollers to deliver accurate page separation and prevent any multi-feeding errors from occurring. This mechanism and our ultrasonic multi-feed sensors combined, provide users with stable paper feeding, prevent any potential information loss from occurring, and enable scanning of all documents and cards at the office with maximized precision and efficiency. Application forms and ID cards at the reception desk, for instance, can be scanned in just one batch, allowing for quick processing and little customer wait time.

# Flexible and easy operation to improve daily workflow

High-speed USB 3.2 Gen 1x1 and wired network connection expands the versatility of user operation so that users are no longer confined to operating near the computer. Operation is now possible in a wider variety of locations, with reliable network environment support. SP-1125N is also compact in size, making it the perfect scanner to use on a desk or reception space where space is limited. As an entry-level model, operation is simple with just 2 buttons to choose from: "Scan/Stop" and "Power ON/OFF". This simple and easy-to-use design minimizes scanning procedures and human errors in any organization. All these features combined, enable anyone to operate the scanner anywhere.

### Software for ultimate business efficiency

PaperStream IP for SP Series, the scanner driver supporting both TWAIN and ISIS, enables hassle-free scanning so that operators do not need to make fine OCR setting adjustments. The software automatically converts scanned images into exceptionally clean images, raising OCR accuracy, even when scanning wrinkled and soiled documents, or documents with background patterns. With PaperStream Capture, capture batches of all sizes with utmost efficiency.

# Document software for maximized flexibility

Easily find the information you need using ABBYY FineReader Sprint. Specializing in OCR processing, the software is compatible with over 190 languages and generates both searchable PDF and Microsoft Office documents.

#### **Technical Information**

Scanner Type	ADF (Automatic Document Feeder), Duplex	Operating Enviror	
Scanning Speed*1 (A4 Portrait)	Simplex: 25 ppm (200/300 dpi)	Temperature	
(Color* <sup>2</sup> /Grayscale* <sup>2</sup> /Monochrome* <sup>3</sup> )	Duplex: 50 ipm (200/300 dpi)	Relative Humidity	
Image Sensor Type	Single line CMOS-CIS x 2 (front x 1, back x 1)	Environmental Co	
Light Source	RGB LED x 2 (front x 1, back x 1)	Dimensions*14	
Optical Resolution	600 dpi	(Width x Depth x	
Output Resolution** (Color / Grayscale / Monochrome)	50 to 600 dpi (adjustable by 1 dpi increments) 1,200 dpi (driver)**	Weight Supported Operat	
Output Format	Color: 24-bit, Grayscale: 8-bit, Monochrome: 1-bit		
Background Colors	White		
Document Size		Included Software	
Maximum	216 x 355.6 mm (8.5 x 14 in.)		
Minimum	52 x 74 mm (2.0 x 2.9 in.)		
Long Page Scanning*6 (Maximum)	3,048 mm (120 in.)		
Paper Weight (Thickness)		Image Processing	
Paper	50 to 209 g/m² (13.4 to 56 lb)*7	, ,	
Plastic Card	0.76 mm (0.0299 in.) or less**		
ADF Capacity****	50 sheets (A4 80 g/m <sup>2</sup> or Letter 20 lb)		
Expected Daily Volume*11	4,000 sheets		
Multifeed Detection	Overlap detection (Ultrasonic sensor)	Included Items	
Interface			
USB*12*13	USB 3.2 Gen 1x1 / USB 2.0 / USB 1.1	Options	
Ethernet	10BASE-T,100BASE-TX,1000BASE-T	PaperStream Capt Scan Station (WG)	
Power Requirements	AC 100 to 240 V ±10 %		
Power Consumption			
Operating Mode	18 W or less	Consumables	
Power Saving Mode	2 W or less		
Auto Standby (Off) Mode	0.3 W or less	Roller Set PA	

Operating Environment				
Temperature	5 to 35 °C (41 to 95 °F)			
Relative Humidity	20 to 80% (non-condensing)			
Environmental Compliance	ENERGY STAR <sup>®</sup> , RoHS			
Dimensions* <sup>14</sup> (Width x Depth x Height)	298 x 135 x 133 mm (11.7 x 5.3 x 5.2 in.)			
Weight	2.5 kg (5.5 lb)			
Supported Operating System	Windows® 10, Windows® 8.1, Windows® 7, Windows Server® 2019, Windows Server® 2016, Windows Server® 2012 R2, Windows Server® 2012, Windows Server® 2008 R2, macOS, Linux (Ubuntu)			
Included Software / Drivers	PaperStream IP for SP Series (TWAIN/TWAIN x64/ISIS), WIA Driver*15, Image Scanner Driver for macOS (ICA)*15*16, Image Scanner Driver for Linux (SANE)*15*16, PaperStream Capture, Software Operation Panel, Error Recovery Guide, ABBYY FineReader for ScanSnap*16, Scanner Central Admin, ABBYY <sup>m</sup> FineReader Sprint <sup>mx+17</sup> , Network Setup Tool for SP Series, SP Series Online Update Multi image output, Automatic color detection, Automatic page size detection, Blank page detection, Dynamic threshold (iDTC), Advanced DTC, SDTC, Error diffusion, Dither, De-Screen, Emphasis, Dropout color (None/Red/Green/Blue/ White/Saturation/Lustom), sRGB output, Split image, De-Skew, Edge filler, Vertical streaks reduction, Digital endorser, Background pattern removal, Character thickness, Character augmentation, Character extraction			
Image Processing Functions				
Included Items	AC adapter, USB cable, Setup DVD-ROM			
Options				
PaperStream Capture Pro PAA Scan Station (WG)	43404-A665 PaperStream Capture Pro optional license			
Consumables				
Roller Set PA03708-0001	Brake Roller Pick Roller Every 100,000 sheets or one year			

stacker. \*15 Functions equivalent to those offered by PaperStream IP may not be available with the Image Scanner Driver for acco/Linux or WIA Driver. \*16 Refer to the SP Series Support Site for for driver/software downloads and full lineup of all supported operating system versions. \*17 Operation on Windows Server® OS is not supported.

#### Trademarks

ABBYY\* FineReader<sup>™</sup> Engine © ABBYY. OCR by ABBYY. ABBYY and FineReader are trademarks of ABBYY Software, Ltd. which may be registered in some jurisdictions. ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. macOS is a trademark of Apple Inc., registered in the U.S. and other countries. Linux is the registered trademark of Linus Torvalds in the U.S. and other countries. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies. Safety Precautions

resultions Be sure to carefully read all safety precautions prior to using this product and use this device as instructed. Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product. Be sure to limit the use of this product to listed power ratings. ENERGY STAR®

PFU Limited, a Fujitsu company, has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.

Specifications are subject to change without notice. Visit your local Fujitsu website for more information.

### Contact

PT Fujitsu Indonesia Fujitsu (Malaysia) Sdn Bhd Fri Tel: +62 21 570 9330 Tel: +603 8230 4188 Tel callcenter@id.fujitsu.com askfujitsu@my.fujitsu.com in	Fujitsu Philippines, Inc. Fu Tel: +63 2 841 8488 Te nfo@ph.fujitsu.com sc	Fujitsu Asia Pte Ltd Fel: +65 6512 7555 scanner@sg.fujitsu.com	Tel: +66 2 302 1500	Vietnam Fujitsu Vietnam Limited Tel: + 84 4 2220 3113 sales@vn.fujitsu.com www.fujitsu.com/vn/en/scanners
---	---	--	---------------------	---