

Data Sheet

FUJITSU Display V22T-2R

Display

Value display: 54.6cm (21.5-inch) widescreen

The FUJITSU Display V22T-2R LED comes in a 16:9 format with a trendy style. There is no compromise in picture quality and energy efficiency. It is the best choice to get high pixel density with restricted desk space. It is easy-to-use and once it is installed you never have to adjust it again – proven Fujitsu quality.

Widescreen display with LED backlight panel in optimum 16:9 format

< 1W/inch typical power consumption

1920 x 1080FHD resolution for excellent entertainment experience

Includes both Analog (VGA) and Digital (DVI or DP, HDMI) display inputs

Low blue light mode



Technical details

Order information		
Order Code	HLMNR23EUB-01	HLMNR23EUB-02
EAN Code	8888551312047	8888551313488
Special Feature	Ultra-slim with integrated power supply	
Stand details		
Stand	Removable	
Picture height over desk (mm)	82 mm	
Tilt angle	-5° / +20°	
Picture performance		
Panel and backlit	VA/LED	
Screen Surface Treatment	Anti-glare, 3H hard coating	
Contrast – typical	3000:1	
Contrast – advanced	10,000,000:1	
Response time	12ms	5 ms(OD)
Viewing angle (h/v) - typical	178°/178°	
Color performance	16.7 million colors (Hi-FRC)	
Brightness – typical	250 cd/m²	
Low blue light mode	Supported	
Size and Resolution		
Aspect ratio	16:9	
Diagonal Size	54.6 cm (21.5-inch)	
Resolution (native)	1920 x 1080 (recommended)	
Resolution (interpolated)	1680 x 1050 pixel, 1440 x 900 pixel, 1366 x 768 pixel, 1280 x 1024 pixel, 1280 x 720 pixel, 1024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel	
Picture Size	476.06mm*267.79mm	
Pixel Pitch	0.24795mm	
Connectivity		
VGA/D-SUB	1 x D-SUB	1 x D-SUB
DVI	1 x DVI-D (Dual Link)	N/A
HDMI	N/A	1 x HDMI 1.4
Display Port	N/A	1 x DP 1.2
Audio signal input	3.5 mm stereo phone jack	
Audio sound output	2 x 2 W	
OSD Languages and setting options		
Languages	English, French, German, Italian, Japanese, Korean, Espanola, Portuguese, Russian, Turkish, Simplified Chinese, Traditional Chinese	
Brightness / Contrast / Color	Brightness, Contrast, Color Temperature	
Image adjust	H-Position, V-Position, Clock, Phase	
On Screen Display (OSD)	Language, H-Position, V-Position, Timer, Transparency	
Setup	Picture Mode, Signal Source, Aspect Ratio, DCR	
Factory Reset	Reset	
Power consumption (typical)		
Soft switch off	<0.5 W	
Operating maximum brightness	<25W	
Power supply display	Integrated	
Electrical values		
Rated voltage range	100 V – 240 V	
Rated frequency range	50 Hz – 60 Hz	
Protection class	1	
Quality and Reliability		
MTBF (demonstrated)	30,000h	
Dimensions / Weight / Environmental		
Dimension with stand (W x D x H)	489mm x 186.7mm x 378mm	

Weight (packed)	3.6 kg	
Weight (Monitor only)	2.8 kg	
Miscellaneous		
Miscellaneous	VESA DDC/CI, Flat Display Mounting Interface VESA MIS-D 100C, Kensington lock	
Color	Matt black	
Package content		
Display delivered accessories	Power cable for wall socket (EU), DVI-D (single link) Data cable, User Manual	Power cable for wall socket (EU), Display Port Data cable, User Manual
Display delivered accessories notes	Data cables and power cable detachable on display	